





## Supreme transfer speeds

Transcend's PCIe SSD 220S follows NVMe 1.3 and utilizes the PCIe™ Gen3 x4 interface, meaning four lanes are used for transmitting and receiving data simultaneously. Its 8-channel controller supports ultra high data throughput, resulting in compelling performance of up to 3,500MB/s read and 2,700MB/s write.



# Understanding the PCIe interface

PCIe (or PCI Express®) is a much faster interface than SATA (or Serial ATA) for connecting a host computer to solid-state storage devices over one or more lanes consisting of one transmit and one receive serial interface in each lane, meaning it can better fulfill new performance requirements.



# Understanding the NVMe standard

NVMe (or NVM Express®) is a host controller interface standard designed to address the needs of enterprise and client applications that utilize PCI Express-based solid-state storage. NVMe calls for better performance vectors than AHCI (Advanced Host Controller Interface), including scalable bandwidth, increased IOPS, and low latency.





## PCIe M.2 SSDs

# PCIe SSD 220S

#### **Features**

- Adopts PCIe Gen3 x4 interface and NVMe
   1.3 standard
- · Up to 3,500 MB/s read; 2,700 MB/s write
- · 3D NAND flash memory, 8-channel controller, and DDR3 DRAM cache
- Engineered with LDPC (Low-Density Parity Check) coding to ensure data integrity; built-in SLC caching technology for exceptional transfer speeds
- Engineered dynamic thermal throttling mechanism

# Transcend

# SSD Scope Software

Transcend SSD Scope is advanced, user-friendly software that makes it easy to ensure your Transcend SSD remains healthy, and continues to run fast and error-free by determining the condition and optimizing the performance of your drive.

# Specification

A	р	р	е	а	r	а	n	C	$\epsilon$
---	---	---	---	---	---	---	---	---	------------

Dimensions	80 mm x 22 mm x 3.58 mm (3.15" x 0.87" x 0.14")
Weight	10 g (0.35 oz)

#### Interface

Bus Interface NVMe PCle Gen3 x4

#### Storage

Flash Type 3D NAND flash
Capacity 256 GB / 512 GB / 1 TB / 2 TB

#### **Operating Environment**

Operating Temperature  $0^{\circ}\text{C } (32^{\circ}\text{F}) \sim 70^{\circ}\text{C } (158^{\circ}\text{F})$ Operating Voltage  $3.3\text{V}\pm5\%$ 

#### Performance

Sequential Read/Write Read: 3,500 MB/s (CrystalDiskMark, max.) Write: 2,700 MB/s

4K Random Read/Write Read: 340,000 IOPS (IOmeter, max.) Write: 310,000 IOPS

Mean Time Between Failures 3,000 000 bour(s)

(MTBF) 2,000,000 hour(s)

Terabytes Written (TBW) 4,400 TB

Drive Writes Per Day (DWPD) 1.2 (5 yrs)

Note • Speed may vary due to host hardware, software, usage, and storage capacity.

• Some motherboards only provide PCle x2 connections for the M.2 slot, creating a bottleneck on even the fastest drives.

## Warranty

Certificate	CE/FCC/BSMI/KC/RCM
Warranty	Five-year Limited Warranty

## **Ordering Information**

256GB	TS256GMTE220S
512GB	TS512GMTE220S
1TB	TS1TMTE220S
2TB	TS2TMTE220S



# PCIe M.2 SSDs Comparison





PCIe SSD 220S

PCIe SSD 110S

	PCIe SSD 220S	PCIe SSD 110S	
Appearance			
Dimensions	80 mm x 22 mm x 3.5	58 mm (3.15" x 0.87" x 0.14")	
Weight	10 g (0.35 oz)	8 g (0.28 oz)	
nterface			
Bus Interface	NVMe PCIe Gen3 x4		
Storage			
Flash Type	3D NAND flash		
Capacity	256 GB/512 GB/1 TB/2 TB	128 GB/256 GB/512 GB/1 TB	
Operating Environment			
Operating Temperature	0°C (32°F) ~ 70°C (158°F)		
Operating Voltage	3.3V±5%		
Performance			
Sequential Read/Write CrystalDiskMark, max.)	Read: 3,500 MB/s Write: 2,700 MB/s	Read: 1,700 MB/s Write: 1,400 MB/s	
4K Random Read/Write (IOmeter, max.)	Read: 340,000 IOPS Write: 310,000 IOPS	Read: 160,000 IOPS Write: 140,000 IOPS	
Mean Time Between Failures (MTBF)	2,000,000 hour(s)	2,000,000 hour(s)	
Terabytes Written (Max.)	4,400 TB	400 TB	
Drive Writes Per Day (DWPD)	1.2 (5 yrs)	0.2 (5 yrs)	
Warranty			
Warranty	Five-year Limited Warranty		
Technology			
S.M.A.R.T.	<b>✓</b>	<b>✓</b>	
DDR3 DRAM Cache	<b>✓</b>	-	
Advanced Garbage Collection	✓	<b>✓</b>	
RAID Engine	✓	-	
DDC Carling	,	,	

 $<sup>{}^{\</sup>star}\mathsf{Speed}$  may vary due to host hardware, software, usage, and storage capacity.