

# GES-2105P Hilbert 5-Port Gigabit PoE Smart Lite Switch, 802.3at/af PoE, 4 PoE Outputs, 60W PoE Power Budget

## Product Images

---



## Short Description

---

- 4 PoE-Plus Gigabit Ethernet ports supports PoE Watchdog
- Total PoE power budget: 60W, up to 30W per port
- IEEE 802.3af/at PoE compliant to simplify deployment and installation
- 1000Mbps full-duplex, 10/100Mbps full/half-duplex, auto-negotiation, auto-MDI/MDIX
- Supports 2K MAC address auto-learning and auto-aging
- 9K jumbo frames to increase data transfer rates

- IP Multicast Filtering through IGMP Snooping V1 / V2
- 802.1Q tag-based VLAN allows network segmentation to enhance performance and security
- IEEE 802.1p QoS with 4 priority queues
- Supports unknown unicast / broadcast / multicast storm control
- Minimize carbon footprint with advanced energy efficient technology (IEEE 802.3az)
- 4KV surge protection, 6KV contact / 8KV air ESD protection
- Web-based and smart lite Management
- Supports LevelOne IP Locator for easier IP management.

## Description

---

The LevelOne GES-2105P Hilbert Gigabit PoE Smart Lite switch is a next-generation Ethernet Switch offering powerful better PoE functionality and usability that delivers the cost-effectively business and transports Ethernet services via copper connections. GES-2105P delivers 5 (10M/100M/1G) RJ45 with 4 PoE+ (Support 802.3at/af, and total up to 60W) ports. can be matched with the latest LevelOne IP Locator, the software is the easiest to use switch discovery tool, it can search all Hilbert series switches, instantly know the forgotten IP and other info. Compatible with mainstream Windows and Mac operating systems.

The LevelOne GES-2105P provides high HW performance and environment flexibility for Enterprises. GES-2105P is ideal to deliver management simplicity, optimum user experience, and lower total cost of ownership.

## Additional Information

---

Approval and compliance	UKCA, CE, FCC Class A, RoHS
Operating humidity	10% RH ~ 90% RH
Operating temperature	0°C ~ 45°C
Storage humidity	5% RH ~ 95% RH
Storage temperature	-40°C ~ 70°C
Embedded system	SoC
Acoustic noise (dB)	0 dB (A)
Packet buffer	1.5 Mbits
Jumbo frame (KB)	9 K
MAC address table	2 K
Flash memory size	2 MB
Mount	Desk mount
Pin assignment and polarity	1/2 (+), 3/6 (-)
Power supply	54 VDC, 1.2A 64.8W
Standards	<ul style="list-style-type: none"> <li>● IEEE 802.3 10-BASE-T (Ethernet)</li> <li>● IEEE 802.3u 100-BASE-TX (Fast Ethernet)</li> <li>● IEEE 802.3ab 1000BASE-T (Gigabit Ethernet)</li> <li>● IEEE 802.3x Flow Control (full-duplex flow control)</li> <li>● IEEE 802.3af Power over Ethernet</li> <li>● IEEE 802.3at Power over Ethernet Plus</li> <li>● IEEE 802.3az: Energy Efficient Ethernet</li> </ul>
Port Configuration	5

Features	L2 Switching Features ● IGMP Snooping ● Link Aggregation (Supports static link aggregation) ● Port Mirroring ● Cable Test VLAN ● Supports up to 32 VLANs (out of 4K VLAN IDs) ● MTU/Port/802.1Q VLAN Quality of Service (QoS) ● Support Port-based/802.1p/DSCP priority ● Support 4 priority queues ● Rate Limit ● Storm Control
Management	● Web-based Graphic User Interface (GUI) ● Supports LevelOne IP Locator for easier IP management.
Product weight (kg)	0.4 kg
Color	Black
EAN	4015867229194
Model number	GES-2105P
Package contents	● GES-2105P ● Power adapter with power cord ● Quick Installation Guide ● Declaration of Conformity
Switching capacity	10 Gbps
Grade	Commercial
Data Rate	Gigabit Ethernet
PoE Supported	Yes
Manageable	Yes
Fanless	Yes
Concurrent ports	Total5.00
Series	HILBERT series
PoE Power Budget	Total60.00
Power consumption	65W (full loading/PoE on)
Heat dissipation	23.88 (Btu/H)
MTBF	43,800 hrs

