



i-tec USB-C HDMI Dual DP Docking Station with Power Delivery 100 W

Brand : i-tec

Product code: C31TRIPLE4KDOCKPDPRO

Product name : USB-C HDMI Dual DP Docking Station with Power Delivery 100 W

- Compatible with USB-C, USB4 and Thunderbolt laptops & tablets. (The host device must support DisplayPort Alt mode)
 - 2x DisplayPort++ and 1x HDMI supporting up to three 4K or a single 5K/60Hz display (depending on notebook performance). macOS supports a single extended display only
 - 6x USB-ports (5x USB-A, 1x USB-C) make it easy to connect multiple USB devices and peripherals
 - Provides up to 100W Power Delivery for compatible USB-C, USB4 and Thunderbolt laptops & tablets. The host device must support USB-C Power Delivery
 - GLAN Ethernet supports network speeds of 10/100/1000 Mbps speeds, providing a robust and high-speed internet connection
 - Combo 3.5 mm audio input/output jack for easy connection to headset or speakers
 - VESA bracket available to help keep your desk tidy and free from cables, plus K-lock slot for added security
 - Power-saving On/Off switch to reduce energy consumption when the docking station is not in use
- USB-C HDMI Dual DP Docking Station with Power Delivery 100 W



Ports & interfaces		Power	
Connectivity technology *	Wired	USB cable length	1 m
Host interface *	USB 3.2 Gen 1 (3.1 Gen 1) Type-C	Software	
USB 2.0 ports quantity *	2	Windows operating systems supported	✓
USB 3.2 Gen 1 (3.1 Gen 1) Type-A ports quantity *	3	Mac operating systems supported	✓
USB 3.2 Gen 2 (3.1 Gen 2) Type-C ports quantity	2	Linux operating systems supported	✓
HDMI ports quantity *	1	Mobile operating systems supported	Android, iOS
DisplayPorts quantity	2	Other operating systems supported	ChromeOS
DisplayPort version	1.4	Operational conditions	
Combo headphone/mic port	✓	Operating temperature (T-T)	0 - 40 °C
Network		Operating relative humidity (H-H)	10 - 100%
Ethernet LAN *	✓	Weight & dimensions	
Ethernet LAN (RJ-45) ports	1	Width	113 mm
Ethernet LAN data rates	10,100,1000 Mbit/s	Depth	113 mm
Performance		Height	31.2 mm
Card reader integrated *	✗	Weight	340 g
Data transfer rate	10 Gbit/s	Packaging content	
Number of displays supported	3	AC adapter included	✗
Maximum refresh rate	144 Hz	Manual	✓
Cable lock slot	✓		
Cable lock slot type	Kensington		
Product colour *	Black		
On/off switch	✓		
LED indicators	✓		



8595611705816

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 27-OCT-2024. Prints or copies of Information are only valid on the printed Publication date