Allied Telesis AT-GS910/16 Unmanaged Gigabit Ethernet (10/100/1000) Grey

Brand : Allied Telesis

Product code: AT-GS910/16-50

Product name : AT-GS910/16

16 x RJ-45, 524 KB, MDI/MDI-X, 10/100/1000T, 100 - 240 V, 50 - 60 Hz, IEEE 802.3/ 802.3u/802.3ab, 802.3x, 802.3az
Allied Telesis AT-GS910/16. Switch type: Unmanaged. Basic switching RJ-45 Ethernet ports type: Gigabit Ethernet (10/100/1000), Basic switching RJ-45 Ethernet ports quantity: 16. Full duplex. MAC address table: 8000 entries, Switching capacity: 32 Gbit/s. Networking standards: IEEE 802.3, IEEE 802.3ab, IEEE 802.3az, IEEE 802.3u, IEEE 802.3x. Wall mountable

Management features	
Switch type *	Unmanaged
Ports & interfaces	
Basic switching RJ-45 Ethernet ports quantity *	16
Basic switching RJ-45 Ethernet ports type *	Gigabit Ethernet (10/100/1000)
Gigabit Ethernet (copper) ports quantity	16
Compatible memory cards	Not supported
Network	
Networking standards *	IEEE 802.3, IEEE 802.3ab, IEEE 802.3az, IEEE 802.3u, IEEE 802.3x
10G support *	✗
Copper ethernet cabling technology	10BASE-T, 100BASE-T, 1000BASE-T
Full duplex	✓
IP routing	✓
Flow control support	✓
Auto MDI/MDI-X	✓
Auto-negotiation	✓
Data transmission	
Switching capacity *	32 Gbit/s
Throughput	23.8 Mpps
MAC address table *	8000 entries
Jumbo frames support	✓
Jumbo frames	10000
Packet forwarding rate (1 Gbps)	1488000 pps
Packet forwarding rate (100 Mbps)	148800 pps
Packet forwarding rate (10 Mbps)	14880 pps
Security	
DHCP features	DHCP client
SSH/SSL support	✓

Security	
Loop protection	✓
BPDU filtering/protection	✓
Design	
Product colour	Grey
Housing material	Metal
Wall mountable	✓
Safety	UL60950-1, 2nd Edition CSA C22.2 No.60950-1-07, 2nd Edition IEC60950-1(UL-EU, UL-CB)
Performance	
Buffer size	524 KB
Power	
AC input voltage	100 - 240 V
AC input frequency	50 - 60 Hz
Output current	0.3 A
Power consumption (max)	12 W
Power plug type	Type C
Power over Ethernet (PoE)	
Power over Ethernet (PoE) *	✗
Operational conditions	
Operating temperature (T-T)	0 - 50 °C
Weight & dimensions	
Width	263 mm
Depth	179 mm
Height	380 mm
Weight	1.5 kg
Packaging content	
Quick start guide	✓
User guide	✓
Packaging data	
Mounting brackets included	✓
Certificates	
Certification	EAC certification EN55024 ICES Class A VCCI Class A FCC Class A RCM CE EN55022 CISPR 55022 RoHS
Logistics data	
Harmonized System (HS) code	85176990

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 31-OCT-2024. Prints or copies of Information are only valid on the printed Publication date