StarTech.com

StarTech.com DK31C3MNCRUE laptop dock/port replicator Wired USB 3.2 Gen 2 (3.1 Gen 2) Type-C

Brand : StarTech.com

Product name : DK31C3MNCRUE

Product code: DK31C3MNCRUE

StarTech.com USB-C Docking Station - Multi Monitor HDMI/DP/DP Alt Mode USB-C Dock - 3x 4K30 / 2x 4K60 - 7-Port USB Hub - 60W Power Delivery - GbE - 3.5mm Audio - Works With Chromebook certified - TAA
StarTech.com DK31C3MNCRUE. Connectivity technology: Wired, Host interface: USB 3.2 Gen 2 (3.1 Gen 2) Type-C, USB Power Delivery up to: 60 W. Ethernet LAN data rates: 10,100,1000 Mbit/s. Data transfer rate: 10 Gbit/s, HD type: 5K Ultra HD, Maximum digital resolution: 5120 x 2880 pixels. AC input voltage: 100 - 240 V, Input current: 2.37 A, Output voltage: 20 V. Width: 80 mm, Depth: 210 mm, Height: 32 mm

Ports & interfaces

Connectivity technology *	Wired
Host interface *	USB 3.2 Gen 2 (3.1 Gen 2) Type-C
USB 2.0 ports quantity *	2
USB 3.2 Gen 2 (3.1 Gen 2) Type-A ports quantity	3
USB 3.2 Gen 2 (3.1 Gen 2) Type-C ports quantity	1
USB Power Delivery	✔
USB Power Delivery revision	3.0
USB Power Delivery up to	60 W
HDMI ports quantity *	2
HDMI version	2.0b
DisplayPorts quantity	2
DisplayPort version	1.4
Combo headphone/mic port	✔
Headphone outputs *	1
Headphone connectivity	3.5 mm
USB Type-C DisplayPort Alternate Mode	✔

Network

Ethernet LAN *	✔
Ethernet LAN (RJ-45) ports	1
Ethernet LAN data rates	10,100,1000 Mbit/s

Performance

Data transfer rate	10 Gbit/s
HD type	5K Ultra HD
Maximum digital resolution	5120 x 2880 pixels
Maximum refresh rate	60 Hz

Performance

Cable lock slot	✔
Cable lock slot type	Kensington
LED indicators	Network, Power

Power

AC input voltage	100 - 240 V
Input current	2.37 A
Output voltage	20 V
Output current	6.75 A
Power consumption (typical)	135 W
Compatible power plug types	EU, UK

Operational conditions

Operating temperature (T-T)	0 - 40 °C
Storage temperature (T-T)	-20 - 70 °C
Operating relative humidity (H-H)	0 - 95%

Sustainability

Sustainability compliance	✔

Weight & dimensions

Width	80 mm
Depth	210 mm
Height	32 mm

Packaging content

Cables included	USB Type-C to USB Type-C
AC adapter included	✔
Quick start guide	✔

Technical details

Compliance certificates	CE, RoHS

Other features	
Chipset	Synaptics - VMM5320, Realtek - RTS5420, Parade - PS8469, Parade - PS8468, Parade - PS8805, Parade - PS8803, VIA/VLI - VL822 Realtek - ALC5686, VIA/VLI - VL211, Realtek - RTL8153B

0065030898133

065030898133