Canon i-SENSYS MF553DW Laser A4 1200 x 1200 DPI 43 ppm Wi-Fi

Brand : Canon

Product family: i-SENSYS


Product code: 5160C019

Product name : MF553DW

A4, 43ppm, 1200 x 1200 dpi, Secure PIN print, LCD Colour Touch Screen, USB 2.0, LAN, WLAN, 220-240V Canon i-SENSYS MF553DW. Print technology: Laser, Printing: Mono printing, Maximum resolution: 1200 x 1200 DPI. Copying: Mono copying, Maximum copy resolution: 600 x 600 DPI. Scanning: Colour scanning, Optical scanning resolution: 600 x 600 DPI. Faxing: Mono faxing. Duplex functions: Copy, Print, Scan. Maximum ISO A-series paper size: A4. Wi-Fi. Direct printing. Product colour: Black, White

Printing		Paper handling	
Print technology *	Laser	ISO A-series sizes (A0A9) *	A4, A5, A6
Printing * Duplex printing *	Mono printing	ISO B-series sizes (B0B9)	B5 Executive, Legal, Letter, Oficio,
Maximum resolution *	1200 x 1200 DPI	Non-ISO print media sizes	Statement
Print speed (black, normal quality,		Envelopes sizes	C5, Com-10, DL, Monarch
A4/US Letter) *	43 ppm	Paper tray media weight	60 - 120 g/m ²
Warm-up time	14 s	Multi-Purpose Tray media weight	60 - 199 g/m²
Time to first page (black, normal) Secure printing	5.7 s	Ports & interfaces	
	•	Direct printing *	✓
Copying		USB port	
Duplex copying *	✓ Mone conving	USB 2.0 ports quantity	1
Copying * Maximum copy resolution *	Mono copying 600 x 600 DPI	Network	
Maximum number of copies	999 copies	Wi-Fi *	✓
Copier resize	25 - 400%	Ethernet LAN *	1
N-in-1 copy function	1	Cabling technology	10/100/1000Base-T(X)
N-in-1 copy function (N=)	2, 4	Ethernet LAN data rates	10,100,1000 Mbit/s
ID-card copy function		Wi-Fi standards	802.11b, 802.11g, Wi-Fi 4 (802.11n)
Scanning		Security algorithms	64-bit WEP, 128-bit WEP, WPA-AES, WPA-PSK, WPA-TKIP, WPA2-AES, WPA2-PSK, WPA2-TKIP
Duplex scanning *	 Image: A set of the set of the	Performance	
Scanning *	Colour scanning	Internal memory *	1024 MB
Optical scanning resolution *	600 x 600 DPI		1024 MB ✓
Scanner type *	ADF scanner	Built-in processor	
Scan to	Cloud, E-mail	Processor frequency Sound pressure level (printing)	800 MHz 54 dB
Image formats supported	JPEG, TIFF	Sound pressure level (standby)	24 dB
Document formats supported Input colour depth	PDF 24 bit		24 00
Output colour depth	24 bit	Design	
Greyscale levels	256	Product colour *	Black, White
Scan drivers	ICA, TWAIN, WIA	Market positioning *	Business
Fax		Built-in display *	
	M 6. 1	Display	LCD
Faxing * Fax resolution (black)	Mono faxing 200 x 100 DPI	Control type	Touch
Modem speed	33.6 Kbit/s	Colour display	✓
Fax memory	512 pages	Power	
Speed dialling	 ✓ 	Power consumption (max)	1430 W
		Power consumption (printing)	590 W
Features		Power consumption (standby)	13.6 W
Recommended duty cycle	2000 - 75000 pages per month	Power consumption (sleep)	0.9 W
Maximum duty cycle * Duplex functions *	150000 pages per month Copy, Print, Scan	Energy Star Typical Electricity Consumption (TEC)	0.41 kWh/week
Printing colours *	Black	AC input voltage	220 - 240 V
Page description languages Printer fonts	PCL 5e, PCL 6, PostScript 3, UFRII PCL, PostScript	AC input frequency	50 - 60 Hz

Input & output capacity		System requirements	
Total number of input trays * Total input capacity *	1 550 sheets	Windows operating systems supported Mac operating systems supported	Windows 10, Windows 11, Windows 8.1
Total output capacity *	150 sheets		Mac OS X 10.11 El Capitan, Mac OS X 10.12 Sierra, Mac OS X 10.13 High Sierra, Mac OS X 10.14 Mojave, Mac OS X 10.15 Catalina, Mac OS X 10.15.3 Catalina, Mac OS X 10.2 Jaguar, Mac OS X 10.3 Panther, Mac OS X 10.4 Tiger, Mac OS X 10.5 Leopard, Mac OS X 10.6 Snow Leopard, Mac OS X 10.7 Lion, Mac OS X 10.8 Mountain Lion, Mac OS X 10.9 Mavericks, Mac OS X 11.0 Big Sur
Multi-Purpose tray	1		
Multi-Purpose tray input capacity	100 sheets		
Auto document feeder (ADF)	1		
Auto document feeder (ADF) input capacity	50 sheets		
Maximum input capacity	2300 sheets		
Paper handling			
Maximum ISO A-series paper size *	A4 Envelopes, Heavy paper, Labels,	Linux operating systems supported	✓
Paper tray media types *	Plain paper, Postcard, Recycled paper, Thin paper	Server operating systems supported	Windows Server 2008, Windows Server 2008 R2, Windows Server 2012, Windows Server 2012 R2, Windows Server 2016, Windows Server 2019
		Operational conditions	
		Operating relative humidity (H-H)	20 - 80%
		Storage temperature (T-T)	10 - 30 °C
		Weight & dimensions	
		Width	494 mm
		Depth	464 mm
		Height	452 mm
		Weight	19.8 kg



8714574670324

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.