## KYOCERA ECOSYS P4140dn 1200 x 1200 DPI A3

Brand: KYOCERA Product code: 1102Y43NL0

Product name: ECOSYS P4140dn

- Double-sided print
- Toner save mode
- Beneficial for the environment with long-life components and low energy consumption
- Print using direct Wi-Fi

A3, 40/22 ppm,  $1200 \times 1200$  DPI, ARM Cortex-A9 1200 MHz, USB 2.0, Ethernet, 220/240 VAC, 50/60 Hz,  $477 \times 410 \times 343$  mm, 21 kg

## KYOCERA ECOSYS P4140dn 1200 x 1200 DPI A3:

This compact A3 black and white printer offers an expandable paper capacity of up to 6 paper trays for flexible paper handling. Plus this device knows exactly how to impress with comprehensive standard security features for optional SSD and ECOSYS long-life technology.

KYOCERA ECOSYS P4140dn. Print technology: Laser. Number of print cartridges: 1, Maximum duty cycle: 150000 pages per month. Maximum resolution: 1200 x 1200 DPI. Maximum ISO A-series paper size: A3. Print speed (black, normal quality, A4/US Letter): 40 ppm, Duplex printing. Display: LCD. Network ready. Product colour: Black, White





Printing		Network	
Duplex printing mode	Auto	Near Field Communication (NFC)	×
Print resolution black	1200 x 1200 DPI	Bluetooth	×
Colour *	×		Apple AirPrint, Google Cloud Print,
Print technology *	Laser	Mobile printing technologies	Kyocera Mobile Print, Mopria Print Service
Duplex printing *	✓		Service
Maximum resolution *	1200 x 1200 DPI	Performance	
Print speed (black, normal quality, A4/US Letter) *	40 ppm	Internal memory *  Maximum internal memory	512 MB 2500 MB
Print speed (black, normal quality, A3)	22 ppm	Built-in processor	✓
Duplex print speed (black, normal quality, A4/US Letter)	28 ppm	Processor family Processor model	ARM Cortex A9
Warm-up time	18 s	Processor frequency	1200 MHz
Time to first page (black, normal)	6.3 s	Sound pressure level (printing)	50.7 dB
Watermark printing	✓	Sound pressure level (quiet mode)	47.9 dB
Secure printing	✓	Design	
Features		Market positioning *	Business
Maximum duty cycle *	150000 pages per month	Product colour *	Black, White
Recommended duty cycle	10000 - 15000 pages per month	Built-in display *	✓
Printing colours *	Black	Display	LCD
Number of print cartridges *	1		
	1	Colour display	×
	Epson LQ, IBM ProPrinter XL24E,	Control type	Buttons
Page description languages *	Epson LQ, IBM ProPrinter XL24E, JPEG, OpenXPS, PCL 5c, PCL 6, PDF	' '	
Page description languages * Printer fonts	Epson LQ, IBM ProPrinter XL24E, JPEG, OpenXPS, PCL 5c, PCL 6, PDF 1.7, TIFF, XPS	Control type	Buttons
	Epson LQ, IBM ProPrinter XL24E, JPEG, OpenXPS, PCL 5c, PCL 6, PDF	Control type Certification	Buttons
Printer fonts	Epson LQ, IBM ProPrinter XL24E, JPEG, OpenXPS, PCL 5c, PCL 6, PDF 1.7, TIFF, XPS Barcode, Bitmap, PCL	Control type Certification  Power	Buttons TÜV, GS, CE
Printer fonts Number of PCL fonts	Epson LQ, IBM ProPrinter XL24E, JPEG, OpenXPS, PCL 5c, PCL 6, PDF 1.7, TIFF, XPS Barcode, Bitmap, PCL 93	Control type Certification  Power  Power consumption (printing) *	Buttons TÜV, GS, CE
Printer fonts Number of PCL fonts Number of barcode fonts	Epson LQ, IBM ProPrinter XL24E, JPEG, OpenXPS, PCL 5c, PCL 6, PDF 1.7, TIFF, XPS Barcode, Bitmap, PCL 93	Control type Certification  Power  Power consumption (printing) * Power consumption (max)	Buttons TÜV, GS, CE 632 W 1415 W
Printer fonts Number of PCL fonts Number of barcode fonts Number of bitmap fonts	Epson LQ, IBM ProPrinter XL24E, JPEG, OpenXPS, PCL 5c, PCL 6, PDF 1.7, TIFF, XPS Barcode, Bitmap, PCL 93 79	Control type Certification  Power  Power consumption (printing) * Power consumption (max) Power consumption (ready) Power consumption (standby) Power consumption (off)	Buttons TÜV, GS, CE 632 W 1415 W 15 W
Printer fonts Number of PCL fonts Number of barcode fonts Number of bitmap fonts Linear (1D) barcodes supported Country of origin Replacement cartridges	Epson LQ, IBM ProPrinter XL24E, JPEG, OpenXPS, PCL 5c, PCL 6, PDF 1.7, TIFF, XPS Barcode, Bitmap, PCL 93 79 1 EAN 128, EAN-13, EAN-8, PDF417	Control type Certification  Power  Power consumption (printing) * Power consumption (max) Power consumption (ready) Power consumption (standby)	Buttons TÜV, GS, CE 632 W 1415 W 15 W
Printer fonts Number of PCL fonts Number of barcode fonts Number of bitmap fonts Linear (1D) barcodes supported Country of origin	Epson LQ, IBM ProPrinter XL24E, JPEG, OpenXPS, PCL 5c, PCL 6, PDF 1.7, TIFF, XPS Barcode, Bitmap, PCL 93 79 1 EAN 128, EAN-13, EAN-8, PDF417 Vietnam	Control type Certification  Power  Power consumption (printing) * Power consumption (max) Power consumption (ready) Power consumption (standby) Power consumption (off) Energy Star Typical Electricity	Buttons TÜV, GS, CE 632 W 1415 W 15 W 11 W

Input & output capacity		System requirements	
Total output capacity *	rs 5	Windows operating systems supported	Mac OS X 10.10 Yosemite, Mac OS X 10.11 El Capitan, Mac OS X 10.12
Multi-Purpose tray input capacity Maximum number of input trays		Mac operating systems supported	Sierra, Mac OS X 10.13 High Sierra, Mac OS X 10.14 Mojave, Mac OS X 10.15 Catalina, Mac OS X 10.9 Mavericks
	2600 sheets 750 sheets	Linux operating systems supported	✓
Paper handling	,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,	Operational conditions	
Maximum ISO A-series paper size * Maximum print size Paper tray media types * ISO A-series sizes (A0A9) * ISO B-series sizes (B0B9) Non-ISO print media sizes	A3 297 x 432 mm Plain paper, Thick paper A3, A4, A4+, A5, A6 B4, B5 Legal, Letter	Operating temperature (T-T) Storage temperature (T-T) Operating relative humidity (H-H) Storage relative humidity (H-H) Operating altitude Non-operating altitude	10 - 32.5 °C -20 - 40 °C 15 - 80% 10 - 90% 0 - 3500 m 0.6 - 15000 m
•	C5, DL	Sustainability	
•	70 - 148 mm	Sustainability certificates	Blue Angel, ENERGY STAR
	297 - 1220 mm	Weight & dimensions	
	60 - 120 g/m <sup>2</sup>	Width	477 mm
	60 - 220 g/m²	Depth	410 mm
Ports & interfaces		Height	343 mm
P	•	Weight	21 kg
p	<b>✓</b>	Packaging data	
	2 Ethernet, Parallel, Wireless LAN	Package width	581 mm
,	Ethernet, Faranci, Wheless LAN	Package depth Package height	542 mm 460 mm
Network		Package weight	26 kg
· · · · · · · · · · · · · · · · · · ·	<b>✓</b>	Packaging content	3
	X	Cartridge(s) included	<b>✓</b>
2	✓ 10/100/1000Base-T(X)	Included cartridge capacity (black)	7500 pages
	10/100/1000BaSe-1(A)	included curtilage capacity (black)	7300 pages
· · · · · · · · · · · · · · · · · · ·	10,100,1000 Mbit/s	Cables included	AC
· · · · · · · · · · · · · · · · · · ·	10,100,1000 Mbit/s	Cables included  Logistics data	AC









Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.