
Hardware Quick Reference LANCOM GS-3628XUP





Connect the configuration interface via the included serial configuration cable to the serial interface of the device you want to use for configuring / monitoring the switch.



TP Ethernet interfaces 10M / 100M / 1G PoE+

Use Ethernet cables to connect the interfaces 1 to 12 to your PC or a LAN switch.



TP Ethernet interfaces 100M / 1G / 2.5G PoE++

Use Ethernet cables to connect the interfaces 13 to 24 to your PC or a LAN switch.








Insert suitable LANCOM SFP modules into the SFP+ interfaces 25 to 28. Choose cables which are compatible with the SFP modules and connect them as described in the module's documentation.






Supply power to the device via the power connector. Please use the IEC power cable supplied or a country-specific LANCOM Power Cord.



**ATTENTION:** High touch current possible! Connect to earth before connecting the power supply.





1 System / Link/Act/Speed / PoE	
System: off	Device switched off
System: green	Device operational
System: red	Hardware error
Link/Act/Speed: green	Port LEDs show link / activity status or port speed
PoE: green	Port LEDs show PoE status

## Mode- / Reset button


Short press	Port LED mode switch	
~5 sec. pressed	Device restart	
Pressed until all port LEDs glow	Configuration reset and device restart	

### TP Ethernet ports 10M / 100M / 1G PoE+ LFDs switched to Link/Act/Speed mode

	4, 104, 00000
Off	Port inactive or disabled
Green	Link 1000 Mbps
Green, blinking	Data transfer, link 1000 Mbps
Orange	Link < 1000 Mbps
Orange, blinking	Data transfer, link < 1000 Mbps

## LEDs switched to PoE mode

Off	Port inactive or disabled
Green	Port enabled, power supply to connected device
Orange	Hardware error





## (4) TP Ethernet ports 100M / 1G / 2.5G PoE++

	LEDs switched to Link/Act/Speed mode	
	Off	Port inactive or disabled
	Green	Link 2500 - 1000 Mbps
or	Green, blinking	Data transfer, link 2500 - 1000 Mbps
	Orange	Link < 1000 Mbps
	Orange, blinking	Data transfer, link < 1000 Mbps
	LEDs switched to Do	r mada

LEDS SW	itcnea to	POE	moae
∩ff			Dort in

(5) SFP+ ports 1G / 10G

off	Port inactive or disabled
reen	Port enabled, power supply to
	connected device
range	Hardware error

Port inactive

Link 10 Gbps Link 1000 Mbps

# Hardware Power supply Environment

ETH	12 TP Ethernet ports 10 / 100 / 1000 Mbps PoE+ 12 TP Ethernet ports 10 / 100 / 2500 Mbps PoE++
SFP+	4 SFP+ ports 1 / 10 Gbps

Temperature range 0-40°C; short-term temperature range 0-50°C; humidity 10-90%, non-

Robust metal housing, 19" 1U (442 × 44 × 375 mm > W x H x D) with removable mounting

## Package Content

Number of fans

 Mounting brackets	2 19" brackets for rack mounting
 Cable	1 IEC power cord, 1 serial configuration cable 1.5 m

Internal power supply unit

brackets, network connectors on the front


Before initial startup, please make sure to take notice of the information regarding the intended use in the enclosed installation guide!

Operate the device only with a professionally installed power supply at a nearby power socket that is freely accessible at all times.

The power plug of the device must be freely accessible.

Please note that support for third-party accessories (SFP and DAC) is not provided.





→ The power plug of the device must be freely accessible.

→ For devices to be operated on the desktop, please attach the adhesive rubber footpads

→ Do not rest any objects on top of the device

→ Keep all ventilation slots on the side of the device clear of obstruction → Mount the device into a 19" unit in a server cabinet using the provided screws and mounting brackets.

Hereby, LANCOM Systems GmbH | Adenauerstrasse 20/B2 | D-52146 Wuerselen, declares that this device is in compliance with Directives 2014/30/EU, 2014/35/EU, 2011/65/EU, and Regulation (EC) No. 1907/2006. The full text of the EU Declaration of Conformity is available at the following Internet address: www.lancom-systems.com/doc