



## LG 49XE4F-M Digital signage flat panel 124.5 cm (49") LED 4000 cd/m<sup>2</sup> Full HD Black 24/7



Brand : LG

Product code: 49XE4F-M.AEU

Product name : 49XE4F-M

- Brightness(Typ.) : 4,000 cd/m<sup>2</sup>  
 - Bezel : 38.4 mm (T/B), 26.0 mm (L/R)  
 - Interface : HDMI/ DP/HDBaseT/USB/ Audio/ RS232C/ RJ45  
 - Anti-Reflection Coating  
 - IP56 Design, IK10 Protective Glass  
 49" IPS, M+(WRGB) 1920 x 1080 4000 cd/m<sup>2</sup>, 24/7, HDMI DP HDBaseT USB Audio RS232C RJ45  
 LG 49XE4F-M. Product design: Digital signage flat panel. Display diagonal: 124.5 cm (49"), Display technology: LED, Display resolution: 1920 x 1080 pixels, Display brightness: 4000 cd/m<sup>2</sup>, HD type: Full HD. Operating hours (hours/days): 24/7. Product colour: Black

Display		Design	
LED backlighting type	Direct-LED	Bezel width (bottom)	3.84 cm
Display diagonal *	124.5 cm (49")	Bezel width (side)	2.6 cm
Display technology *	LED	Bezel width (top)	3.84 cm
Display resolution *	1920 x 1080 pixels	<b>Performance</b>	
Display brightness *	4000 cd/m <sup>2</sup>	Purpose *	Universal
HD type *	Full HD	Operating hours (hours/days)	24/7
Touchscreen *	✗	International Protection (IP) code	IP56
Native aspect ratio	16:9	<b>Power</b>	
Response time	8 ms	Power consumption (typical) *	300 W
Contrast ratio (typical)	1300:1	Energy efficiency class (SDR)	A
Contrast ratio (dynamic)	500000:1	AC input voltage	100 - 240 V
Viewing angle, horizontal	178°	AC input frequency	50 - 60 Hz
Viewing angle, vertical	178°	<b>Weight &amp; dimensions</b>	
Panel life	50000 h	Display width	1153 mm
Haze rate	3%	Display depth	88 mm
<b>Ports &amp; interfaces</b>		Display height	656.2 mm
HDMI ports quantity *	2	Display weight	32 kg
HDMI input ports quantity	2	<b>Packaging data</b>	
DisplayPorts quantity *	1	Package width	1286 mm
USB port *	✓	Package depth	207 mm
USB ports quantity	2	Package height	797 mm
Ethernet LAN *	✓	Package weight	37 kg
Ethernet LAN (RJ-45) ports	2	<b>Packaging content</b>	
Audio (L/R) out	1	Remote control included	✓
RS-232C	✓	Cables included	AC, HDMI, RS-232
<b>Audio</b>		<b>Operational conditions</b>	
Built-in speaker(s) *	✗	Operating temperature (T-T)	-30 - 50 °C
<b>Design</b>		Operating relative humidity (H-H)	5 - 100%
Product design *	Digital signage flat panel	<b>Logistics data</b>	
Placement supported *	Indoor/outdoor	Harmonized System (HS) code	85285210
Orientation	Horizontal/Vertical		
Product colour *	Black		
VESA mounting *	✓		

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.