

AXIS Camera Station S2208 Appliance

All-in-one recorder with integrated 8 channel PoE switch for high-definition surveillance

AXIS Camera Station S2208 Appliance is an all-in-one recording solution with integrated, manageable PoE switch designed to deliver reliable high-definition surveillance with up to 4K resolution. For quick and easy installation, AXIS S2208 is preconfigured and preloaded with AXIS Camera Station video management software, and includes licenses for 8 channels plus all necessary system software. AXIS Camera Station offers an intuitive user interface that allows users to take full advantage of Axis wide range of video surveillance cameras and other IP products. With the operating system stored on a solid-state drive (SSD) and 3-year hardware warranty, AXIS S2208 provides a reliable surveillance solution.

- > All-in-one solution with integrated PoE switch
- > High-definition surveillance with up to 4K resolution
- > AXIS Camera Station licenses included
- > Full compatibility with Axis products



AXIS Camera Station S2208 Appliance

| | | |
|-------------------------|---|--|
| Licenses | Includes 8 AXIS Camera Station Core Device licenses | 8x PoE ports 10/100 Mbps |
| Processor | Intel® Core i3 | 1x SFP 10/100/1000 Mbps |
| Memory | 8 GB RAM | 1x RJ45 10/100/1000 Mbps |
| Storage | 4 TB (1x4 TB) Surveillance Class HDD Additional storage: 1 free bay | Rear side Server: |
| Switch | 8 ports integrated, 135 W total power budget Power over Ethernet (PoE) IEEE 802.3at Class 4 | 1x RJ45 10/100/1000 Mbps |
| Graphic card | Intel® HD Graphics 630 | 2x USB 2.0 |
| Operating system | Microsoft® Windows® 10 IoT Enterprise Operating system recovery: yes Operating system drive: 120 GB SSD | 1 Displayport™ |
| Video streaming | Live view: 1 x 4K stream full screen 4 split x 1080p Up to 8 cameras split view Supports two monitors, maximum one 4K monitor recommended Playback: Supports the same split scenarios as live view Supports only one monitor | 1 HDMI port |
| Recording | Qualified for recording with a total recording rate up to 192 Mbit per second | Operating conditions |
| Power | Max 270 W, 135 W PoE dedicated 100 – 240 V AC, 3.5 A, 50/60 Hz 54 V DC, 5 A External power adapter | 0 °C to 40 °C (32 °F to 104 °F) Humidity: 10–90% RH (non-condensing) |
| Connectors | Front side: 1x USB 3.0 1x Audio line in 1x Audio line out Rear side Switch: | Storage conditions |
| | | –40 °C to 65 °C (–40 °F to 149 °F) |
| | | Approvals |
| | | EMC CNS 13438, EAC, EN 55024, , EN 61000-3-2, EN 61000-3-3, EN 61000-6-1, EN 61000-6-2, FCC Part 15 Subpart B Class A, ICES-003 Class A, KC KN32 Class A, KC KN35, RCM AS/NZS CISPR 32 Class A, VCCI Class A Safety IEC/EN 60950-1, IEC/EN 62368-1, KC-Mark, UL 62368-1 |
| | | Dimensions |
| | | 330 x 230 x 78 mm (13 x 9.1 x 3.1 in) |
| | | Weight |
| | | 5.8 kg (12.8 lb) |
| | | Included accessories |
| | | Rack ears, power adapter |
| | | Optional accessories |
| | | Surveillance Hard Drive Axis desktop terminals Axis Ethernet surge protector For more accessories, see axis.com |
| | | Warranty |
| | | Axis 3-year warranty and AXIS Extended Warranty option, see axis.com/warranty |

AXIS Camera Station

For details about AXIS Camera Station features and functions, see the AXIS Camera Station datasheet on axis.com

Environmental responsibility:

www.axis.com/environmental-responsibility