

POLY Rove 20 Single Cell DECT 1880-1900 MHz B1 Base Station and 20 Phone Handset Kit

Brand: POLY Product code: 8F3E3AA

Product name: Rove 20 Single Cell DECT 1880-1900 MHz

B1 Base Station and 20 Phone Handset Kit

- Designed for busy professionals, Poly Rove 20 handsets emphasize usability, functionality, and style. Enjoy HD voice for lifelike conversations, customizable line keys, and effortless call parking.
- You shouldn't have to worry about outgrowing your communication solution or feel held back by its options. Poly Rove 20 wireless DECT™ IP phone solution has the flexibility to scale with handsets, bases, and repeaters as you grow.

Rove 20 Single Cell DECT 1880-1900 MHz B1 Base Station and 20 Phone Handset Kit

POLY Rove 20 Single Cell DECT 1880-1900 MHz B1 Base Station and 20 Phone Handset Kit:

We've got you covered

Keep the conversation going whenever, wherever in the office. Built for on-site employees the Poly Rove 20 wireless DECT $^{\text{m}}$ IP phone solution delivers the freedom to move and the flexibility to scale as you grow.

POLY Rove 20 Single Cell DECT 1880-1900 MHz B1 Base Station and 20 Phone Handset Kit. Type: DECT telephone. Speakerphone. Maximum indoor range: 50 m. Display diagonal: 5.08 cm (2"). Product colour: Black. Number of handsets included: 1





Performance		Power	
Type *	DECT telephone	Standby time	300 h
Maximum indoor range	50 m	Multimedia	
On/off key	✓	Voice codecs	G.165, G.168
Country of origin	China	Weight & dimensions	
Design		Width	552 mm
Product colour *	Black	Depth	127 mm
Elderly phone *	×	Height	263 mm
Keypad lock	✓	Weight	455 g
Anti-slip grip	✓	Packaging data	
Phone features		Package width	230 mm
Speakerphone *	✓	Package depth	173 mm
Microphone mute	✓	Package height	60 mm
Management features		Package weight	300 g
Navigation key	✓	Packaging content	
	•	Number of handsets included *	1
Display		Base station	✓
Display	TFT	Manual	✓
Display diagonal	5.08 cm (2") 128 x 160 mm	Headset included	✓
Display size (HxV) Built-in display *		Certificates	
		Certification	UL 62368-1
		CCI GIICGGOII	OL 02300-1

Power		Operational conditions	
AC adapter output voltage	5 V	Operating temperature (T-T)	-10 - 55 °C
AC adapter output current	1 A	Storage temperature (T-T)	-40 - 70 °C
Battery technology	Lithium-Ion (Li-Ion)	Operating relative humidity (H-H)	5 - 95%
Talk time	35 h		



















Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.