

# AXIS C1410 Mk II Network Mini Speaker

Speaker with wide-area coverage for voice messages

AXIS C1410 Mk II Network Mini Speaker is a discreet and affordable speaker that fits into smaller spaces and provides wide area audio coverage. It allows users to remotely warn off intruders before they commit a crime, to deliver instructions during an emergency or to make general announcements. Built-in memory supports pre-recorded messages, or personnel can respond to notifications with live speak. Digital signal processing (DSP) ensures clear sound. Open standards support easy integration with network video, access control, analytics, and VoIP. It also has a built-in PIR sensor for motion detection. AXIS C1410 Mk II is a standalone unit that can be placed almost anywhere, which supports a flexible, scalable and cost-effective approach to system design.

- > [All-in-one speaker system](#)
- > [Connects to standard network](#)
- > [Simple installation with PoE](#)
- > [Remote health testing](#)
- > [PIR sensor for motion detection](#)



# AXIS C1410 Mk II Network Mini Speaker

Audio hardware	
Enclosure	Sealed enclosure with 2.5 inches broadband dynamic cone speaker
Max sound pressure level	90 dB
Frequency response	100 Hz – 20 kHz
Coverage pattern	145° coaxial
Audio input/output	Built-in microphone (can be disabled)
Built-in microphone specification	50 Hz – 12 kHz
Amplifier description	Built-in 7 W Class D amplifier
Digital signal processing	Built-in and pre-configured
Audio management	
AXIS Audio Manager Edge	Built in: <ul style="list-style-type: none"><li>– Zone management allowing you to divide up to 200 speakers into 20 zones.</li><li>– Content management for music and live/pre-recorded announcements.</li><li>– Scheduling to decide when and where to play content.</li><li>– Content prioritization to ensure urgent messages interrupt the schedule.</li><li>– Health monitoring for remote discovery of system errors.</li><li>– User management to control who has access to what features.</li></ul> For more details, see the datasheet on <a href="https://axis.com/products/axis-audio-manager-edge/support">axis.com/products/axis-audio-manager-edge/support</a>
AXIS Audio Manager Pro	For larger and more advanced systems. Sold separately. For specifications, see the datasheet on <a href="https://axis.com/products/axis-audio-manager-pro/support">axis.com/products/axis-audio-manager-pro/support</a>
AXIS Audio Manager Center	AXIS Audio Manager Center is a cloud service for remote access and management of multi-site systems. For specifications, see the datasheet on <a href="https://axis.com/products/axis-audio-manager-center/support">axis.com/products/axis-audio-manager-center/support</a>
Audio software	
Audio streaming	One-way/two-way with optional half-duplex echo cancellation. Mono.
Audio encoding	AAC LC 8/16/32/48 kHz, G.711 PCM 8 kHz, G.726 ADPCM 8 kHz, Axis µ-law 16 kHz, WAV, MP3 in mono/stereo from 64 kbps to 320 kbps. Constant and variable bit rate. Sampling rate from 8 kHz up to 48 kHz.
System integration	
Application Programming Interface	Open API for software integration, including VAPIX®, One-click cloud connection, AXIS Camera Application Platform (ACAP).
Video management systems	Compatible with AXIS Companion, AXIS Camera Station, video management software from Axis' Application Development Partners available at <a href="https://axis.com/vms">axis.com/vms</a>
Mass notification	Singlewire InformaCast®, Intrado Revolution, Lynx, Alertus
Unified communication	Verified compatibility: SIP clients: 2N, Yealink, Cisco, Linphone, Grandstream PBX/SIP servers: Cisco Call Manager, Cisco BroadWorks, Avaya, Asterix, Grandstream Cloud service providers: Webex, Zoom
SIP	Supported SIP features: Secondary SIP server, IPv6, SRTP, SIPs, SIP TLS, DTMF (RFC2976 and RFC2833), NAT (ICE, STUN, TURN) RFC 3261: INVITE, CANCEL, BYE, REGISTER, OPTIONS, INFO DTMF (RFC 4733/RFC 2833)
Event conditions	Audio: audio clip playing, speaker test result Call: state, state change Device status: IP address blocked/removed, new IP address, network lost, system ready, live stream active, PIR sensor Edge storage: recording ongoing, storage disruption, storage health issues detected I/O: manual trigger, virtual input
MQTT: stateless Scheduled and recurring: schedule	
Event actions	Audio: run automatic speaker test Audio clips: play, stop LEDs: flash status LED, flash status LED while the rule is active Light and siren: run light profile, run light profile while the rule is active, stop activities MQTT: publish Notification: HTTP, HTTPS, TCP and email Recordings: record audio, record audio while the rule is active Security: erase configuration SNMP traps: send, send while the rule is active
Built-in installation aids	Test tone verification and identification
Functional monitoring	Auto Speaker Test (verification via built-in microphone)
Approvals	
Product markings	CSA, UL/cUL, UKCA, CE, KC, VCCI, RCM
Supply chain	TAA compliant
EMC	EN 55035, EN 55032 Class B, EN 61000-3-2, EN 61000-3-3, EN 61000-6-1, EN 61000-6-2, Australia/New Zealand: RCM AS/NZS CISPR 32 Class B Canada: ICES-3(B)/NMB-3(B) Japan: VCCI Class B Korea: KS C 9835, KS C 9832 Class B USA: FCC Part 15 Subpart B Class B
Safety	CAN/CSA C22.2 No. 62368-1 ed. 3, IEC/EN 62368-1 ed. 3
Environment	IEC/EN 60529 IP4X
Network	
Network protocols	IPv4/v6 <sup>a</sup> , HTTP, HTTPS, SSL/TLS, QoS Layer 3 DiffServ, FTP, SFTP, CIFS/SMB, SMTP, Bonjour, UPnP™, SNMP v1/v2c/v3 (MIB-II), DNS, DynDNS, NTP, RTSP, RTP, TCP, UDP, IGMPv1/v2/v3, RTCP, ICMP, DHCP, ARP, SOCKS, SSH, NTCIP, SIP
Cybersecurity	
Edge security	Software: Signed OS, brute force delay protection, digest authentication, password protection, encrypted file system Hardware: Axis Edge Vault cybersecurity platform Secure element (CC EAL 6+), Axis device ID, secure keystore, secure boot
Network security	IEEE 802.1X (EAP-TLS, PEAP-MSCHAPv2), IEEE 802.1AE (MACsec PSK/EAP-TLS), IEEE 802.1AR, HTTPS/HSTS, TLS v1.2/v1.3, Network Time Security (NTS), X.509 Certificate PKI, host-based firewall
Documentation	AXIS OS Hardening Guide Axis Vulnerability Management Policy Axis Security Development Model AXIS OS Software Bill of Material (SBOM) To download documents, go to <a href="https://axis.com/support/cybersecurity/resources">axis.com/support/cybersecurity/resources</a> To read more about Axis cybersecurity support, go to <a href="https://axis.com/cybersecurity">axis.com/cybersecurity</a>
System on chip (SoC)	
Model	NXP i.MX 8M Nano
Memory	1024 MB RAM, 1024 MB Flash
General	
Casing	Plastic casing, IP40 rated Colors: White Repaintable. For repainting instructions and impact on warranty, contact your Axis partner.
Mounting option	When you mount the device on a soft tile ceiling, use a plate behind the tile for reinforcement.
Power	Power over Ethernet (PoE) IEEE 802.3af/802.3at Type 1 Class 3 (max 12.95 W)
Connectors	RJ45 10BASE-T/100BASE-TX PoE
LED indicators	Status LED, front-facing LED
PIR sensor	Passive infrared (PIR) motion sensor Max range: 6 m (19.7 ft)

<b>Operating conditions</b>	-20 °C to 50 °C (4 °F to 122 °F) Humidity 10–85% RH (condensing)
<b>Storage conditions</b>	-40 °C to 65 °C (-40 °F to 149 °F) Humidity 5–95% RH (non-condensing)
<b>Dimensions</b>	For the overall product dimensions, see the dimension drawing in this datasheet. Ø182 X 52 mm (7.2 x 2.1 in)
<b>Weight</b>	600 g (1.3 lb)
<b>Box content</b>	Speaker, installation guide, Owner Authentication Key
<b>Optional accessories</b>	AXIS T91A33 Lighting Track Mount, AXIS T91A23 Tile Grid Ceiling Mount, AXIS TC1601 Universal Mount For more accessories, see <a href="https://axis.com">axis.com</a>
<b>Languages</b>	English, German, French, Spanish, Italian, Russian, Simplified Chinese, Japanese, Korean, Portuguese, Polish, Traditional Chinese, Dutch, Czech, Swedish, Finnish, Turkish, Thai, Vietnamese
<b>Warranty</b>	5-year warranty, see <a href="https://axis.com/warranty">axis.com/warranty</a>
<b>Part numbers</b>	Available at <a href="https://axis.com/products/axis-c1410-mk-ii#part-numbers">axis.com/products/axis-c1410-mk-ii#part-numbers</a>
<b>Tools</b>	
<b>Design</b>	AXIS Site Designer

	Available at <a href="https://axis.com">axis.com</a>
<b>Installation</b>	AXIS Device Manager, product selector, accessory selector Available at <a href="https://axis.com">axis.com</a>
<b>Sustainability</b>	
<b>Substance control</b>	PVC free in accordance with JEDEC/ECA Standard JS709 RoHS in accordance with EU RoHS Directive 2011/65/EU/ and EN 63000:2018 REACH in accordance with (EC) No 1907/2006. For SCIP UUID, see <a href="https://axis.com/partner">axis.com/partner</a> .
<b>Materials</b>	Renewable carbon-based plastic content: Up to 76% (recycled) Screened for conflict minerals in accordance with OECD guidelines To read more about sustainability at Axis, go to <a href="https://axis.com/about-axis/sustainability">axis.com/about-axis/sustainability</a>
<b>Environmental responsibility</b>	<a href="https://axis.com/environmental-responsibility">axis.com/environmental-responsibility</a> Axis Communications is a signatory of the UN Global Compact, read more at <a href="https://unglobalcompact.org">unglobalcompact.org</a>

a. Audio synchronization with IPv4 only.

Parameter	Unit	Reference data	5000-27500
Optical axis	°	64	5000-17,220
Crystal thickness	mm	0.05	5000-17,220