



The Right Size for Modern Business













ASUS NUC 13 Pro Mini PCs, Kits, and Boards deliver breakthrough performance and connectivity in a 4x4 device for productivity, collaboration, and edge compute. Drive enterprise-class performance with 12-core 13th Gen Intel® CoreTM processors, up to 64GB dual-channel memory and massive SSD capacity. Fast and flexible connectivity with Intel® Wi-Fi 6E (Gig+) and dual ThunderboltTM 4 ports are just a few of the many business-class features ASUS NUC 13 Pro offers. Select NUC 13 Pro SKUs feature Intel vPro® Enterprise for Windows with 13th Gen Intel® CoreTM processors, which provides performance, security, stability, and manageability features for managed businesses of all sizes.

Key Selling Points

- Pack the power of a full-size desktop PCs into a form factor small enough to hold in your hand
- Support a variety of uses including kiosks, multiple displays walls, meeting rooms, telehealth, and more.
- Get all the ports and wireless connections expected from a desktop PC−USB, HDMI, Thunderbolt[™] technology, 2.5 Gigabit Ethernet, Wi-Fi−in ASUS's industry-leading ultra-small form factor.
- Build on the Intel vPro® Platform for greater manageability, built -insecurity features, and stability to help lower costs by simplifying IT administration and increasing uptime.

Audience:

• MSPs, resellers and professionals, Forwardthinking early adopters

Target Usages:

- NUC Pro Software Suite featuring Intel Watchdog Utility
- Display emulation









ASUS NUC 13 PRO

Image B

| lini-PC Specifications | | Image A Image B | |
|------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--|
| Marketing Name | ASUS NUC 13 Pro Mini-PC | ASUS NUC 13 Pro Mini-PC | |
| Project Code | NUC13ANH-B / NUC13LCH-B | NUC13ANK-B / NUC13LCK-B | |
| Photo | Image A | Image B | |
| ASUS Logo | N/A | N/A | |
| ASUS NUC Logo | N/A | N/A | |
| Color | Black | Black | |
| OS Support | Windows 11 64-bit | Windows 11 Pro 64-bit | |
| CPU | Intel® Core™ i7-1360P Processor, cTDP 40W Intel® Core™ i5-1340P Processor, cTDP 40W Intel® Core™ i3-1315U Processor, cTDP 20W | Intel® Core™ i7-1360P Processor, cTDP 40W Intel® Core™ i5-1340P Processor, cTDP 40W Intel® Core™ i3-1315U Processor, cTDP 20W | |
| Chipset | Integrated | Integrated | |
| Graphics | Intel® Iris® Xe Graphics (i5/i7) Intel® UHD Graphics (i3) | Intel® Iris® Xe Graphics (i5/i7) Intel® UHD Graphics (i3) | |
| Memory | 2 x SO-DIMM, Up to DDR4-3200, 32GB*2 | 2 x SO-DIMM, Up to DDR4-3200, 32GB*2 | |
| Storage | 1 x M.2 2280 PCIe Gen4x4, supports 128GB~8TB NVMe™ SSD 1 x 2.5" SATA 6Gb/s, supports 4TB 7~15mm HDD 1 x SATA Power/DATA header for 2.5in SSD/HDD, supports 128GB~2TB SATA drive | 1 x M.2 2280 PCIe Gen4x4, supports 128GB~8TB NVMe™ SS 1 x 2.5" SATA 6Gb/s, supports 4TB 7~15mm HDD 1 x SATA Power/DATA header for 2.5in SSD/HDD, supports 128GB~2TB SATA drive | |
| Wireless Network | Intel® AX211 (Gig+), Wi-Fi 6E, Bluetooth 5.3 | Intel® AX211 (Gig+), Wi-Fi 6E, Bluetooth 5.3 | |
| LAN | Intel® Ethernet Controller I226-V, 2.5G | Intel® Ethernet Controller I226-V, 2.5G | |
| Audio | Realtek ALC269 | Realtek ALC269 | |
| TPM | fTPM or TPM 2.0 chip | fTPM or TPM 2.0 chip | |
| Card Reader | None | None | |
| HDMI CEC | Yes, 2 ports on back panel | Yes, 2 ports on back panel | |
| Front I/O Ports | 2 x USB 3.2 Gen2 Type-A 1 x 3.5mm Headset Jack | 2 x USB 3.2 Gen2 Type-A 1 x 3.5mm Headset Jack | |
| Back I/O Ports | 2 x Thunderbolt 4 Type-C w/ DisplayPort 1.4 1 x USB 3.2 Gen 2 Type-A 1 x USB 2.0 Type-A 2 x HDMI 2.1 (TMDS) 1 x RJ45 LAN 1 x DC-in | 2 x Thunderbolt 4 Type-C w/ DisplayPort 1.4 1 x USB 3.2 Gen 2 Type-A 1 x USB 2.0 Type-A 2 x HDMI 2.1 (TMDS) 1 x RJ45 LAN 1 x DC-in | |
| Side I/O Ports | 1 x Kensington Lock slot | 1 x Kensington Lock slot | |
| Power Supply | 20VDC, 6.0A, 120W Power Adapter (i7/i5 CPU) 19VDC, 4.74A, 90W Power Adapter (i3 CPU) | 20VDC, 6.0A, 120W Power Adapter (i7/i5 CPU) 19VDC, 4.74A, 90W Power Adapter (i3 CPU) | |
| Operating Temp | 0 to 40C | 0 to 40C | |
| Storage Temp | -40 to 60C | -40 to 60C | |
| Humidity | 0%-92% non-condensing ¹ | 0%-92% non-condensing ¹ | |
| mensions (W x D x H) | "H" 117 x 112 x 54 mm | "K" 117 x 112 x 37 mm | |
| Weights | ~610g | ~502g | |
| Accessories | AC Adapter + Power Cord ² VESA Bracket and Screws M3 Screws for 2.5in Drive Cable Clip Safety/Caution/Regulatory Insert Warranty Card | AC Adapter + Power Cord ² VESA Bracket and Screws Cable Clip Safety/Caution/Regulatory Insert Warranty Card | |
| | | | |

⁽¹⁾ Humidity Info detail please check link: Non-condensing humidity as defined by temperature vs dew point. (2) Power cord included is region specific, and some SKUs do not include the power cord









Image C

Image D

| Kit Specifications | | Image C | Image D | |
|------------------------|---------------------------------------------------------|-------------------------------------|--------------------------|--|
| Marketing Name | ASUS NUC 13 Pro Kit | ASIIS NIIC | 12 Dro Kit | |
| | | ASUS NUC 13 Pro Kit | | |
| Project Code | NUC13ANH-B / NUC13LCH-B | NUC13ANK-B / | | |
| Photo | Image C | Imag | e D | |
| ASUS Logo | N/A N/A | | A | |
| ASUS NUC Logo | N/A | N/A | | |
| Color | Black | Black | | |
| OS Support | Windows 11 64-bit | Windows | 11 64-hit | |
| | Windows 10 IoT Enterprise 64-bit | Windows 10 IoT E | | |
| | RedHat Enterprise Linux 9.1 64-bit | | • | |
| | Ubuntu 20.04/22.04 LTS 64-bit | RedHat Enterprise Ubuntu 20.04/2 | | |
| CPU | Obulitu 20.04/22.04 L13 04-bit | Obdittu 20.04/2 | 2.04 L13 04-DIL | |
| CPU | | Intel® Core™ i7-1370P Proc | essor w/ vPro, cTDP 40W | |
| | | Intel® Core™ i7-1370PE Pro | cessor w/ vPro, cTDP 40W | |
| | Intel® Core™ i7-1370P Processor w/ vPro, cTDP 40W | Intel® Core™ i7-1360P | Processor, cTDP 40W | |
| | Intel® Core™ i7-1360P Processor, cTDP 40W | Intel® Core™ i5-1350P Proc | essor w/ vPro, cTDP 40W | |
| | Intel® Core™ i5-1350P Processor w/ vPro, cTDP 40W | Intel® Core™ i5-1350PE | Processor, cTDP 40W | |
| | Intel® Core™ i5-1340P Processor, cTDP 40W | Intel® Core™ i5-1340P | Processor, cTDP 40W | |
| | Intel® Core™ i3-1315U Processor, cTDP 20W | Intel® Core™ i5-1340PE Pro | cessor w/ vPro, cTDP 40W | |
| | | Intel® Core™ i3-1315U | Processor, cTDP 20W | |
| | | Intel® Core™ i3-1315UE | Processor, cTDP 20W | |
| Chipset | Integrated | Integr | ated | |
| Graphics | Intel® Iris® Xe Graphics (i5/i7) | Intel® Iris® Xe G | raphics (i5/i7) | |
| · | Intel® UHD Graphics (i3) | Intel® UHD G | | |
| Memory | 2 x SO-DIMM, Up to DDR4-3200, 32GB*2 | 2 x SO-DIMM, Up to I | | |
| Storage | , , , , , , , , , , , , , , , , , , , , | 1 x M.2 2280 PCIe Gen4x4, supp | | |
| 2.0.1.00 | 1 x M.2 2280 PCIe Gen4x4, supports 128GB~8TB NVMe™ SSD | 1 x M.2 2242 PCIe x1, supp | | |
| | 1 x M.2 2242 PCIe x1, supports 128GB~1TB SATA SSD | 1 x SATA Power/DATA header for 2. | | |
| | 1 x 2.5" SATA 6Gb/s, supports 4TB 7~15mm HDD | SATA FOWER/DATA fleader for 2.5 | | |
| Wireless Network | * * * * * * * * * * * * * * * * * * * * | Intel® AX211 (Gig+), W | | |
| Wileless Network | Intel® AX211 (Gig+), Wi-Fi 6E, Bluetooth 5.3 | | ' | |
| LAN | Intel® vPro® Technology (i7/i5 vPro SKUs only) | Intel® vPro® Technology | | |
| | Intel® Ethernet Controller I226-V/LM, 2.5G ¹ | Intel® Ethernet Contro | | |
| Audio | Realtek ALC269 | Realtek | | |
| TPM | fTPM or TPM 2.0 chip | fTPM or TPI | • | |
| Card Reader | None | Nor | | |
| HDMI CEC | Yes, 2 ports on back panel | Yes, 2 ports o | | |
| Front I/O Ports | 2 x USB 3.2 Gen2 Type-A | 2 x USB 3.2 G | • • | |
| | 1 x Headset Jack | 1 x Heads | set Jack | |
| Back I/O Ports | 2 x Thunderbolt 4 Type-C w/ DisplayPort 1.4 | 2 x Thunderbolt 4 Type | -C w/ DisplayPort 1.4 | |
| | 1 x USB 3.2 Gen 2 Type-A | 1 x USB 3.2 G | en 2 Type-A | |
| | 1 x USB 2.0 Type-A | 1 x USB 2. | 0 Type-A | |
| | 2 x HDMI 2.1 (TMDS) | 2 x HDMI 2 | .1 (TMDS) | |
| | 1 x RJ45 LAN | 1 x RJ4 | 5 LAN | |
| | 1 x DC-in | 1 x D | C-in | |
| Side I/O Ports | 1 x Kensington Lock slot | 1 x Kensingto | on Lock slot | |
| Power Supply | 20VDC, 6.0A, 120W Power Adapter (i7/i5 CPU) | 20VDC, 6.0A, 120W Pow | er Adapter (i7/i5 CPU) | |
| | 19VDC, 4.74A, 90W Power Adapter (i3 CPU) | 19VDC, 4.74A, 90W Po | wer Adapter (i3 CPU) | |
| Operating Temp | 0 to 40C | 0 to 4 | 40C | |
| Storage Temp | -40 to 60C | -40 to | 60C | |
| Humidity | 0%-92% non-condensing ² | 0%-92% non- | condensing ² | |
| Dimensions (W x D x H) | "H" 117 x 112 x 54 mm | "K" 117 x 11 | 2 x 37 mm | |
| Weights | ~610g | ~50 | | |
| Accessories | AC Adapter+Power Cord ³ | 30 | -0 | |
| 7.0003301103 | VESA Bracket and Screws | AC Adapter+F | Power Cord ³ | |
| | M3 Screws for 2.5in Drive | VESA Bracket | and Screws | |
| | Cable Clip | Cable | | |
| | Safety/Caution/Regulatory Insert | Safety/Caution/R | - | |
| | Warranty Card | Warrant | y Card | |
| | waituitty Catu | | | |

 $^{^{(1)}}$ Intel® Ethernet Controller 1226-LM included on vPro enable systems

⁽²⁾ Humidity Info detail please check link: Non-condensing humidity as defined by temperature vs dew point

⁽³⁾ Power cord included is region specific, and some SKUs do not include the power cord







Board Specifications

Image E

| Board Specifications | image E |
|------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Marketing Name | ASUS NUC 13 Pro Board |
| Project Code | NUC13ANB-M / NUC13LCB-M |
| Photo | Image E |
| ASUS Logo | N/A |
| ASUS NUC Logo | N/A |
| Color | N/A |
| OS Support | Windows 11 64-bit Windows 10 IoT Enterprise 64-bit RedHat Enterprise Linux 9.1 64-bit Ubuntu 20.04/22.04 LTS 64-bit |
| CPU | Intel® Core™ i7-1370PE Processor w/ vPro, cTDP 40W Intel® Core™ i5-1350P Processor w/ vPro, cTDP 40W Intel® Core™ i5-1350PE Processor w/ vPro, cTDP 40W Intel® Core™ i5-1340P Processor, cTDP 40W Intel® Core™ i5-1340PE Processor, cTDP 40W Intel® Core™ i3-1315UP Processor, cTDP 20W Intel® Core™ i3-1315UE Processor, cTDP 20W |
| Chipset | Integrated |
| Graphics | Intel® Iris® Xe Graphics (i5/i7) Intel® UHD Graphics (i3) |
| Memory | 2 x SO-DIMM, Up to DDR4-3200, 32GB*2 |
| Storage | 1 x M.2 2280 PCIe Gen4x4, supports 128GB~8TB NVMe SSD 1 x M.2 2242 PCIe x1, supports 128GB~1TB SATA SSD 1 x SATA Power/DATA header for 2.5in SSD/HDD, supports 128GB~2TB SATA drive |
| Wireless Network | No Wireless Card Installed |
| LAN | Intel® Ethernet Controller I226-V/LM, 2.5G ¹ |
| Audio | Realtek ALC269 |
| TPM | fTPM or TPM 2.0 chip |
| Card Reader | None |
| HDMI CEC | Yes, 2 ports on back panel |
| Front I/O Ports | 2 x USB 3.2 Gen2 Type-A 1 x 3.5mm Headset Jack |
| Back I/O Ports | 2 x Thunderbolt 4 Type-C w/ DisplayPort 1.4 1 x USB 3.2 Gen 2 Type-A 1 x USB 2.0 Type-A 2 x HDMI 2.1 (TMDS) 1 x RJ45 LAN 1 x DC-in |
| Side I/O Ports | N/A |
| Power Supply | N/A |
| Operating Temp | 0 to 50C |
| Storage Temp | -40 to 60C |
| Humidity | 0%-92% non-condensing ² |
| Dimensions (W x D x H) | 110mm x 102mm x 28mm |
| Weights | ~225g |
| Accessories | Warranty Card Safety/Caution/Regulatory Insert |
| | |

 $^{^{(1)}}$ Intel® Ethernet Controller 1226-LM included on vPro enable systems


⁽²⁾ Humidity Info detail please check link: Non-condensing humidity as defined by temperature vs dew point





Model NUC13ANH-B / NUC13LCH-B (Tall) Connections





- 2 x USB 3.2 Gen2 Type-A
- 2 1x 3.5mm Headset Jack
- 3 1x Power Bottom
- 4 1x Kensington Lock (Side Port)
- 1x DC Input
- 6 2 x HDMI 2.1 (TMDS)
- 7 1x Thunderbolt 4 Type-C w


12

8 1x 2.5Gb Ethernet

- 9 1x USB 3.2 Gen 2, Type-A
- 1x USB 2.0, Type-A
- 11 1x Thunderbolt 4 Type-C w
- 12 Cable Locking Arm

Model NUC13ANK-B / NUC13LCK-B (Slim) Connections





- 1 2 x USB 3.2 Gen2 Type-A
- 2 1x 3.5mm Headset Jack
- 3 1x Power Bottom
- 4 1x Kensington Lock (Side Port)
- 1x DC Input
- 6 2 x HDMI 2.1 (TMDS)
- 1x Thunderbolt 4 Type-C w
- 8 1x 2.5Gb Ethernet

- 9 1x USB 3.2 Gen 2, Type-A
- 10 1 x USB 2.0, Type-A
- 11 1x Thunderbolt 4 Type-C w
- 12 Cable Locking Arm





What's in the box







NUC 13 PRO



90 / 120 W power supply



Inserts



Power Cord*



VESA bracket and Screws

NOTE:

- The most up-to-date and accurate product specifications are available on www.asus.com for download.
- Product and accessory images are for illustrative purposes only. The actual appearance and specifications may vary depending on the model.
- *The bundled power adapter may vary depending on the model and the country (or region) of sale.
- Some bundled accessories may vary depending on the model. For details on these accessories, refer to their respective user manuals.
- If the device or its components fail or malfunction during normal and proper use within the warranty period, bring the warranty card to the ASUS Service Center for replacement of the defective components.