

Philips 1000 series 24E1N1100A/00 LED display 60.5 cm (23.8") 1920 x 1080 pixels Full HD LCD Black

Brand : Philips

Product family: 1000 series

Product code: 24E1N1100A/00

Product name :
24E1N1100A/00

Monitor 24E1N1100A Full HD LCD monitor

Philips 1000 series 24E1N1100A/00 LED display 60.5 cm (23.8") 1920 x 1080 pixels Full HD LCD Black:

Experience productivity in Full HD. This monitor is equipped with essentials for the workplace, such as LowBlue mode to protect the eyes, IPS LED wide view technology for high-quality imagery, and 1ms MPRT for sharp visuals.

Philips 1000 series 24E1N1100A/00. Display diagonal: 60.5 cm (23.8"), Display resolution: 1920 x 1080 pixels, HD type: Full HD, Display technology: LCD, Response time: 4 ms, Native aspect ratio: 16:9, Viewing angle, horizontal: 178°, Viewing angle, vertical: 178°. Built-in speaker(s). VESA mounting. Product colour: Black



Display		Ergonomics	
Display diagonal *	60.5 cm (23.8")	VESA mounting *	✓
Display resolution *	1920 x 1080 pixels	Panel mounting interface	100 x 100 mm
HD type *	Full HD	Cable lock slot *	✓
Native aspect ratio *	16:9	Cable lock slot type	Kensington
Display technology *	LCD	Tilt adjustment	✓
Panel type *	IPS	Tilt angle range	-5 - 20°
Backlight type	W-LED	On Screen Display (OSD)	✓
Touchscreen *	✗	On Screen Display (OSD) languages	Simplified Chinese, Traditional Chinese, Czech, German, Dutch, English, Spanish, Finnish, French, Greek, Hungarian, Italian, Japanese, Korean, Polish, Portuguese, Russian, Swedish, Turkish, Ukrainian
Display brightness (typical)	250 cd/m²		
Response time *	4 ms		
Anti-glare screen	✓	Number of OSD languages	21
Screen shape *	Flat	Plug and Play	✓
Contrast ratio (typical) *	1300:1	LED indicators	Operation, Stand-by
Dynamic contrast ratio marketing name	Mega Infinity DCR	Power	
Maximum refresh rate *	100 Hz	Energy efficiency class (SDR) *	D
Viewing angle, horizontal	178°	Energy efficiency class (HDR) *	Not available
Viewing angle, vertical	178°	Power consumption (typical) *	14.5 W
Display number of colours *	16.7 million colours	Power consumption (standby) *	0.5 W
Response time (fast)	1 ms	Power consumption (off)	0.3 W
Pixel pitch	0.2745 x 0.2745 mm	AC input voltage	100 - 240 V
Pixel density	92.56 ppi	AC input frequency	50/60 Hz
Horizontal scan range	30 - 85 kHz	Power supply type	External
Vertical scan range	48 - 60 Hz	Operational conditions	
Viewable size, horizontal	52.7 cm	Operating temperature (T-T)	0 - 40 °C
Viewable size, vertical	29.6 cm	Storage temperature (T-T)	-20 - 60 °C
Digital horizontal frequency	30 - 115 kHz	Operating relative humidity (H-H)	20 - 80%
Digital vertical frequency	48 - 100 Hz	Operating altitude	0 - 3658 m
Display diagonal (metric)	60.5 cm	Non-operating altitude	3658 - 12192 m
DDC/CI	✓		
Haze rate	25%		

Display		Weight & dimensions	
Surface hardness	3H	Width (with stand)	542 mm
Colour gamut standard	sRGB	Depth (with stand)	180 mm
Display sRGB	✓	Height (with stand)	417 mm
Performance		Weight (with stand)	2.92 kg
NVIDIA G-SYNC *	✗	Width (without stand)	542 mm
AMD FreeSync *	✗	Depth (without stand)	45 mm
VESA Adaptive Sync support	✓	Height (without stand)	316 mm
Component video sync	Separate sync	Weight (without stand)	2.57 kg
Flicker-free technology	✓	Packaging data	
Low Blue Light technology	✓	Package width	610 mm
Multimedia		Package depth	124 mm
Number of speakers	2	Package height	370 mm
RMS rated power	4 W	Package weight	4.68 kg
Built-in speaker(s) *	✓	Packaging content	
Built-in camera *	✗	Stand included	✓
Design		Cables included	AC, HDMI
Market positioning *	Home	Manual	✓
Product colour *	Black	Sustainability	
Feet colour	Black	Sustainability compliance	✓
Ports & interfaces		Doesn't contain	BFR, Mercury, PVC
Built-in USB hub *	✗	Other features	
VGA (D-Sub) ports quantity	1	Compatible operating systems	Mac OS X Windows 11 / 10
HDMI *	✓	Picture enhancement	SmartImage game
HDMI ports quantity	1	Heavy metals free	Hg (mercury)
HDMI version	1.4	EasyRead mode	✓
Audio input	✓	LowBlue mode	✓
Audio output	✓	Compliance certificates	BSMI, EAC, Federal Communications Commission (FCC), ICES, RoHS, cTUVus, VCCI
HDCP	✓	Mean time between failures (MTBF)	50000 h
HDCP version	1.4		



8712581804244

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 01-FEB-2025. Prints or copies of Information are only valid on the printed Publication date