

DELL Precision 3591 Intel Core Ultra 7 155H Mobile workstation 39.6 cm (15.6") Full HD 32 GB DDR5-SDRAM 1 TB SSD NVIDIA RTX 1000 Ada Wi-Fi 6E (802.11ax) Windows 11 Pro Grey

Brand : DELL

Product family: Precision

Product code: GGV0R



DELL Precision 3591. Product type: Mobile workstation, Form factor: Clamshell. Processor family: Intel Core Ultra 7, Processor model: 155H. Display diagonal: 39.6 cm (15.6"), HD type: Full HD, Display resolution: 1920 x 1080 pixels. Internal memory: 32 GB, Internal memory type: DDR5-SDRAM. Total storage capacity: 1 TB, Storage media: SSD. On-board graphics card model: Intel Arc Graphics, Discrete graphics card model: NVIDIA RTX 1000 Ada. Operating system installed: Windows 11 Pro. Product colour: Grey





Design		Camera	
Product type * Mobile workstation Product colour * Grey	Privacy camera Privacy type	✓ Privacy shutter	
Form factor * Market positioning	Clamshell Business	Network	W/ 5' 65 (000 11 -)
Display		Top Wi-Fi standard *	Wi-Fi 6E (802.11ax) Wi-Fi 5 (802.11ac), 802.11b,
Display diagonal * Display resolution *	39.6 cm (15.6") 1920 x 1080 pixels	Wi-Fi standards Mobile network connection *	802.11g, Wi-Fi 4 (802.11n), Wi-Fi 6E (802.11ax)
Touchscreen * HD type Panel type LED backlight	× Full HD IPS ✓	Wi-Fi data rate (max) Antenna type WLAN controller model	× 2400 Mbit/s 2x2 Intel Wi-Fi 6E AX211
Native aspect ratio Anti-glare screen Display brightness Pixel density RGB colour space Colour gamut Maximum refresh rate	16:9 ✓ 400 cd/m ² 141 ppi sRGB 100% 60 Hz	WLAN controller manufacturer Ethernet LAN Ethernet LAN data rates Bluetooth WWAN MIMO MIMO type	Intel I0,100,1000 Mbit/s Upgradable Multi User MIMO
Contrast ratio (typical)	800:1	Ports & interfaces	
Processor Processor manufacturer * Processor family * Processor generation Processor model * Processor cores Processor threads Processor boost frequency Performance cores	Intel Intel Core Ultra 7 Intel® Core™ Ultra (Series 1) 155H 16 22 4.8 GHz 6	USB 3.2 Gen 1 (3.1 Gen 1) Type-A ports quantity * Ethernet LAN (RJ-45) ports HDMI ports quantity * HDMI version Thunderbolt 4 ports quantity Intel® Thunderbolt 4 Combo headphone/mic port	2 1 1 2.1 2

Processor		Ports & interfaces	
Efficient cores	8	USB Type-C DisplayPort Alternate	1
Low Power Efficient-cores	2	Mode	
Performance-core Max Turbo Frequency	4.8 GHz	PowerShare	
Efficient-core Max Turbo Frequency	3.8 GHz	Number of USB ports with PowerShare support	1
Low Power Efficient-core Max Turbo Frequency	2.5 GHz	Keyboard	
Performance-core base frequency	1.4 GHz	Pointing device	Touchpad
Efficient-core base frequency	0.9 GHz	Keyboard language	Belgian
Low Power Efficient-core Base	700 MHz	Numeric keypad *	v
Frequency		Keyboard backlit	1
Processor cache	24 MB	Keyboard number of keys	100
Processor cache type	Smart Cache	Software	
Processor base power Maximum turbo power	28 W 115 W	Operating system architecture	64-bit
Neural processor unit (NPU)	115 W	Operating system language	German, Dutch, English, French,
Neural processor unit (NPU)	Intel Al Boost		Italian Activate Your Microsoft 365 For A 30
Maximum frequency NPU	1.4 GHz	Trial software	Day Trial
Sparsity support	1	Operating system installed *	Windows 11 Pro
Windows Studio effects support	1	Battery	
AI datatype support on NPU	FP16, FP32, Int8	Number of battery cells	4
AI software frameworks supported by NPU	DirectML, ONNX RT, OpenVINO, Windows ML	Battery capacity *	64 Wh
-		Battery voltage	15.2 V
Memory		Battery recharge time	3 h 🗸
Internal memory *	32 GB	Fast charging	
Internal memory type	DDR5-SDRAM	Battery charge indicator	✓ 200 ≖
Memory form factor	SO-DIMM	Battery weight	280 g
Memory layout (slots x size) Memory slots	1 x 32 GB 2x SO-DIMM	Power	
Maximum internal memory *	64 GB	AC adapter power	130 W
Memory data transfer rate	5600 MT/s	AC adapter frequency	50 - 60 Hz
Non-ECC		AC adapter input voltage	100 - 240 V
		USB Type-C charging port *	✓
Chausan			
Storage		USB Power Delivery (USB PD)	1
Total storage capacity *	1 TB	USB Power Delivery (USB PD) USB charging voltage	✓ 5,20 V
Total storage capacity * Storage media *	SSD		
Total storage capacity * Storage media * Total SSDs capacity	SSD 1 TB	USB charging voltage	
Total storage capacity * Storage media * Total SSDs capacity Number of SSDs installed	SSD 1 TB 1	USB charging voltage Security	5,20 V
Total storage capacity * Storage media * Total SSDs capacity Number of SSDs installed SSD capacity	SSD 1 TB 1 1 TB	USB charging voltage Security Cable lock slot	5,20 V
Total storage capacity * Storage media * Total SSDs capacity Number of SSDs installed	SSD 1 TB 1	USB charging voltage Security Cable lock slot Cable lock slot type	5,20 V ✓ Wedge
Total storage capacity * Storage media * Total SSDs capacity Number of SSDs installed SSD capacity SSD interface	SSD 1 TB 1 1 TB PCI Express 4.0	USB charging voltage Security Cable lock slot Cable lock slot type Smart card reader	5,20 V ✓ Wedge ✓
Total storage capacity * Storage media * Total SSDs capacity Number of SSDs installed SSD capacity SSD interface NVMe	SSD 1 TB 1 1 TB PCI Express 4.0	USB charging voltage Security Cable lock slot Cable lock slot type Smart card reader Trusted Platform Module (TPM)	5,20 V ✓ Wedge ✓
Total storage capacity * Storage media * Total SSDs capacity Number of SSDs installed SSD capacity SSD interface NVMe SSD form factor	SSD 1 TB 1 1 TB PCI Express 4.0 ✓ M.2	USB charging voltage Security Cable lock slot Cable lock slot type Smart card reader Trusted Platform Module (TPM) Trusted Platform Module (TPM)	5,20 V ✓ Wedge ✓
Total storage capacity * Storage media * Total SSDs capacity Number of SSDs installed SSD capacity SSD interface NVMe SSD form factor SSD performance class	SSD 1 TB 1 1 TB PCI Express 4.0 ✓ M.2 40	USB charging voltage Security Cable lock slot Cable lock slot type Smart card reader Trusted Platform Module (TPM) Trusted Platform Module (TPM)	5,20 V ✓ Wedge ✓
Total storage capacity * Storage media * Total SSDs capacity Number of SSDs installed SSD capacity SSD interface NVMe SSD form factor SSD performance class M.2 SSD size	SSD 1 TB 1 1 TB PCI Express 4.0 ✓ M.2 40 2280 (22 x 80 mm)	USB charging voltage Security Cable lock slot Cable lock slot type Smart card reader Trusted Platform Module (TPM) Trusted Platform Module (TPM) version	5,20 V ✓ Wedge ✓ 2.0
Total storage capacity * Storage media * Total SSDs capacity Number of SSDs installed SSD capacity SSD interface NVMe SSD form factor SSD performance class M.2 SSD size Optical drive type * Card reader integrated	SSD 1 TB 1 1 TB PCI Express 4.0 ✓ M.2 40 2280 (22 x 80 mm) × ✓ MicroSD (TransFlash), MicroSDHC,	USB charging voltage Security Cable lock slot Cable lock slot type Smart card reader Trusted Platform Module (TPM) Trusted Platform Module (TPM) version Operational conditions Operating temperature (T-T)	5,20 V ✓ Wedge ✓ 2.0 0 - 35 °C
Total storage capacity * Storage media * Total SSDs capacity Number of SSDs installed SSD capacity SSD interface NVMe SSD form factor SSD performance class M.2 SSD size Optical drive type * Card reader integrated Compatible memory cards	SSD 1 TB 1 1 TB PCI Express 4.0 ✓ M.2 40 2280 (22 x 80 mm) × ✓	USB charging voltage Security Cable lock slot Cable lock slot type Smart card reader Trusted Platform Module (TPM) Trusted Platform Module (TPM) version Operational conditions Operating temperature (T-T) Storage temperature (T-T) Storage relative humidity (H-H) Storage relative humidity (H-H)	5,20 V ✓ Wedge ✓ 2.0 0 - 35 °C -40 - 65 °C 10 - 90% 0 - 95%
Total storage capacity * Storage media * Total SSDs capacity Number of SSDs installed SSD capacity SSD interface NVMe SSD form factor SSD performance class M.2 SSD size Optical drive type * Card reader integrated Compatible memory cards Graphics	SSD 1 TB 1 1 TB PCI Express 4.0 ✓ M.2 40 2280 (22 x 80 mm) × ✓ MicroSD (TransFlash), MicroSDHC, MicroSDXC	USB charging voltage Security Cable lock slot Cable lock slot type Smart card reader Trusted Platform Module (TPM) Trusted Platform Module (TPM) version Operational conditions Operating temperature (T-T) Storage temperature (T-T) Operating relative humidity (H-H) Storage relative humidity (H-H) Operating altitude	5,20 V ✓ Wedge ✓ 2.0 0 - 35 °C -40 - 65 °C 10 - 90% 0 - 95% -15.2 - 3048 m
Total storage capacity * Storage media * Total SSDs capacity Number of SSDs installed SSD capacity SSD interface NVMe SSD form factor SSD performance class M.2 SSD size Optical drive type * Card reader integrated Compatible memory cards Graphics Discrete graphics card model *	SSD 1 TB 1 1 TB PCI Express 4.0 ✓ M.2 40 2280 (22 x 80 mm) × ✓ MicroSD (TransFlash), MicroSDHC, MicroSDHC,	USB charging voltage Security Cable lock slot Cable lock slot type Smart card reader Trusted Platform Module (TPM) Trusted Platform Module (TPM) version Operational conditions Operating temperature (T-T) Storage temperature (T-T) Storage relative humidity (H-H) Storage relative humidity (H-H) Operating altitude Non-operating altitude	5,20 V ✓ Wedge ✓ ✓ 2.0 0 - 35 °C -40 - 65 °C 10 - 90% 0 - 95% -15.2 - 3048 m -15.2 - 10668 m
Total storage capacity * Storage media * Total SSDs capacity Number of SSDs installed SSD capacity SSD interface NVMe SSD form factor SSD performance class M.2 SSD size Optical drive type * Card reader integrated Compatible memory cards Graphics Discrete graphics card model * Discrete graphics card memory	SSD 1 TB 1 1 TB PCI Express 4.0 ✓ M.2 40 2280 (22 x 80 mm) × ✓ MicroSD (TransFlash), MicroSDHC, MicroSDHC, NVIDIA RTX 1000 Ada 6 GB	USB charging voltage Security Cable lock slot Cable lock slot type Smart card reader Trusted Platform Module (TPM) Trusted Platform Module (TPM) version Operating temperature (T-T) Storage temperature (T-T) Storage relative humidity (H-H) Storage relative humidity (H-H) Operating altitude Non-operating altitude Operating shock	5,20 V ✓ Wedge ✓ 2.0 0 - 35 °C -40 - 65 °C 10 - 90% 0 - 95% -15.2 - 3048 m
Total storage capacity * Storage media * Total SSDs capacity Number of SSDs installed SSD capacity SSD interface NVMe SSD form factor SSD performance class M.2 SSD size Optical drive type * Card reader integrated Compatible memory cards Graphics Discrete graphics card model * Discrete graphics card memory type	SSD 1 TB 1 1 TB PCI Express 4.0 ✓ M.2 40 2280 (22 x 80 mm) × ✓ MicroSD (TransFlash), MicroSDHC, OB MicroSDXC	USB charging voltage Security Cable lock slot Cable lock slot type Smart card reader Trusted Platform Module (TPM) Trusted Platform Module (TPM) version Operational conditions Operating temperature (T-T) Storage temperature (T-T) Storage relative humidity (H-H) Storage relative humidity (H-H) Operating altitude Non-operating altitude	5,20 V ✓ Wedge ✓ ✓ 2.0 0 - 35 °C -40 - 65 °C 10 - 90% 0 - 95% -15.2 - 3048 m -15.2 - 10668 m 110 G
Total storage capacity * Storage media * Total SSDs capacity Number of SSDs installed SSD capacity SSD interface NVMe SSD form factor SSD performance class M.2 SSD size Optical drive type * Card reader integrated Compatible memory cards Graphics Discrete graphics card model * Discrete graphics memory type On-board graphics card *	SSD 1 TB 1 1 TB PCI Express 4.0 ✓ M.2 40 2280 (22 x 80 mm) × ✓ MicroSD (TransFlash), MicroSDHC, MicroSDHC, CransFlash), MicroSDHC, MicroSDHC, ↓ MicroSDHC, ↓ ↓	USB charging voltage Security Cable lock slot Cable lock slot type Smart card reader Trusted Platform Module (TPM) Trusted Platform Module (TPM) version Operational conditions Operating temperature (T-T) Storage temperature (T-T) Storage relative humidity (H-H) Storage relative humidity (H-H) Operating altitude Non-operating altitude Operating shock Non-operating shock	5,20 V ✓ Wedge ✓ ✓ 2.0 0 - 35 °C -40 - 65 °C 10 - 90% 0 - 95% -15.2 - 10668 m 110 G 160 G
Total storage capacity * Storage media * Total SSDs capacity Number of SSDs installed SSD capacity SSD interface NVMe SSD form factor SSD performance class M.2 SSD size Optical drive type * Card reader integrated Compatible memory cards Graphics Discrete graphics card model * Discrete graphics card memory Discrete graphics card * On-board GPU manufacturer	SSD 1 TB 1 1 TB PCI Express 4.0 ✓ M.2 40 2280 (22 x 80 mm) × ✓ MicroSD (TransFlash), MicroSDHC, MicroSDHC, CTANA MicroSD (TransFlash), MicroSDHC, MicroSDHC, ✓ MicroSD (TransFlash), MicroSDHC, ✓ MicroSD (TransFlash), MicroSDHC, ✓ MicroSD (TransFlash), MicroSDHC, MicroSDHC, MicroSDHC, MicroSDHC, MicroSDHC, MicroSDHC, MicroSDHC, MicroSDHC, MicroSDHC, MicroSDHC, MicroSDHC, MicroSDHC, MicroSDHC, MicroSDHC, MicroSDHC, MicroSDHC, MicroSDHC, MicroSDHC, MicroSDHC, MicroSDHC, MicroSDHC, MicroSDHC, MicroSDHC, MicroSDHC, MicroSDHC, MicroSDHC, MicroSDHC, MicroSDHC, MicroSDHC, MicroSDHC, MicroSDHC, MicroSDHC, MicroSDHC, MicroSDHC, MicroSDHC, MicroSDHC, MicroSDHC, MicroSDHC, MicroSDHC, MicroSDHC, MicroSDHC, MicroSDHC, MicroSDHC, MicroSDHC, MicroSDHC, MicroSDHC, MicroSDHC, MicroSDHC, MicroSDHC, MicroSDHC, MicroSDHC, MicroSDHC, MicroSDHC, MicroSDHC, MicroSDHC, MicroSDHC, MicroSDHC, MicroSDHC, MicroSDHC, MicroSDHC, MicroSDHC, MicroSDHC, MicroSDHC, MicroSDHC, MicroSDHC, MicroSDHC, MicroSDHC, MicroSDHC, MicroSDHC, MicroSDHC, MicroSDHC, MicroSDHC, MicroSDHC, MicroSDHC, MicroSDHC, MicroSDHC, MicroSDHC, MicroSDHC, MicroSDHC, MicroSDHC, MicroSDHC, MicroSDHC, MicroSDHC, MicroSDHC, MicroSDHC, MicroSDHC, MicroSDHC, MicroSDHC, MicroSDHC, MicroSDHC, MicroSDHC, MicroSDHC, MicroSDHC, MicroSDHC, MicroSDHC, MicroSDHC, MicroSDHC, MicroSDHC, MicroSDHC, MicroSDHC, MicroSDHC, MicroSDHC, MicroSDHC, MicroSDHC, MicroSDHC, MicroSDHC, MicroSDHC, MicroSDHC, MicroSDHC, MicroSDHC, MicroSDHC, MicroSDHC, MicroSDHC, MicroSDHC, MicroSDHC, MicroSDHC, MicroSDHC, MicroSDHC, MicroSDHC, MicroSDHC, MicroSDHC, MicroSDHC, MicroSDHC, MicroSDHC, MicroSDHC, MicroSDHC, MicroSDHC, MicroSDHC, MicroSDHC, MicroSDHC, MicroSDHC, MicroSDHC, MicroSDHC, MicroSDHC, MicroSDHC, MicroSDHC, MicroSDHC, MicroSDHC, MicroSDHC, MicroSDHC, MicroSDHC, MicroSDHC, MicroSDHC, MicroSDHC, MicroSDHC, MicroSDHC, MicroSDHC, MicroSDHC	USB charging voltage Security Cable lock slot Cable lock slot type Smart card reader Trusted Platform Module (TPM) Trusted Platform Module (TPM) version Operational conditions Operating temperature (T-T) Storage temperature (T-T) Operating relative humidity (H-H) Storage relative humidity (H-H) Storage relative humidity (H-H) Operating altitude Non-operating altitude Operating shock Non-operating shock Operating vibration	5,20 V ✓ Wedge ✓ ✓ 2.0 0 - 35 °C -40 - 65 °C 10 - 90% 0 - 95% -15.2 - 10668 m 110 G 160 G 0.66 G
Total storage capacity * Storage media * Total SSDs capacity Number of SSDs installed SSD capacity SSD interface NVMe SSD form factor SSD performance class M.2 SSD size Optical drive type * Card reader integrated Compatible memory cards Graphics Discrete graphics card model * Discrete graphics card memory Discrete graphics card * On-board GPU manufacturer Discrete graphics card *	SSD 1 TB 1 1 TB PCI Express 4.0 ✓ M.2 40 2280 (22 x 80 mm) × ✓ MicroSD (TransFlash), MicroSDHC, MicroSDHC, CINIDIA RTX 1000 Ada 6 GB GDDR6 ✓ Intel ↓	USB charging voltage Security Cable lock slot Cable lock slot type Smart card reader Trusted Platform Module (TPM) Trusted Platform Module (TPM) Version Operating temperature (T-T) Storage temperature (T-T) Storage temperature (T-T) Operating relative humidity (H-H) Storage relative humidity (H-H) Operating altitude Non-operating altitude Operating shock Non-operating shock Non-operating vibration Non-operating vibration	5,20 V ✓ Wedge ✓ ✓ 2.0 0 - 35 °C -40 - 65 °C 10 - 90% 0 - 95% -15.2 - 3048 m -15.2 - 10668 m 110 G 160 G 0.66 G 1.3 G
Total storage capacity * Storage media * Total SSDs capacity Number of SSDs installed SSD capacity SSD interface NVMe SSD form factor SSD performance class M.2 SSD size Optical drive type * Card reader integrated Compatible memory cards Graphics Discrete graphics card model * Discrete graphics card memory Discrete graphics card * On-board GPU manufacturer Discrete graphics card * On-board graphics card family	SSD 1 TB 1 1 TB PCI Express 4.0 ✓ M.2 40 2280 (22 x 80 mm) × ✓ MicroSD (TransFlash), MicroSDHC, MicroSDXC NVIDIA RTX 1000 Ada 6 GB GDDR6 ✓ Intel Intel ✓	USB charging voltage Security Cable lock slot Cable lock slot type Smart card reader Trusted Platform Module (TPM) Trusted Platform Module (TPM) version Operational conditions Operating temperature (T-T) Storage temperature (T-T) Storage relative humidity (H-H) Storage relative humidity (H-H) Operating altitude Non-operating altitude Non-operating shock Non-operating shock Non-operating vibration Non-operating vibration Sustainability compliance	5,20 V Wedge ✓ ✓ 2.0 0 - 35 °C -40 - 65 °C 10 - 90% 0 - 95% -15.2 - 3048 m -15.2 - 10668 m 110 G 160 G 0.66 G 1.3 G
Total storage capacity * Storage media * Total SSDs capacity Number of SSDs installed SSD capacity SSD interface NVMe SSD form factor SSD performance class M.2 SSD size Optical drive type * Card reader integrated Compatible memory cards Graphics Discrete graphics card model * Discrete graphics card memory Discrete graphics card * On-board GPU manufacturer Discrete graphics card family On-board graphics card family On-board graphics card model *	SSD 1 TB 1 1 TB PCI Express 4.0 ✓ M.2 40 2280 (22 x 80 mm) × ✓ MicroSD (TransFlash), MicroSDHC, MicroSDHC, CINIDIA RTX 1000 Ada 6 GB GDDR6 ✓ Intel ↓	USB charging voltage Security Cable lock slot Cable lock slot type Smart card reader Trusted Platform Module (TPM) Trusted Platform Module (TPM) version Operational conditions Operating temperature (T-T) Storage temperature (T-T) Operating relative humidity (H-H) Storage relative humidity (H-H) Operating altitude Non-operating altitude Operating shock Non-operating vibration Non-operating vibration Sustainability Sustainability compliance Sustainability certificates	5,20 V ✓ Wedge ✓ ✓ 2.0 0 - 35 °C -40 - 65 °C 10 - 90% 0 - 95% -15.2 - 3048 m -15.2 - 10668 m 110 G 160 G 0.66 G 1.3 G
Total storage capacity * Storage media * Total SSDs capacity Number of SSDs installed SSD capacity SSD interface NVMe SSD form factor SSD performance class M.2 SSD size Optical drive type * Card reader integrated Compatible memory cards Graphics Discrete graphics card model * Discrete graphics card memory Discrete graphics card * On-board GPU manufacturer Discrete graphics card * On-board graphics card family	SSD 1 TB 1 1 TB PCI Express 4.0 ✓ M.2 40 2280 (22 x 80 mm) × ✓ MicroSD (TransFlash), MicroSDHC, MicroSDXC NVIDIA RTX 1000 Ada 6 GB GDDR6 ✓ Intel Intel ✓	USB charging voltage Security Cable lock slot Cable lock slot type Smart card reader Trusted Platform Module (TPM) Trusted Platform Module (TPM) version Operational conditions Operating temperature (T-T) Storage temperature (T-T) Storage relative humidity (H-H) Storage relative humidity (H-H) Operating altitude Non-operating altitude Non-operating shock Non-operating shock Non-operating vibration Non-operating vibration Sustainability compliance	5,20 V Wedge ✓ ✓ 2.0 0 - 35 °C -40 - 65 °C 10 - 90% 0 - 95% -15.2 - 3048 m -15.2 - 10668 m 110 G 160 G 0.66 G 1.3 G

Audio		Weight & dimensions	
Speakers manufacturer Speaker power Built-in microphone Number of microphones	Waves 2 W ✓ 2	Depth Height (front) Height (rear) Weight * Carbon footprint	233.3 mm 2.27 cm 2.47 cm 1.79 kg
Camera Front camera Front camera resolution (numeric) Front camera resolution Front camera HD type Video capturing speed	 2.07 MP 1920 x 1080 pixels Full HD 30 fps 	Total carbon footprint (kg of CO2e) Carbon emissions, manufacturing (kg of CO2e) Carbon emissions, logistics (kg of CO2e) Carbon emissions, energy usage (kg of CO2e) Carbon emissions, end-of-life (kg of CO2e) Total carbon emissions, w/o use phase (kg of CO2e) PAIA version	120 84 5 31 1 89 GaBi version 1, 2024
		Packaging content	

Cables included

AC



5397184774182

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.