

DELL Latitude 5450 Intel Core Ultra 5 135U Laptop 35.6 cm (14") Full HD 16 GB DDR5-SDRAM 512 GB SSD Wi-Fi 6E (802.11ax) Windows 11 Pro Grey

Brand : DELL

Product family: Latitude

Product code: 31R26

Product name : 5450

DELL Latitude 5450. Product type: Laptop, Form factor: Clamshell. Processor family: Intel Core Ultra 5, Processor model: 135U. Display diagonal: 35.6 cm (14"), HD type: Full HD, Display resolution: 1920 x 1080 pixels. Internal memory: 16 GB, Internal memory type: DDR5-SDRAM. Total storage capacity: 512 GB, Storage media: SSD. On-board graphics card model: Intel Graphics. Operating system installed: Windows 11 Pro. Product colour: Grey. Weight: 1.4 kg





Design		Network	
Product type *	Laptop	Top Wi-Fi standard *	Wi-Fi 6E (802.11ax)
Product colour *	Grey	Mr. F. and a set	Wi-Fi 5 (802.11ac), 802.11b,
Form factor *	Clamshell	Wi-Fi standards	802.11g, Wi-Fi 4 (802.11n), Wi-Fi 6E (802.11ax)
Market positioning	Business	Mobile network connection *	×
Intel® vPro [™] Platform Eligibility	1	Antenna type	2x2
Display		WLAN controller model	Intel Wi-Fi 6E AX211
Display diagonal *	35.6 cm (14")	WLAN controller manufacturer	Intel
Display resolution *	1920 x 1080 pixels	Ethernet LAN	1
Touchscreen *	×	Ethernet LAN data rates	10,100,1000 Mbit/s
HD type	Full HD	Bluetooth	 Image: A set of the set of the
Panel type	IPS	WWAN	Upgradable
LED backlight	1	Ports & interfaces	15
Native aspect ratio	16:9		
Anti-glare screen	1	USB 3.2 Gen 1 (3.1 Gen 1) Type-A ports quantity *	2
Display brightness	250 cd/m ²	Ethernet LAN (RJ-45) ports	1
Pixel density	157 ppi	HDMI ports quantity *	1
RGB colour space	NTSC	HDMI version	2.1
Colour gamut	45%	Thunderbolt 4 ports quantity	2
Maximum refresh rate	60 Hz	Intel [®] Thunderbolt 4	1
Contrast ratio (typical)	600:1	Combo headphone/mic port	1
Processor		USB Type-C DisplayPort Alternate Mode	 Image: A start of the start of
Processor manufacturer *	Intel	PowerShare	1
Processor family *	Intel Core Ultra 5		•
Processor generation	Intel® Core [™] Ultra (Series 1)	Keyboard	
Processor model * Processor cores	135U 12	Pointing device	Touchpad
Processor threads	12	Keyboard language	US International
Processor boost frequency	4.4 GHz	Numeric keypad *	×
Performance cores	2	Keyboard backlit	✓
Efficient cores	8	Keyboard number of keys	79
Low Power Efficient-cores	2	Copilot key	1
Performance-core Max Turbo Frequency	4.4 GHz	Software	
Efficient-core Max Turbo Frequency	3.6 GHz	Operating system architecture	64-bit
Low Power Efficient-core Max Turbo Frequency	2.1 GHz	Operating system language	German, Dutch, English, French, Italian

Partomaccore base frequency1.6 GPITrail softwareAutymet Your Microsoft 355 For A 30Finistencore base frequency1.1 GPIOperating system installedDay TrainProcessor cache2.2 MSCaplor + C~Processor cache5.WBrand-specific features~Processor cache5.WBrand-specific featuresControl Vault 34, Express ChargeMaximum trade power5.WBrand-specific features3Maximum trade power1.4 GP2Battay control Vault 34, Express ChargeMaximum frequency1.4 GP2Battay control Vault 34, Express ChargeMaximum frequency1.4 GP2Battay control Vault 34, Express ChargeMaximum frequency1.4 GP2Battay control Vault 34, Express ChargeMindows Studi effects support4. GP23Mindows Studi effects support4. GP2Battay control Vault 34, Express ChargeMindows Studi effects support4. GP23Mindows Studi effects support5.G GPSMindows Studi effects support5.G GPSMindows Studi effects support1.G GPSMindows Studi effects support5.G	D		C - flowers	
Initial solutionInitial solutionUnitial solutionInder Sourd CalcialQuartic CalcialWindows 11 ProPrequency Cache typeSand CacheFace-Source CalcialWindows 11 ProPrecessor scale typeSand CacheFace-Source CalcialControl Vauil 3+, Express ChargeMeans processor state typeSand CacheFace-Source CalcialControl Vauil 3+, Express ChargeMeans processor state typeSand CacheBatteryControl Vauil 3+, Express ChargeMeans processor state type14 GHzBattery calcial34 Windows 11 ProMaximum tracture type14 GHzBattery calcial34 Windows 11 ProMaximum frequency NFU14 GHzBattery calcial34 Windows 11 ProA contract frameworks supportedDirect/H, OWX KT, OpenWindoFact charging32 Open-SourceMemory Use16 GBPowerSource20 Open-SourceMemory UseSo OblinkA calciapter prover55 Windows 11 ProMemory Use16 GBSourceSource20 Open-SourceMemory Use16 GBSource20 Open-Source20 Open-SourceMemory Use16 GBSource20 Open-Source20 Open-SourceMemory Use16 GBCalciapter prover55 WindowsMemory Use15 CB GBCalciapter Input value20 -Ot VMemory Use15 CB GBCalciapter Input value20 -Ot VMemory Use15 CB GBSource20 Open-SourceSource Calcia12 CBSource20 Open-GB <t< td=""><td>Processor</td><td></td><td>Software</td><td></td></t<>	Processor		Software	
DescriptionOperating system installedMeans 11 ProPropersor00 Ma/aContor CoulouMeansProcessor cache1.5 MCapito F.C.*Processor cache spore1.5 MFrant-specific featuresSource specific featuresNeural processor unit NPUInfel Al BoorNumber of basies (and the specific features)Source specific featuresNeural processor unit NPUInfel Al BoorMuther of basies (and the specific features)4 Montor featuresSpacing status (Status			Trial software	
FrequencyNot Mr2Mcrosoft Copilat PCProcessor cache typeSmart Cache YmeEnad-specific featuresProcessor cache typeS7 WBrand specific featuresNamir processor unit (NPU)Intel Al BoostBattery cacher ymeNamard processor unit (NPU)Intel Al BoostS4 WNamard processor unit (NPU)Intel Al BoostS4 WhMaximum traquency NPU1.4 GHzBattery cacher ymeS4 WhSparish ynapport4.6 GHzBattery ynage indicatorS4 WhAl coffward frameworks supportDirectML, ONIX RT, OpenYWOBattery ynage indicatorA DirectML ONIX RT, OpenYWOMadows Studio effects support1.6 GBS4 WhS4 WhMemory Support1.6 GBS4 WhS4 WhMemory Support2.8 S GDAMAA Gadaper Inprovent (NPU)S4 Open (NPU)Memory Support2.8 S Op ONMAA Gadaper InpruvintogaS0 L, S0 V CAMemory Support2.8 S Op ONMAA Gadaper InpruvintogaS0 L, S0 V CAMemory Support2.8 S Op ONMACache Increating (NPU)S0 L, S0 V CAMemory Support2.8 S Op ONMACache Increating (NPU)S0 L, S0 V CAMemory Support1.5 CGS0 S Cacher (NPU)S0 Cop RCMemory Support2.8 S Op OPMACacher (NPU)S0 L, S0 V CAMemory Support1.5 CGS0 S Cacher (NPU)S0 S Cop RCMemory Support1.5 CGS0 S Cacher (NPU)S0 S S0			Operating system installed *	-
Processor lack pipeSmart CacheFund-specific featuresJournal processor unit (MPU)Smart Specific featuresSmart Specific featuresNeural processor unit (MPU)Ideal PoostStartery caches, and specific featuresSource Journal Specific featuresNouring processor unit (MPU)Ideal PoostStartery caches, and specific featuresSource Journal Specific featuresNouring processor unit (MPU)Ideal PoostStartery caches, and specific featuresSource Journal Specific featuresNouring processor unit (MPU)Ideal PoostStartery valuesSource Journal Specific featuresNouring Specific featuresSource Journal Specific featuresSource Journal Specific features <t< td=""><td>Frequency</td><td>700 MHz</td><td>Microsoft Copilot</td><td>1</td></t<>	Frequency	700 MHz	Microsoft Copilot	1
Processor prive5 WPrand specific featuresControl Value 3.4. Express Signed, TRNMaximum trob powe5 WPrand specific technologiesControl Value 3.4. Express Signed, TRNNeural processor unit INPUItel Al BootNumber of battary cells3 (4)Spanishy support1.4. GH2Battary voltage1.A. VSpanishy support1.4. GH2Battary voltage1.A. VStaffware financias Signed Financias1.A. V1.A. VStaffware financias Signed Financias1.A. V1.A. VStaffware financiasVersite Value 3.4. Signed Financias1.A. VStaffware financiasVersite Value 3.4. Signed Financias1.A. VMonory Staff CalcuesVersite Value 3.4. Signed Financias1.A. VMemory Staff Calcues2.A. Calagater Inequency0.A. Calagater Inequency1.D. 2.A. VMemory Staff Calcues Staff2.S. Sol-DMMCalagater Inequency1.D. 2.A. VMemory Staff Calcues Staff2.S. Sol-DMMCalagater Inequency1.D. 2.A. VMemory Staff Calcues Staff2.S. Sol-DMMCalagater Inequency1.D. 2.A. VStaff Calcues Staff3.S. Sol-DMMSol-DMM2.A. VStaff Calcues Staff3.S. Sol-DMMSol-DMM3.S. Sol-DMMStaff Calcues Staff3.S. Sol-DMMSol-DMM<	Processor cache		Copilot+ PC	1
Industation labs point21 of Parial specific technologiesCarrol Vail 2+ Spreaschange Battery concertsCarrol Vail 2+ Spreaschange Battery concertsCarrol Vail 2+ Spreaschange Battery concertsSattery concertsSatter			Brand-specific features	
Name processor unit (NPU)Intel A BootsBatteryBoots capable, Expression in (NPNeural processor unit (NPU)Intel A BootsBattery volage3Spanidy support-Battery volage1Spanidy support-Battery volage1A software frameworks supported-Battery volage1Name of battery volage11.4 VASoftware frameworks supported-Battery volage1Namework frameworks supportedDirectyll, ONIX RT, OpenVINO, Window RM.Battery volage indicator-Memory16 GBDORS SDRAMMemory function50 DIMMemory function50 DIMMemory function50 DIMMemory function50 DIMCadapter fraguncy50 - 60 HzMemory function2 x 8 GBA C adapter fraguncy50 - 60 HzMemory function2 x 8 GBCadapter fraguncy50 - 60 HzMemory function2 x 8 GBCadapter fraguncy50 - 60 HzMemory function2 x 8 GBCadapter fraguncy50 - 60 HzSoftrage capacity *512 GBCable lock sist-Softrage capacity *512 GBCable lock sist-Total storage capacity *512 GBFace recognition-Softrage capacity *512 GBFace recognition-Softrage capacity *12 Sarge eating storage carditer humidity (HH)0 - 55'CSoftrage capacity *Net wolage-<	·			Control Vault 3+ Express Charge
Neural processor unit (NPU)Intel Al BoostBattery Pactage and the set of	·	57 W	Brand specific technologies	
Maximum frequency NPU1.4 GHzNumber of battery cells3 defery applicationSparsity support-Gattery vorbage1.1.4 VSparsity support-Battery vorbage1.1.4 VMindows Stulio effects support-Stattery recharge time4.A) software frameworks supportDirectML, OMNK RT, OpenVINO, windows MLFact charging indicators-Internal memory framemory16 GBDirectML, OMNK RT, OpenVINO, windows MLStattery veriphical200 cInternal memory framemory16 GBDirectML, OMNK RT, OpenVINO, windows MLStattery veriphical50 - 00 NzMemory Joby Chifsts x Size)20 DDBS, SDRAMAC adapter fragment50 - 00 NzStattery veriphicalMemory Joby Chifsts x Size)20 DDBS, SDRAMCA dapter fragment50 - 00 NzStattery veriphicalMemory Joby Chifsts x Size)20 DDBS, SDRAMCA dapter fragment50 - 00 NzStattery veriphicalMemory Jobs Chifsts50 DO MTAUSB Chargine Chifsts% Operation\$-15.20 VStorage mediaSDO MTACalele lock sist typeWedgeTotal storage capacity512 GBFace recognition% OperationSD capacity512 CBFace recognition% OperationSD capacity12 CBFace recognition% OperationSD capacity2320 (22 x 30 mm)Calele lock sist% Operation gatherySD form factorFilles press 4.0Natetery press 4.0% Operation gatherySD form factorM2Operation gather	•		Battery	
Sparsity supportBattery capacity *54WhWindows Studio effects supportI.4 vBattery vicelarge time4 hA software frameworks support ofFast chargingWindows MLBattery recharge time4 hBattery vicelarge time4 hWindows MLBattery recharge time4 hWindows MLSoloma2 sWindows MLSolomaA clashter frequency50 hWindows MLSolomaA clashter power65 WWindows MLSolomaA clashter frequency50 hWindows MLSolomaA clashter frequency50 hMamony Jont (istis x size)2 x SO-01MMA clashter frequency50 hMatinum internal memory M64 GUSB Type-C charging port50 hMattery CapacityS12 GBCable lock slot typeVedgeStorage madia *SD ConceFrace recognition4Total storage capacityS12 GBFrace recognition2.0SD capacityS12 GBFrace recognition4SD capacityS12 GBFrace recognition4SD capacityS12 GBFrace recognition4SD capacityS12 GBFrace recognition4SD capacityS12 GB <td>•</td> <td></td> <td>Number of battery cells</td> <td>3</td>	•		Number of battery cells	3
Windows Studie effects support· · · · · · · · · · · · · · · · · · ·			Battery capacity *	54 Wh
Alsoftware frameworks supported by NPUDirect Query NU, Qu		-		
by NPUWindows Mt.Pastery Arage Indicator Battery Arage Indicator Battery Arage Indicator Battery weight20 gHemany16 G8SoverInternal memory typeDDR5 SONAMAC adapter prover65 WMemory for Inderof2 x 8 GBAC adapter indru voltage00 -24 O VMemory logiot2 x 8 GBAC adapter indru voltage00 -24 O VMemory slots2 x 8 GBAC adapter indru voltage50.16 N/CMemory slots2 x 8 GBAC adapter indru voltage5.9.15.20 VMemory slots6 G8USB Type-C charging port -9.0100000000000000000000000000000000000		-	, ,	
MemoryJa G8 burneral memory 'vpeBattery weight220 ginternal memory 'vpeDDRS-SDRAMPowerMemory loyot (disx size)SD-00 MMA Cadapter frequency50 - 60 HzMemory loyot (disx size)X 8 G8M Cadapter frequency50 - 60 HzMemory loyot (disx size)X 8 G8W Stargin voltage10 - 240 VMemory loyot (disx size)So - 50 MKM Cadapter frequency50 - 60 HzMemory dist diransfer rateSo Do DIMMCadapter frequency50 - 60 HzStorage capacity *S12 G8USB Anergin voltage9,15.20 VStorage capacityS12 G8Cable lock slot typeWedgeTotal Storage capacityS12 G8Face recognition4S50 capacityS12 G8Face recognition4S50 capacityS12 G8Face recognition4S50 capacityS12 G8Face recognition2.0S50 fartaficePCI Express 4.0Trusted Platform Module (TPM)2.0NVMe2230 (22 x 30 mm)Operating relative humidity (HH)10 - 90%Maximum intercal memory 'upeNStorage relative humidity (HH)10 - 90%On-board graphics card modelNatapacityStorage relative humidity (HH)10 - 90%On-board graphics card×Storage relative humidity (HH)10 - 90%On-board graphics card fomilyIntel GraphicsNon-operating altitude15.2 - 3048 mOn-board graphics card fomilyIntel GraphicsOperating shock110 GOn-board graphics card fo	by NPU		5 5	
Internal memory *16.68PowerMemory form factorSO-DIMMAC adapter powerSO * 60 HzMemory logout (side x size)2.x 8.6 BAC adapter input voltage100 - 240 VMemory logout (side x size)2.x 8.0 DIMMAC adapter input voltage100 - 240 VMaximum internal memory *64.0 BUSB Type-C charging port *-Memory data transfer rate5600 MT/sSOB charging voltage5.0 VStorageSobia for Size VSobia charging voltage*Total storage capacity *512.0 GBCable lock slot typeWedgeTotal storage capacity *512.0 GBFingerprint reader-Storage media *SDDCable lock slot typeWedgeTotal SDS capacity512.0 GBFingerprint reader-SD charger typeTLCTrusted Platform Module (TPM)-SD form factorM2Sessord protection-SD form factorM2Sessord protection-MYMe-Sorage temperature (T-T)0 - 35 °CSorage temperature (T-T)0 - 35 °C-Sorage temperature (T-T)0 - 65 °CDiscrete graphics card model *Not availableOperating temperature (T-T)0 - 65 °COn-board Graphics card familyIntel GraphicsOperating altitudeOn-board Graphics card familyIntel GraphicsOperating shock110 GOn-board Graphics card familyIntel GraphicsOperating shock110 GOn-board Graphics card familyV	Memory			
Internal memory typeDUS-SDRAMAC adapter power5 WMemory fur factorSO-DIMMAC adapter frequency50 e0 MzMemory layout (slots x size)2 x SO-DIMMAC adapter finput voltage100 - 240 VMemory slots2 x SO-DIMMAC adapter input voltage50 e0 MzMemory data transfer rate500 UMTsUSB trype-C harging port **Storage512 GBCable lock slot trypeWedgeTotal storage capacity512 GBCable lock slot trypeWedgeTotal storage capacity512 GBFace recognition*StorageFLCSmart card reader*SSD memory typeTLCTrusted Platform Module (TPM)*SSD factorPLE spress 4.0Trusted Platform Module (TPM)*SSD form factorM2Sward are recognition*SSD form factorM2Storage transfer rate*SD form factorM2Storage transfer rate*SD form factorM2Storage transfer rate*SD form factorM2Storage transfer rate*SD form factorM2Operating temperature (T-T)*Optical direk bypeNot availableOperating altitude*On-baard graphics card modelNot apperating vibration**On-baard graphics card modelNot operating altitude**On-baard graphics card modelNot operating altitude**On-baard graphics card modelNot operating vibration** <td>Internal memory *</td> <td>16 GB</td> <td>Battery weight</td> <td>220 g</td>	Internal memory *	16 GB	Battery weight	220 g
Inclusion beamony layout (sloits x size)2 x B GB 2 x B GB A C adapter input voltage100 - 24 V VMemory layout (sloits x size)2 x B GB x AC adapter input voltage100 - 24 V VMemory layout (sloits x size)2 x B GBAC adapter input voltage100 - 24 V VMaximum internation64 GBUSB Typec C charing poly of the size500 VStorage endal550 O MT/sUSB charging voltage5,01 VStorage endal512 GBCable lock slot typeVedgeTotal storage capacity512 GBFingerprint reader4Storage media512 GBFingerprint reader4SSD capacity512 GBFace recognition4SSD capacity512 GBFace recognition2.0SSD interfacePCI Express 4.0Trusted Platform Module (TPM)4SSD interface2230 (22 x 30 mm)Qerational conditions3.0SSD form factorM.2Password protection4.05.0Orbeard Graphics card modelNot availableOperating temperature (T-T)4.04.0On-board graphics card modelNot availableOperating altitude1.5.23.04 MOn-board graphics card modelNot availableOperating shock10.0 G3.0On-board graphics card familyIntel GraphicsNon-operating shock10.0 G3.0On-board graphics card modelNot availableNon-operating shock10.0 G3.0On-board graphics card familyIntel GraphicsNon-operating shock10.0 G3.	Internal memory type	DDR5-SDRAM	Power	
Interface Memory isolation Memory isolation Maximum internal memory2 x S0-DIMA Memory isolation S0 Kerriging port*100 - 240 VMaximum internal memory Memory data transfer rate5600 MT/sUSB Type-C tharging port*VStorage Memory data transfer rate5600 MT/sUSB Type-C tharging port*VStorage media *520 GAUSB Charging voltages5,15.2 VStorage media *SDCable lock slot typeWedgeStorage media *SDCable lock slot typeWedgeStorage media *SDSDCable lock slot typeWedgeSD capacity512 GBFingeronin readerSD capacityS12 GBFingeronin readerSD memory typeTLCTrusted Platform Module (TPM)2.0SD form factorM.2Password protectionSD form factorM.2Password protectionSD form factorNoParating temperature (T-T)0.40 -65 *COptical drive type*Not availableOperating lettidue10.2 · 0.40 · 65 *COptical drive type*Not availableOperating lettidue10.9 · 0.5 ·	Memory form factor	SO-DIMM		
Name of the set o	Memory layout (slots x size)	2 x 8 GB		
Memory data transfer rate5600 MT/sUSB charging voltage5,15,20 VStorageSecuritySecurityTotal storage capacity12 GBCable lock slot typeWedgeTotal SDS capacity512 GBCable lock slot typeWedgeTotal SDS capacity12 GBFingerprint reader<	Memory slots			
Storage Security Total storage capacity * 512 GB Cable lock slot ✓ Storage media * SSD Cable lock slot ✓ Total SSD capacity 512 GB Fingerprint reader ✓ Number of SSDs installed 1 Smart card reader ✓ SSD capacity 512 GB Face recognition ✓ SSD interface PCI Express 4.0 Trusted Platform Module (TPM) ✓ SSD form factor M.2 Password protection ✓ SSD form factor M.2 Password protection ✓ Operating temperature (T-T) -0.55 °C Storage relative humidity (H+H) 0.95% On-board graphics card model * Nat available Operating relative humidity (H+H) 0.95% On-board graphics card * × Non-operating slitude 1.5.2 · 3048 m On-board graphics card * × Non-operating slock 110 G On-board graphics card model * Intel Graphics Operating slock 100 G On-board graphics card family Intel Graphics Operating vibration			,	
Total storage capacity512 GBCable lock slot·Storage mediaSSDCable lock slot typeWedgeTotal SSDs capacity512 GBFingerprint reader·SSD capacity512 GBFace recognition·SSD capacity512 GBFace recognition·SSD capacity512 GBFace recognition·SSD interfacePCI Express 4.0Trusted Platform Module (TPM)·NVMe···SSD interfaceM.2Password protection·A2 SSD size2330 (22 x 30 mm)Password protection·Operating temperature (T-T)0 - 35 °C·Storage temperature (T-T)0 - 65 °C·Operating temperature (T-T)0 - 65 °C·Operating relative humidity (H-H)0 - 90%·On-board GPuincs card model *Not availableOperating relative humidity (H-H)0 - 95%On-board graphics card familyIntel GraphicsOperating slitude-15.2 - 1066B mOn-board graphics card familyIntel GraphicsOperating slock110 GOn-board graphics card familyIntel GraphicsOperating slock100 GAudio systemMaxsAudio ProCertificates-Number of built-in speakers2Compliance certificates-Speaker power2 WWedee1.12 mm-Built-in microphone2 WWidth3.21 mm-Number of built-in speakers2 ComplianceSp		5600 MI/S		5,9,15,20 V
Storage media*SSDGale lock slot typeWedgeTada SSD capacityS12 GBFingerprint raderNumber of SSDs installed12 GBFinder of rader of excercipationSSD capacityS12 GBTusted Platform Module (TPM)SSD memory typeCTusted Platform Module (TPM)SSD form factorM2Sessword proteinSSD form factorM2Sessword proteinSSD form factorM2Sessword proteinSD form factorNativalbleOperating relative humidity (H)Discrete graphics card modelNativalbleOperating radiute/ humidity (H)On-board GPU manufactureNativalbleOperating shortOn-board graphics card modelNativalbleNon-operating altudeOn-board graphics card modelNativalbleNon-operating altudeOn-board GPU manufactureNativalbleNon-operating altudeNumber of building spaceNativalbleNon-operating altudeNumber of building spaceNativalbleNon-operating altudeNumber of building spaceNativalbleNon-operating altudeNumber of bui	•		-	
Total SSDs capacity512 GBFingerprint reader×Number of SSDs installed1Smart card reader×SSD capacity512 GBFace recognition×SSD capacityTLCFrusted Platform Module (TPM)×SSD interfacePCI Express 4.0Trusted Platform Module (TPM)×NVMe×*Password protection2.0SSD interfaceM.2Password protection0.35 °CSSD form factorM.2Perational Condition0.35 °CM2 SSD Size2230 (22 x 30 mm)0.95 °CStorage temperature (T-T)0.35 °COptical drive type*×Operating relative humidity (H-H)0.95%On-board graphics card model *Not availableOperating relative humidity (H-H)0.95%On-board GPU manufacturerIntelOperating relative humidity (H-H)0.95%On-board graphics card familyIntel GraphicsNon-operating altitude15.2 · 1066B mOn-board graphics card familyIntel GraphicsNon-operating shock100 GOn-board graphics card familyIntel GraphicsNon-operating vibration1.3 GNumber of built-in speakers2Compliance certificatesEcoleginSpeaker power2VWaresSecond Compliance1.9 CmSpeaker power2Non-operating vibration3.21.4 mmNumber of built-in speakers2Compliance certificatesEcoleginSpeaker power2Non-operating vibration3.21.4 mmNumber of				
Number of SSDs installed1Image of readerSSD capacity512 GBSmart card readerSSD capacity121 GBFace recognitionSSD interfacePCE kpress 4.0Trusted Platform Module (TPM)NVMeSSD form factorM.2Password protection2.0SSD form factorM.2Password protectionM.2 SSD size2230 (22 x 30 mm)Operating temperature (T-T)0.35 °COptical drive type *XOperating temperature (T-T)0.35 °CObjected graphics card model *Not availableOperating reliable humidity (H-H)10 - 90%On-board graphics card *Not availableOperating altitude15.2 · 3048 mOn-board graphics card familyIntel GraphicsOperating shock110 GOn-board graphics card familyIntel GraphicsOperating shock100 GOn-board graphics card familyIntel GraphicsOperating shock10 GOn-board graphics card familyIntel GraphicsOperating shock10 GOn-board graphics card familyIntel GraphicsOperating shock10 GAudio SystemMaxAudio ProNon-operating wibration1.3 GNumber of microphones2Curtificates21 rumSpeaker power2Width321.4 mmJumer of microphones2Width1.91 cmSpeaker power2.0 XIMPWidth2.1 cmSpeaker power2.0 XIMP1.91 cm21 rum <t< td=""><td>5</td><td></td><td></td><td>5</td></t<>	5			5
SD capacity512 GBFace recognitionImage: Instance of recognitionSD memory typeTLCFace recognitionImage: Instance of recognitionSD memory typeTLCTrusted Platform Module (TPM)Image: Instance of recognitionSD interfaceM2Trusted Platform Module (TPM)Image: Instance of recognitionSD form factorM.2Password protectionImage: Instance of recognitionM2 SSD size230 (22 x 30 mm)Operation temperature (TT)0 - 35 °COptical drive type *XOperating temperature (TT)0 - 35 °CGraphicsNot availableOperating relative humidity (H+)10 - 90%On-board graphics card model *Not availableOperating relative humidity (H+)10 - 90%On-board graphics card familyIntel GraphicsOperating relative humidity (H+)10 - 90%On-board graphics card familyIntel GraphicsOperating relative humidity (H+)10 - 90%On-board graphics card familyIntel GraphicsOperating shock110 GOn-board graphics card familyIntel GraphicsOperating vibration0.66 GAudio systemMaxAudio ProCompliance certificatesEcoDesignNumber of built-in speakers2Compliance certificatesEcoDesignSpeaker snaufacturerVWight1.12 cmSpeaker snaufacturer2Might Grant1.12 cmSpeaker snaufacturer2Might Grant1.12 cmSpeaker snaufacturer1.07 MPPielt ffront)1.12 cmF				
SSD memory typeTLCFace recognitionProde recognition </td <td></td> <td></td> <td></td> <td></td>				
SbD interfacePCI Express 4.0Trusted Platform Module (TPM) version2.0NVMePassword protection2.0MZ SSD form factorM.2Password protectionM2 SSD size230 (22 x 30 mm)Operating temperature (T-T)0.35 °CGraphicsXOperating temperature (T-T)0.40 - 65 °CDiscrete graphics card model *Not availableOperating relative humidity (H-H)0.90%On-board graphics card familyIntel GraphicsOperating relative humidity (H-H)0.95%On-board graphics card familyIntel GraphicsOperating altitude15.2 - 3048 mOn-board graphics card familyIntel GraphicsOperating altitude10.0 GOn-board graphics card model *Intel GraphicsOperating shock100 GOn-board graphics card familyIntel GraphicsOperating vibration0.66 GOn-board graphics card model *Non-operating shock13.0 GOn-board graphics card model *Nacxaudio Pro1.3 GAudio systemVavesCompliance certificatesEcoDesignNumber of built-in speakers2Vares21.4 mmSpeaker power2Wats21.2 mm21.4 mmNumber of microphone2Versign21.4 mmNumber of microphones2Wats21.4 mmNumber of microphones2Wats21.4 mmFront camera resolution (numeri1.90 NM21.4 mmFront camera resolution (numeri1.90 NM21.4 mm<	SSD memory type	TLC	-	
NVMeVversion2.0SSD form factorM.2Password protectionVM.2 SSD Size2230 (22 x 30 mm)Operation for potectionVOptical drive type *XOperating temperature (T-T)0 - 35 °CGraphicsNot availableOperating relative humidity (H-H)0 - 95%On-board graphics card *VStorage relative humidity (H-H)0 - 95%On-board graphics card *YNon-operating altitude-15.2 - 3048 mOn-board graphics card *XNon-operating shock10 6On-board graphics card familyIntel GraphicsOperating shock100 GOn-board graphics card familyIntel GraphicsOperating shock100 GNumber of built-in speakers2Certificates2Speaker power2 WWavesCompliance certificates21.4 mmBuilt-in microphone2Width21.4 mm21.4 mmNumber of microphones2.0 TMPHeight (rear)2.1 cmFront camera ersolution (numeric)2.07 MPCarbon footprint2.1 cmFront camera resolution (numeric)1.02 MIHTotal carbon footprint (kg of CO2e)111Video capturing speed30 fpsCarbon emissions, manufacturing (kg of CO2e)111 <td>SSD interface</td> <td>PCI Express 4.0</td> <td></td> <td></td>	SSD interface	PCI Express 4.0		
Password protectionPassword prote	NVMe	1		2.0
Optical drive type*×Operational conditionsGraphicsOperating temperature (T-T)0 - 35 °CDiscrete graphics card model*Not availableOperating relative humidity (H-H)0 - 90%On-board graphics card *×Storage relative humidity (H-H)0 - 90%On-board GPU manufacturerIntelOperating relative humidity (H-H)0 - 95%Discrete graphics card *×Non-operating altitude-15.2 - 3048 mOn-board graphics card familyIntel GraphicsOperating shock100 GOn-board graphics card familyIntel GraphicsOperating shock100 GOn-board graphics card familyIntel GraphicsOperating shock100 GOn-board graphics card familyIntel GraphicsOperating vibration0.66 GNumber of built-in speakers2Certificatesiso GSpeaker power2VVVSylask power2Width321.4 mmNumber of microphones2Width1.91 cmPront camera resolution (numeri Front camera resolution (numeri Full HDCarbon footprint1.4 cmVideo capturing speedSolo (post Front camera resolution (numeri Full HDTotal carbon footprint (kg of CO2e)111Video capturing speed30 fpsCarbon emissions, manufactureri (kg of CO2e)111Video capturing speed30 fpsCarbon emissions, manufacturi (kg of CO2e)11			Password protection	1
Operating typeAGraphicsOperating temperature (T-T)-40 - 65 °CDiscrete graphics card model *Not availableOperating relative humidity (H-H)10 - 90%On-board graphics card *-Storage relative humidity (H-H)0 - 95%On-board GPU manufacturerIntelOperating altitude-55.2 - 3048 mDiscrete graphics card *XNon-operating altitude-15.2 - 10668 mOn-board graphics card familyIntel GraphicsOperating shock110 GOn-board graphics card familyIntel GraphicsOperating shock100 GOn-board graphics card model *Intel GraphicsNon-operating shock10.0 GOn-board graphics card model *Intel GraphicsOperating vibration0.66 GAudio systemMaxxAudio ProCardificatesEcoDesignNumber of built-in speakers2Compliance certificatesEcoDesignSpeaker smanufacturerVavesCompliance certificatesEcoDesignSubtin microphone2Width321.4 mmNumber of microphones2Pepth112 mmFront camera resolution (numeri)207 MPWeight "ran"1.4 kgFront camera resolution (numeri)1920 x 1080 pixelsCarbon footprint (kg of CO2e)111Yideo capturing speed30 fpsCarbon missions, manufacturing81Yideo capturing speed30 fpsCarbon emissions, manufacturing81Yideo capturing speed30 fpsCarbon emissions, manufacturing81			Operational conditions	
Graphics Storage temperature (T-T) 40 - 65 °C Discrete graphics card model * Not available Operating relative humidity (H-H) 10 - 90% On-board graphics card * ✓ Storage relative humidity (H-H) 0 - 95% On-board GPU manufacturer Intel Operating relative humidity (H-H) 0 - 95% On-board GPU manufacturer Intel Operating glittude -15.2 - 3048 m Discrete graphics card * × Non-operating altitude -15.2 - 10668 m On-board graphics card family Intel Graphics Operating shock 110 G On-board graphics card model * Intel Graphics Operating shock 100 G On-board graphics card model * Intel Graphics Non-operating shock 100 G On-board graphics card model * Intel Graphics Operating vibration 0.66 G Autio MaxxAudio Pro Discrete graphics Seesker Number of built-in speakers 2 Compliance certificates EcoDesign Speaker power 2 W Weight & dimensions 21.4 mm Number of microphones 2 N Depth 212 mm Romar - Height (rear) 2.1 cm Front camera resolution (numeric 2.07 MP Meight frear) 1.4 kg <		×	-	0 - 35 °C
Discrete graphics card model*Not availableOperating relative humidity (H-H)10 - 90%On-board graphics card *Storage relative humidity (H-H)0 - 95%On-board GPU manufacturerIntelOperating altitude-15.2 - 3048 mDiscrete graphics card *XNon-operating altitude-15.2 - 10668 mOn-board graphics card familyIntel GraphicsOperating yibration-15.2 - 10668 mOn-board graphics card familyIntel GraphicsOperating yibration-16.0 GOn-board graphics card familyIntel GraphicsOperating yibration-6.6 GAutioMaxAudio Pro-0.6 G-0.6 GNumber of builtin speakersQavesCompliance certificates-0.6 Operating yibrationSpeaker power2WCompliance certificatesEcoDesignNumber of microphone2-0.6 Operating vibration-21.2 mmNumber of microphone2-0.6 Operating vibration21.4 mmNumber of microphone2-0.6 Operating vibration21.4 mmNumber of microphone2-0.6 Operating vibration21.2 mmFront camera<-0.7 MP	Graphics			
On-board GPU manufacturerIntelOperating altitude-15.2 - 3048 mDiscrete graphics card *×Non-operating altitude-15.2 - 10668 mOn-board graphics card familyIntel GraphicsOperating shock110 GOn-board graphics card model *Intel GraphicsOperating shock160 GAudioIntel GraphicsNon-operating shock160 GAudio systemMaxAudio Pro0.66 GNumber of built-in speakers2CertificatesSpeaker smanufacturerWavesCompliance certificatesEcoDesignSpeaker power2Weight & dimensionsBuilt-in microphone<	Discrete graphics card model *	Not available		10 - 90%
Discrete graphics card **XNon-operating altitude13.2 - 5 060 mDiscrete graphics card **XNon-operating altitude-15.2 - 10668 mOn-board graphics card familyIntel GraphicsOperating shock110 GOn-board graphics card model **Intel GraphicsNon-operating shock160 GAudioVerating vibration0.66 GAudio systemMaxAudio Pro0.66 GNumber of built-in speakers2Certificatesteroperating vibrationSpeaker power2 WavesCompliance certificatesteroDesignBuilt-in microphone-WavesCompliance certificates21.4 mmNumber of microphones2Width321.4 mmNumber of microphones2Pepth21.2 mmFront camera-Height (front)1.91 cmFront camera resolution (numeric)2.07 MPHeight (rear)2.1 cmFront camera resolution1920 x 1080 pixelsCarbon footprint1.4 kgFront camera HD typeFull HDTotal carbon footprint (kg of CO2e)111Video capturing speed30 fpsGarbon emissions, manufacturing (kg of CO2e)81	5 1		Storage relative humidity (H-H)	0 - 95%
On-board graphics card family On-board graphics card model*Intel GraphicsOperating shock110 GAudioIntel GraphicsNon-operating shock160 GAudio systemMaxxAudio ProNon-operating vibration1.3 GNumber of built-in speakers2CertificatesEcoDesignSpeaker smanufacturerWavesCompliance certificatesEcoDesignBuilt-in microphone2Weight & dimensions321.4 mmNumber of microphones2Width321.4 mmNumber of microphones2Height (front)1.91 cmFront cameraI2.07 MPHeight (rear)1.91 cmFront camera resolution (numeric)1.920 x 1080 pixelsCarbon footprint (kg of CO2e)111Front camera HD typeFull HDTotal carbon footprint (kg of CO2e)111Video capturing speed30 fpsGarbon emissions, manufacturing kg of CO2e)111				
On-board graphics card model *Intel GraphicsNon-operating shock160 GAudioMaxAudio ProOperating vibration0.66 GAudio systemMaxxAudio Pro1.3 GNumber of built-in speakers2CertificatesEcoDesignSpeaker smanufacturerWavesCompliance certificatesEcoDesignSpeaker power2 WWeight & dimensions201.4 mmBuilt-in microphoneWidth321.4 mmNumber of microphones2Weight (front)1.91 cmFront cameraHeight (front)1.91 cmFront camera resolution (numeri)2.07 MPWeight *1.4 kgFront camera resolution1920 x 1080 pixelsCarbon footprint (kg of CO2e)111Video capturing speed30 fpsGarbon emissions, manufacturing kg of CO2e)311Video capturing speed30 fpsGarbon emissions, manufacturing kg of CO2e)311Marcot for the cameraKeine for the camera311Marcot for the cameraKeine for the camera311Marcot for the cameraKeine for the camera311Marcot for the cameraKeine for the c				
AudioOperating vibration Non-operating vibration0.66 G Non-operating vibrationAudio systemMaxAudio Pro1.3 GNumber of built-in speakers2CertificatesEcoDesignSpeakers manufacturerWavesCompliance certificatesEcoDesignSpeaker power2Weight & dimensionsS21.4 mmBuilt-in microphone4Width321.4 mmNumber of microphones2Depth212 mmFont cameraHeight (rear)1.91 cmFront camera resolution (numeri1.92 x 1080 pixelsHeight (rear)1.4 kgFront camera HD typeFull HDTota carbon footprint (kg of CO2e)1.1Video capturing speed30 fpsGroben emissions, manufacturing Kg of CO2e81		•		
AutioNon-operating vibration1.3 GAudio systemMaxxAudio ProCertificates1.3 GNumber of built-in speakers2CertificatesEcoDesignSpeakers manufacturerWavesCompliance certificatesEcoDesignSpeaker power2 WWeight & dimensionsS21.4 mmBuilt-in microphone-WidthS21.4 mmNumber of microphones2Depth212 mmCamera-Height (rear)1.91 cmFront camera.Non-operating vibration1.4 kgFront camera Aub type1.92 x 1080 pixelsCertificates1.4 kgFront camera HD typeFull HDTotal carbon footprint (kg of CO2)1.11Video capturing speed.S0 fpsarbon emissions, manufacturen8.1Infrared (IR) cameraInfrared (IR		inter oraphies		
Number of built-in speakers2CertificatesCertificatesEcoDesignSpeaker power2Compliance certificatesEcoDesignBuilt-in microphone2Meight & dimensions21.4 mmNumber of microphones2With21.4 mmNumber of microphones2Deph22 mmFornt camera1.91 cm1.91 cmFront camera resolution (numeric)2.07 MPWeight Franc1.4 kgFront camera resolution (numeric)1.920 x1080 pixelsCertor fortophone fortophone for the specific fortophone for the specific fortophone for the specific fortophone for the specific fort fort fortophone for the specific fort fort fort fort fort fort fort fort				
Number of building peakers2Conspiance certificatesEcoDesignSpeakers manufacturerWavesCompliance certificatesEcoDesignSpeaker power2Weight & dimensionsSeaker powerBuilt-in microphoneMidth321.4 mmNumber of microphones2Depth212 mmCameraHeight (front)1.91 cmFront cameraHeight (rear)2.1 cmFront camera resolution (numeric)2.07 MPWeight *1.4 kgFront camera resolution1920 x 1080 pixelsCarbon footprint (kg of CO2e)111Front camera HD typeFull HDTotal carbon footprint (kg of CO2e)111Video capturing speed30 fpsCarbon emissions, manufacturing (kg of CO2e)81			Certificates	
Speaker power2 WWeight & dimensionsBuilt-in microphonesIWidh32.4 mmNumber of microphones2Deth212 mmCameraIHeight (front)1.91 cmFront cameraIPom2.1 cmFront camera resolution (numeric)1.92 x 1080 pixelsWeight *1.4 kgFront camera HD typeHull HDTotal carbon footprint (kg of CD2)1.1Front camera (kg, camera)JongArbon emissions, manufacturing1.1Front camera (kg, camera)ISetter (kg, camera)1.1Front cameraISetter (kg, camera)1.1Front cameraISetter (kg, camera)1.1Front cameraISetter (kg, camera)1.1Front cameraISetter (kg, camera)1.1	•			EcoDesian
Built-in microphoneImage: Constraint of the section of t			•	Leobesign
Number of microphones2Depth212 mmCameraHeight (front)1.91 cmFront camera✓Height (rear)2.1 cmFront camera resolution (numeri)2.07 MPWeight *1.4 kgFront camera resolution1920 x 1080 pixelsCarbon footprint (kg of CO2e)111Front camera HD typeFull HDTotal carbon footprint (kg of CO2e)111Video capturing speed✓✓Carbon emissions, manufacturing (kg of CO2e)81	Built-in microphone			221 4 mm
CameraHeight (front)1.91 cmFront cameraImage: Arrow of the sector o	Number of microphones	2		
Front cameraImage: Cambon cameraHeight (rear)2.1 cmFront camera resolution (numeric)2.07 MPWeight *1.4 kgFront camera resolution1920 x 1080 pixelsCarbon footprint1.4 kgFront camera HD typeFull HDTotal carbon footprint (kg of CO2e)111Video capturing speed30 fpsCarbon emissions, manufacturing kg of CO2e)81	Camera		· ·	
Front camera resolution (numeric)2.07 MPWeight *1.4 kgFront camera resolution1920 x 1080 pixelsCarbon footprintImage: Carbon footprint (kg of CO2e)Image: Carbon emissions, manufacturing of CO2eFront camera HD typeFull HDTotal carbon emissions, manufacturing of CO2eImage: Carbon emissions, manufacturing of CO2eImage: Carbon emissions, manufacturing of CO2eInfrared (IR) cameraImage: Carbon emissions, manufacturing of CO2eImage: Carbon emissions, manufacturing of CO2eImage: Carbon emissions, manufacturing of CO2e	Front camera	1	-	
Front camera resolution1920 x 1080 pixelsCarbon footprintFront camera HD typeFull HDTotal carbon footprint (kg of CO2e)111Video capturing speed30 fpsCarbon emissions, manufacturing (kg of CO2e)81	Front camera resolution (numeric)		Weight *	1.4 kg
Front camera HD typeFull HDTotal carbon footprint (kg of CO2e)111Video capturing speed30 fpsCarbon emissions, manufacturing (kg of CO2e)81Infrared (IR) camera(kg of CO2e)111	Front camera resolution		Carbon footprint	
Video capturing speed30 fpsCarbon emissions, manufacturing (kg of CO2e)81	Front camera HD type	Full HD		111
Infrared (IR) camera 🗸 (kg of CO2e)	Video capturing speed	30 fps	Carbon emissions, manufacturing	81
Privacy camera 🗸	Infrared (IR) camera	1	(kg of CO2e)	
	Privacy camera	1		

Camera		Carbon footprint	
Privacy type	Privacy shutter	Carbon emissions, logistics (kg of CO2e)	4
		Carbon emissions, energy usage (kg of CO2e)	24
		Carbon emissions, end-of-life (kg of CO2e)	2
		Total carbon emissions, w/o use phase (kg of CO2e)	87
		PAIA version	GaBi version 1, 2024
		Packaging content	
		Cables included	AC



5397184828212

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.