

## DELL Pro 24 Plus USB-C Hub Monitor P2425E computer monitor 61.1 cm (24.1") 1920 x 1200 pixels WUXGA LCD Black

Brand : DELL

Product code: DELL-P2425E

Product name : Pro 24 Plus USB-C Hub Monitor P2425E

- 61.1cm (24.07") WUXGA 1920 x 1200 LED IPS

- 8ms, 16:10, 300cd/m<sup>2</sup>, 1500:1

- USB, HDMI, DisplayPort

61.1cm (24.07") WUXGA 1920 x 1200 LED IPS, 16:10, 300cd/m<sup>2</sup>, 16.7M, 8ms, 178°/178°, 1500:1

DELL Pro 24 Plus USB-C Hub Monitor P2425E computer monitor 61.1 cm (24.1") 1920 x 1200 pixels WUXGA LCD Black:

Certified by TÜV for 4-star eye comfort, this 16:10 hub monitor offers enhanced visual comfort and offers up to 90W of power delivery.


DELL Pro 24 Plus USB-C Hub Monitor P2425E. Display diagonal: 61.1 cm (24.1"), Display resolution: 1920 x 1200 pixels, HD type: WUXGA, Display technology: LCD, Response time: 8 ms, Native aspect ratio: 16:10, Viewing angle, horizontal: 178°, Viewing angle, vertical: 178°. Built-in USB hub, USB hub version: 3.2 Gen 1 (3.1 Gen 1). VESA mounting, Height adjustment. Product colour: Black





| Display                        |   | Ergonomics                                |               |
|--------------------------------|---|---|---------------|
| Display diagonal *             | 61.1 cm (24.1")   | Pivot angle                               | -90 - 90°     |
| Display resolution *           | 1920 x 1200 pixels  | Swivelling                                | ✓ ×           |
| HD type *                      | WUXGA   | Swivel angle range                        | -45 - 45°     |
| Native aspect ratio *          | 16:10   | Tilt adjustment                           |               |
| Display technology *           | LCD   | Tilt angle range                          | -5 - 21°      |
| Panel type *                   | IPS   | 5 5                                       |               |
| LED backlight                  | 1   | On Screen Display (OSD)                   | <i>✓</i>      |
| Backlight type                 | LED   | Plug and Play                             | ✓             |
| Touchscreen *                  | ×   | LED indicators                            | <i>s</i>      |
| Display brightness (typical)   | 300 cd/m²   | Power                                     |               |
| Response time *                | 8 ms  | Energy efficiency class (SDR) *           | D             |
| Anti-glare screen              | 1   | Energy efficiency class (HDR) *           | Not available |
| Screen shape *                 | Flat  | Energy consumption (SDR) per 1000 hours * | 15 kWh        |
| Supported graphics resolutions | 640 x 480 (VGA), 720 x 400, 800 x<br>600 (SVGA), 1024 x 768 (XGA),<br>1152 x 864 (XGA+), 1280 x 1024<br>(SXGA), 1280 x 720 (HD 720), 1600<br>x 1200, 1920 x 1080 (HD 1080), | Power consumption (typical) *             | 15 W          |
|                                |   | Power consumption (standby) *             | 0.3 W         |
|                                |   | Power consumption (max)                   | 190 W         |
|                                | 1920 x 1200 (WUXGA)   | Power consumption (off)                   | 0.3 W         |
| Supported video modes          | 480p, 576p, 720p, 1080p   | AC input voltage                          | 100 - 240 V   |
| Contrast ratio (typical) *     | 1500:1  | AC input frequency                        | 50/60 Hz      |
| Maximum refresh rate *         | 100 Hz  | Input current                             | 2 A           |
| Viewing angle, horizontal      | 178°  | Power supply type                         | Internal      |
| Viewing angle, vertical        | 178°  | Energy efficiency scale                   | A to G        |
| Display number of colours *    | 16.7 million colours  | European Product Registry for             | 1870769       |
| Response time (fast)           | 5 ms  | Energy Labelling (EPREL) code             |               |
| Pixel pitch                    | 0.27 x 0.27 mm  | Operational conditions                    |               |
| Pixel density                  | 94.07 ppi   | Operating temperature (T-T)               | 0 - 40 °C     |
| Horizontal scan range          | 30 - 122 kHz  | Storage temperature (T-T)                 | -20 - 60 °C   |
| Vertical scan range            | 48 - 100 Hz   | Operating relative humidity (H-H)         | 10 - 80%      |

| Display                                     |                            | Operational conditions                           |                           |
|---|----------------------------|--|---------------------------|
| Viewable size, horizontal                   | 51.8 cm                    | Storage relative humidity (H-H)                  | 5 - 90%                   |
| Viewable size, vertical                     | 32.4 cm                    | Operating altitude                               | 0 - 5000 m                |
| Viewable size diagonal                      | 61.1 cm                    | Non-operating altitude                           | 0 - 12192 m               |
| Surface hardness                            | 3H                         | Weight & dimensions                              |                           |
| sRGB coverage (typical)                     | 99%                        | Width (with stand)                               | 531.8 mm                  |
| Dell ComfortView technology                 | ✓                          | Depth (with stand)                               | 181.8 mm                  |
| Performance                                 |                            | Height (with stand)                              | 364 mm                    |
| NVIDIA G-SYNC *                             | ×                          | Weight (with stand)                              | 5.02 kg                   |
| AMD FreeSync *                              | ×                          | Width (without stand)                            | 531.8 mm                  |
| Flicker-free technology                     | ✓                          | Depth (without stand)<br>Height (without stand)  | 50 mm<br>343.7 mm         |
| Low Blue Light technology                   | 1                          | Weight (without stand)                           | 3.51 kg                   |
| Windows operating systems                   | Windows 10, Yes            | Bezel width (side)                               | 6.7 mm                    |
| supported                                   |                            | Bezel width (top)                                | 6.7 mm                    |
| Mac operating systems supported             | MacOS                      | Bezel width (bottom)                             | 1.3 cm                    |
| Multimedia                                  |                            | Packaging data                                   |                           |
| Built-in speaker(s) *                       | ×                          | Package weight                                   | 7.12 kg                   |
| Built-in camera *                           | ×                          | USB cable length                                 | 1 m                       |
| Design                                      |                            | Packaging content                                |                           |
| Product colour *                            | Black                      | Stand included                                   | 1                         |
| Front bezel colour                          | Black                      | Cables included                                  |                           |
| Feet colour                                 | Grey                       | Quick start guide                                | AC, DisplayPort, USB      |
| Ports & interfaces                          |                            | DisplayPort cable length                         | 1.8 m                     |
| Built-in USB hub *                          | 1                          |  | 1.6 111                   |
| USB hub version                             | •<br>3.2 Gen 1 (3.1 Gen 1) | Sustainability                                   |                           |
| Number of USB Type-C upstream               |                            | Sustainability compliance                        | <i>✓</i>                  |
| ports quantity                              | 1                          | Sustainability certificates                      | ENERGY STAR, TCO          |
| USB Type-A downstream ports                 | 3                          | Doesn't contain                                  | Arsenic, Mercury, PVC/BFR |
| quantity<br>USB Type-C downstream ports     |                            | Carbon footprint                                 |                           |
| quantity                                    | 1                          | Total carbon footprint (kg of CO2e)              | 179                       |
| USB Type-C DisplayPort Alternate            | 1                          | Carbon emissions, manufacturing<br>(kg of CO2e)  | 87                        |
| Mode  |                            | Carbon emissions, logistics (kg of               |                           |
| USB Power Delivery (USB PD)                 |                            | CO2e)  | 13                        |
| USB Power Delivery up to                    | 90 W                       | Carbon emissions, energy usage (kg               | 74                        |
| HDMI *<br>HDMI ports quantity               | 1                          | of CO2e)<br>Carbon emissions, end-of-life (kg of |                           |
| HDMI ports quantity                         | 1.4                        | CO2e)  | 5                         |
| DisplayPorts quantity                       | 2                          | Total carbon emissions, w/o use                  | 105                       |
| DisplayPort version                         | 1.4                        | phase (kg of CO2e)                               |                           |
| Headphone out *                             | ×                          | PAIA version                                     | GaBi version 1, 2024      |
| HDCP  | 1                          | Other features                                   |                           |
| HDCP version                                | 1.4                        | RJ-45 ports quantity                             | 1                         |
| AC (power) in                               | ✓                          | Compliance certificates                          | RoHS, TÜV mark            |
| Ergonomics                                  |                            | Brand-specific features                          |                           |
| VESA mounting *                             | 1                          | Dell Display Manager (DDM)                       | 1                         |
| Panel mounting interface                    | 100 x 100 mm               | compatibility                                    |                           |
| Cable management                            | 100 × 100 mm               |  |                           |
| Cable lock slot *                           | -                          |  |                           |
|   |                            |  |                           |
|   | ✓<br>Kensington            |  |                           |
| Cable lock slot type                        | ✓<br>Kensington<br>✓       |  |                           |
| Cable lock slot type<br>Height adjustment * | Kensington                 |  |                           |
| Cable lock slot type                        | Kensington                 |  |                           |





5397184821688

0884116468653



884116468653

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.