

## CyberPower PR3000ERTXL2UAC uninterruptible power supply (UPS) Line-Interactive 3 kVA 300 W 10 AC outlet(s)

**Brand :** CyberPower

**Product code:** PR3000ERTXL2UAC

**Product name :** PR3000ERTXL2UAC



CyberPower PR3000ERTXL2UAC. UPS topology: Line-Interactive, Output power capacity: 3 kVA, Output power: 300 W. AC outlet types: C13 coupler, C19 coupler, Power plug: C20 coupler, AC outlets quantity: 10 AC outlet(s). Battery technology: Sealed Lead Acid (VRLA), Typical backup time at full load: 3.8 min, Typical backup time at half load: 11.2 min. Form factor: Rackmount/Tower, Product colour: Black, Housing material: Metal. Width: 433 mm, Depth: 630 mm, Height: 86.5 mm



Features		Battery	
UPS topology *	Line-Interactive	Number of batteries supported	1
Output power capacity *	3 kVA	Typical backup time at full load	3.8 min
Output power *	300 W	Typical backup time at half load	11.2 min
Waveform *	Pure sine	Battery recharge time	3 h
Input operation voltage (min) *	148 V	Hot-swap battery	✓
Input operation voltage (max) *	288 V	Replacement battery cartridge	BP48VP2U03
Input frequency *	50/60 Hz	Design	
Output operation voltage (min)	220 V	Form factor *	Rackmount/Tower
Output operation voltage (max)	240 V	Housing material	Metal
Output frequency	50/60 Hz	Rack capacity	2U
Output frequency regulation	1 Hz	Extended battery module rack capacity	2U
Output voltage regulation	5%	Cooling type	Active
Automatic Voltage Regulation (AVR)	✓	Built-in fan	✓
Maximum current	16 A	Product colour *	Black
Surge energy rating	2430 J	Control type	Buttons
Response time	6 ms	Display type	LCD
Heat dissipation	192.5 BTU/h	LED indicators	✓
Number of input phases	1	Operational conditions	
Number of output phases	1	Operating temperature (T-T)	0 - 40 °C
Output power factor	1	Storage temperature (T-T)	-15 - 45 °C
Power Factor Correction (PFC) type	Active	Operating relative humidity (H-H)	0 - 95%
Emergency Power Off (EPO)	✓	Storage relative humidity (H-H)	0 - 95%
EMI/RFI noise filtering	✓	Operating altitude	0 - 3000 m
Surge protection	✓	Non-operating altitude	0 - 15000 m
Power protection features	Overload	Technical details	
Audible alarm modes	Alarm when on battery, Fault, Low battery alarm, Overload alarm	Sustainability compliance	✓
Power source type	AC	Compliance certificates	CE, Federal Communications Commission (FCC), RCM, RoHS, UL, VCCI
Detachable power cord	✓	Packaging content	
Country of origin	China	Batteries included	✓
Ports & interfaces			
AC outlet types	C13 coupler, C19 coupler		
Power plug	C20 coupler		

Ports & interfaces		Weight & dimensions	
AC outlets quantity	10 AC outlet(s)	Width	433 mm
USB port	✓	Depth	630 mm
USB 2.0 ports quantity	1	Height	86.5 mm
USB port type	USB Type-B	Weight	38.9 kg
Serial interface	✓	Package width	575 mm
Serial interface type	RS-232	Package depth	765 mm
Serial ports quantity	2	Package height	275 mm
RS-232 ports	2	Package weight	50.2 kg
Ethernet LAN (RJ-45) ports	2	Package type	Box
Emergency Power Off (EPO) connector	✓	Packaging data	
Battery		Rack mount kit	✓
Battery technology	Sealed Lead Acid (VRLA)	Cables included	Serial
		Manual	✓
		Other features	
		Battery type	RBP0130



4711027798950

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 01-NOV-2024. Prints or copies of Information are only valid on the printed Publication date