

TP-Link TL-WR802N wireless router Fast Ethernet Monobande (2,4 GHz) Bleu, Blanc

Marque : TP-Link Code produit: TL-WR802N

Nom du produit : TL-WR802N

TP-Link TL-WR802N. WAN connection type: RJ-45. Wi-Fi band: Monobande (2,4 GHz), Top Wi-Fi standard: Wi-Fi 4 (802.11n), WLAN data transfer rate (max): 300 Mbit/s. Ethernet LAN interface type: Fast Ethernet, LAN Ethernet: taux de transfert des données: 10,100 Mbit/s, Technologie de cablâge: 10/100Base-T(X). Algorithme de sécurité soutenu: WEP, WPA, WPA-Enterprise, WPA2, WPA2-Enterprise, Pare-feu de sécurité: SPI. Protocoles réseau pris en charge: IPv4, IPv6





WAN connection		Protocols	
Ethernet WAN *	✓	Supported network protocols	IPv4, IPv6
DSL WAN *	x	Design	
SIM card slot *	×	Product colour	Blue, White
3G/4G USB modem compatibility *	×	LED indicators	Activity, LAN, Power, WLAN
WAN connection type	RJ-45	On/off switch	✓
Wireless LAN features		Product type *	Portable router
Wi-Fi band *	pand * Single-band (2.4 GHz)	Certificates	
Top Wi-Fi standard * Wi-Fi 4 (802.11n) WLAN data transfer rate (max) * 300 Mbit/s	,	Compliance certificates	Federal Communications Commission (FCC)
Wi-Fi standards	802.11b, 802.11g, Wi-Fi 4 (802.11n)	Packaging content	
Network		Cables included	LAN (RJ-45), USB
Ethernet LAN *	✓	AC adapter included	✓
Ethernet LAN interface type *	Fast Ethernet	Quick installation guide	✓
Ethernet LAN data rates	10,100 Mbit/s 10/100Base-T(X) IEEE 802.11b, IEEE 802.11g, IEEE 802.11n	Sustainability	
Cabling technology		Sustainability compliance	1
Networking standards		Antenna	
Port forwarding	✓	Antenna design *	Internal
Port triggering	✓	Antennas quantity	2
Dynamic DNS (DDNS)	✓		270M: -65dBm@10% PER , 130M:
Number of guest networks (2.4 GHz)	1	Receive power	-70dBm@10% PER , 108M: -82dBm@10% PER , 54M: -73dBm@10% PER , 11M:
VPN Passthrough	/		-82dBm@8% PER , 6M: -86dBm@10% PER , 1M: -90dBm@8% PER

Ports & interfaces		Antenna	
Ethernet LAN (RJ-45) ports *	1		CE: , <20dBm(2.4GHz) , FCC: ,
USB port *	✓	Transmit power	<30dBm
Memory card slot(s)	×	Features	
DC-in jack	/	Built-in processor	1
Management features		Processor cores	1
Web-based management	✓	Power	
Quality of Service (QoS) support	✓	Power source type *	USB
Reset button	✓	Output voltage	5 V
Security		Output current	1 A
	WEP, WPA, WPA-Enterprise, WPA2,	Operational conditions	
Security algorithms	WPA2-Enterprise	Operating temperature (T-T) Storage temperature (T-T)	0 - 40 °C -40 - 70 °C
Firewall	✓	Operating relative humidity (H-H)	10 - 90%
Firewall security	SPI	Storage relative humidity (H-H)	5 - 90%
Stateful Packet Inspection (SPI)	V	System requirements	
DoS attack prevention	/	.,	Windows 2000, Windows 7
Filtering MAC address filtering	/		Enterprise, Windows 7 Enterprise
MAC address filtering IP address filtering	1		x64, Windows 7 Home Basic, Windows 7 Home Basic x64,
DMZ support	V		Windows 7 Home Premium,
	•		Windows 7 Home Premium x64, Windows 7 Professional, Windows 7
Protocols			Professional x64, Windows 7 Starter, Windows 7 Starter x64,
DHCP client	✓		Windows 7 Ultimate, Windows 7
DHCP server	✓		Ultimate x64, Windows 8, Windows 8 Enterprise, Windows 8 Enterprise
Universal Plug and Play (UPnP)		Windows operating systems supported Linux operating systems supported	x64, Windows 8 Pro, Windows 8 Pro x64, Windows 8 Rro, Windows 8 Pro x64, Windows 8.1, Windows 8.1 Enterprise x64, Windows 8.1 Pro, Windows 8.1 Pro x64, Windows 8.1 Pro, Windows 8.1 Pro x64, Windows 8.1 x64, Windows 985E, Windows NT, Windows Vista Business, Windows Vista Business x64, Windows Vista Enterprise, Windows Vista Enterprise x64, Windows Vista Home Basic, Windows Vista Home Basic x64, Windows Vista Home Premium, Windows Vista Home Premium x64, Windows Vista Ultimate, Windows Vista Ultimate x64, Windows XP Home, Windows XP Home x64, Windows XP Professional, Windows XP Professional x64
		Mac operating systems supported	macOS
		Weight & dimensions	
		Width	57 mm
		Depth	57 mm
		Height	18 mm
		Packaging data	
		Package width	110 mm
		Package depth	109 mm
		Package height	73.5 mm
		Package weight	240 g
		Logistics data	
		Harmonized System (HS) code	85176990



6935364071714

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.