



TP-Link EAP110 point d'accès réseaux locaux sans fil 300 Mbit/s Blanc Connexion Ethernet, supportant l'alimentation via ce port (PoE)

Marque : TP-Link

Code produit: EAP110

Nom du produit : EAP110

TP-Link EAP110. 2,4 GHz, Maximum data transfer rate: 300 Mbit/s. Algorithme de sécurité soutenu: 64-bit WEP, 128-bit WEP, 152-bit WEP, HTTPS, SNMP, SNMPv2, SSH, WPA, WPA-PSK, WPA2-Enterprise,....
LAN Ethernet : taux de transfert des données: 10,100 Mbit/s. Connexion Ethernet, supportant l'alimentation via ce port (PoE). Couleur du produit: Blanc



Features		Power	
2.4 GHz *	✓	Power over Ethernet (PoE) *	✓
5 GHz *	✗	AC input voltage	24 V
Maximum data transfer rate *	300 Mbit/s	Power consumption (typical)	2.8 W
Maximum data transfer rate (2.4 GHz)	300 Mbit/s	Design	
Ethernet LAN data rates	10,100 Mbit/s	Placement *	Ceiling, Wall
Frequency band	2.4 - 2.4835 GHz	Product colour *	White
Networking standards	IEEE 802.11b, IEEE 802.11g, IEEE 802.11n, IEEE 802.1x	Reset button	✓
Cabling technology	10/100Base-T(X)	LED indicators	Power
Automatic channel selection	✓	Antenna	
Wi-Fi Multimedia (WMM)/(WME)	✓	Antenna type *	Internal
VLAN support	✓	Antenna direction type	Omni-directional
Virtual LAN features	SSID-based VLAN assignment	Antennas quantity	2
Rate limiting	✓	Antenna gain level (max)	4 dBi
Wireless isolation	✓	Certificates	
Quality of Service (QoS) support	✓	Certification	FCC, RoHS
Transmitting power (CE)	21 dBm	Weight & dimensions	
Receiver sensitivity	300M: -71dBm@10% PER 150M: -75dBm@10% PER 54M: -78dBm@10% PER 11M: -93dBm@8% PER 6M: -92dBm@10% PER 1M: -96dBm@8% PER	Width	189.4 mm
		Depth	172.3 mm
Security		Height	29.5 mm
		Packaging data	
Security algorithms *	64-bit WEP, 128-bit WEP, 152-bit WEP, HTTPS, SNMP, SNMPv2, SSH, WPA, WPA-PSK, WPA2-Enterprise, WPA2-PSK	Package type	Box
MAC address filtering	✓	Packaging content	
		Quantity per pack	1 pc(s)
		PoE adapter included	✓
		Cables included	AC

Security		Packaging content	
Service Set Identifier (SSID) features	Multiple SSIDs	Mounting kit	✓
Number of SSID supported	8	Quick start guide	✓
Remote Authentication Dial-In User Service (RADIUS)	✓	Operational conditions	
Access Control List (ACL)	✓	Operating relative humidity (H-H)	10 - 90%
Management features		Operating temperature (T-T)	0 - 40 °C
Web-based management	✓	Storage temperature (T-T)	-40 - 70 °C
Syslog	✓	Storage relative humidity (H-H)	5 - 90%
Ports & interfaces		Logistics data	
Ethernet LAN (RJ-45) ports *	1	Harmonized System (HS) code	85176990

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 15-MAR-2025. Prints or copies of Information are only valid on the printed Publication date