Yealink

Yealink SIP-T43U téléphone fixe Gris 12 lignes LCD Wifi

Marque : Yealink

Nom du produit : SIP-T43U

Code produit: 1301202

Yealink SIP-T43U. Type de produit: Téléphone IP, Couleur du produit: Gris, Type de combiné: Combiné filaire. Dual-Tone Multi-Frequency (DTMF) modes: In-band, En dehors de la bande, Info SIP. Quantité de lignes: 12 lignes, Capacité du répertoire: 1000 entrées. Écran: LCD, Taille de l'écran: 9,4 cm (3.7"), Résolution de l'écran: 360 x 160 pixels. Codecs vocaux: AGC, AJB, AMR-NB, AMR-WB, G.711Mu, G.711a, G.723.1, G.726, G.729ab, OPUS, PLC, VAD, iLBC

Design

Product type *	IP Phone
Handset type	Wired handset
Product colour *	Grey
Wall mountable	✔
Mounting	Desk/Wall

Performance

Dual-Tone Multi-Frequency (DTMF) modes	In-band, Out-of band, SIP info
Hearing aid compatibility	✔

Phone features

Lines quantity *	12 lines
Answering machine	✔
Call waiting	✔
Speed dialling	✔
Call hold	✔
Call forwarding	✔
Caller ID *	✔
Phonebook capacity *	1000 entries
Number of VoIP accounts *	12
Conference call	✔
Redialing	✔
Anonymous call	✔
Anonymous call rejection	✔
Full duplex	✔
Call return	✔
Call transfer	✔
Call history	✔
SIP registrar server	✔

Management features

Plug and Play	✔

Display

Display	LCD
Display diagonal	9.4 cm (3.7")
Display resolution	360 x 160 pixels
Touchscreen *	✘
Backlight display	✔

Audio

Speakerphone *	✔

Network

Ethernet LAN *	✔
Ethernet LAN interface type	Gigabit Ethernet
Ethernet LAN data rates	10,100,1000 Mbit/s
Wi-Fi *	✔
Bluetooth *	✔
Bluetooth version	4.1
Supported network protocols	FTP/TFTP/HTTP/HTTPS, IPv6, LLDP/CDP/DHCP VLAN
Quality of Service (QoS) support	✔
DHCP client	✔
Syslog	✔
Networking standards	IEEE 802.1Q, IEEE 802.1p, IEEE 802.1x, IEEE 802.3af

Ports & interfaces

USB 2.0 ports quantity	2
Ethernet LAN (RJ-45) ports	2
RJ-9 ports quantity	2
Expansion module support	✔
DC-in jack	✔

Certificates

Sustainability compliance	✔
Compliance certificates	REACH, RoHS

Power

Power over Ethernet (PoE) *	✔
AC adapter input voltage	100 - 240 V
AC adapter output voltage	5 V
AC adapter output current	1.2 A
Power consumption (typical)	2.2 W

Operational conditions

Operating temperature (T-T)	-10 - 50 °C
Operating relative humidity (H-H)	10 - 95%

Weight & dimensions

Width	224.9 mm
Depth	206.2 mm
Height	174.9 mm
Package width	246 mm
Package depth	223 mm
Package height	120 mm

Packaging content

Mounting kit	✔

Audio

Microphone mute	✔
Voice codecs	AGC, AJB, AMR-NB, AMR-WB, G.711Mu, G.711a, G.723.1, G.726, G.729ab, OPUS, PLC, VAD, iLBC
Comfort noise generation (CNG)	✔
Packet loss concealment (PLC)	✔

Packaging content

Ethernet cable	✔
Handset	✔
Quick start guide	✔
Number of handles included *	1 pc(s)

Logistics data

Harmonized System (HS) code	85171800

6938818304284

0841885102973

841885102973

5704174978954