

EIZO FlexScan EV2495-WT LED display 61,2 cm (24.1") 1920 x 1200 pixels WUXGA Blanc

Marque : EIZO Famille de produit: FlexScan Code produit: EV2495-WT

Nom du produit : EV2495-WT

EIZO FlexScan EV2495-WT. Taille de l'écran: 61,2 cm (24.1"), Résolution de l'écran: 1920 x 1200 pixels, Type HD: WUXGA, Technologie d'affichage: LED, Temps de réponse: 5 ms, Ratio de format d'image: 16:10, Angle de vision horizontal: 178°, Angle de vision vertical: 178°. Haut-parleurs intégrés. Built-in USB hub, USB hub version: 3.2 Gen 1 (3.1 Gen 1). Montage VESA, Réglage de la hauteur. Couleur du produit: Blanc





Dienlay		Ergonomics	
Display		9	
Display diagonal *	61.2 cm (24.1")	Panel mounting interface	100 x 100 mm
Display resolution *	1920 x 1200 pixels	Cable lock slot *	✓
HD type *	WUXGA	Cable lock slot type	Kensington
Native aspect ratio *	16:10	Height adjustment *	✓
Display technology *	LED	Height adjustment	18.2 cm
Panel type *	IPS	Pivot	✓
Backlight type	LED	Pivot angle	-90 - 90°
Touchscreen *	×	Swivelling	1
Display brightness (typical)	350 cd/m ²	Swivel angle range	0 - 344°
Response time *	5 ms	Tilt adjustment	✓ 344
Screen shape *	Flat	•	-5 - 35°
	640 x 480 (VGA), 720 x 400, 800 x	Tilt angle range	
Supported graphics resolutions	600 (SVGA), 1024 x 768 (XGA), 1280 x 1024 (SXGA), 1600 x 1200 (UXGA), 1680 x 1050 (WSXGA+), 1920 x 1200 (WUXGA)	On Screen Display (OSD) On Screen Display (OSD) languages	German, English, Spanish, French, Italian, Swedish
Contrast ratio (typical) *	1000:1	Power	
Maximum refresh rate *	60 Hz	Energy efficiency class (SDR) *	С
Viewing angle, horizontal Viewing angle, vertical	178° 178°	Energy consumption (SDR) per 1000 hours *	12 kWh
Display number of colours *	16.78 million colours	Power consumption (typical) *	11.6 W
Pixel pitch	0.27 x 0.27 mm	Power consumption (standby) *	0.5 W
Viewable size, horizontal	51.8 cm	AC input voltage	100 - 240 V
Viewable size, vertical	32.4 cm	AC input frequency	50 - 60 Hz
Viewable size diagonal	61.1 cm	Energy efficiency scale	A to G
Digital horizontal frequency	31 - 76 kHz	Operational conditions	
Digital vertical frequency	59 - 61 Hz	Operating temperature (T-T)	5 - 35 °C
Colour gamut standard	sRGB	Storage temperature (T-T)	-20 - 60 °C
		Operating relative humidity (H-H)	20 - 80%
		Storage relative humidity (H-H)	10 - 90%

Performance		Weight & dimensions	
Flicker-free technology	✓	Width (with stand)	531 mm
Low Blue Light technology	1	Depth (with stand)	230 mm
Multimedia		Height (with stand)	356 mm
Number of speakers	2	Weight (with stand) Width (without stand)	7.6 kg 531 mm
RMS rated power	2 W	Depth (without stand)	54 mm
Built-in speaker(s) *	✓	Height (without stand)	344 mm
Design		Weight (without stand)	4.9 kg
Market positioning *	Business	Packaging content	
Product colour *	White	Stand included	✓
Ports & interfaces		Cables included	AC, USB Type-C to USB Type-C
Built-in USB hub *	✓	Quick start guide	✓
USB hub version	3.2 Gen 1 (3.1 Gen 1)	Sustainability	
Number of upstream ports	2	Sustainability compliance	✓
USB Type-A downstream ports quantity	3	Sustainability certificates	ENERGY STAR, EPEAT Climate +, EPEAT Gold, TCO
USB Type-C downstream ports quantity	1	Other features	
USB Type-C DisplayPort Alternate Mode	✓	Compliance certificates	CB, CCC, CE, China RoHS, Federal Communications Commission (FCC), GS mark, ICES, PSE, RCM, RoHS, cTUVus, UKCA, VCCI, WEEE
DVI port	×	Compliance certificates	
HDMI *	✓	Ethernet LAN data rates	10,100,1000 Mbit/s
HDMI ports quantity	1	Ethernet LAN (RJ-45) ports	1
DisplayPorts quantity	1		CE, UKCA, CB, TÜV/GS,
Audio input	✓		TÜV/Ergonomics (including ISO 9241-307), TCO Certified
Headphone out *	•	- 15	Generation 9, EPEAT 2018 (US),
Headphone outputs	1	Certification	TÜV/Blue Low Light Content, TÜV/Flicker Free, RCM, cTÜVus,
Headphone connectivity HDCP	3.5 mm		FCC-B, CAN ICES-3 (B), TÜV/S, PSE,
	•		VCCI-B, EPA ENERGY STAR, RoHS, WEEE, China RoHS, CCC
Network		Logistics data	, ,
Ethernet LAN	✓	Harmonized System (HS) code	85285210
Ergonomics		Harmonized System (HS) code	03203210
VESA mounting *	✓		





4995047056546

0690592049572



690592049572

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.