



Canon i-SENSYS MF455DW Laser A4 1200 x 1200 DPI 38 ppm Wifi

Marque : Canon

Famille de produit: i-SENSYS

Code produit: 5161C016

Nom du produit : MF455DW

Canon i-SENSYS MF455DW. Technologie d'impression: Laser, Impression: Impression mono, Résolution maximale: 1200 x 1200 DPI. Copier: Copie simple, Résolution max. des copies: 600 x 600 DPI. Numérisation: Numérisation couleur, Résolution de numérisation optique: 600 x 600 DPI. Télécopier: Télécopie simple. Fonctions recto verso: Copie, Impression, Numérisation. Taille de papier de série A ISO maximum: A4. Wifi. Impression directe. Couleur du produit: Noir, Blanc

Printing		Paper handling	
Duplex printing mode	Auto	ISO A-series sizes (A0...A9) *	A4, A5, A6
Print technology *	Laser	ISO B-series sizes (B0...B9)	B5
Printing *	Mono printing	Non-ISO print media sizes	Executive, Index card, Legal, Letter, Statement
Duplex printing *	✓	Envelopes sizes	C5, Com-10, DL, Monarch
Maximum resolution *	1200 x 1200 DPI	Paper tray media weight	60 - 120 g/m ²
Print speed (black, normal quality, A4/US Letter) *	38 ppm	Multi-Purpose Tray media weight	60 - 163 g/m ²
Warm-up time	14 s	Ports & interfaces	
Time to first page (black, normal)	5.5 s	Direct printing *	✓
Secure printing	✓	USB port	✓
Copying		Network	
Duplex copying *	✓	Wi-Fi *	✓
Copying *	Mono copying	Ethernet LAN *	✓
Maximum copy resolution *	600 x 600 DPI	Cabling technology	10/100/1000Base-T(X)
Maximum number of copies	999 copies	Ethernet LAN data rates	10,100,1000 Mbit/s
Copier resize	25 - 400%	Wi-Fi standards	802.11b, 802.11g, Wi-Fi 4 (802.11n)
ID-card copy function	✓	Security algorithms	64-bit WEP, 128-bit WEP, WPA-AES, WPA-PSK, WPA-TKIP, WPA2-AES, WPA2-PSK, WPA2-TKIP
Scanning		Mobile printing technologies	Apple AirPrint, Canon PRINT Business, Mopria Print Service
Duplex scanning *	✓	Performance	
Scanning *	Colour scanning	Internal memory *	1024 MB
Optical scanning resolution *	600 x 600 DPI	Built-in processor	✓
Scanner type *	ADF scanner	Processor frequency	800 MHz
Scan to	Cloud, E-mail	Sound pressure level (printing)	53 dB
Image formats supported	JPEG, TIFF	Design	
Document formats supported	PDF	Product colour *	Black, White
Input colour depth	24 bit	Market positioning *	Business
Output colour depth	24 bit	Built-in display *	✓
Greyscale levels	256	Display	LCD
Scan drivers	ICA, TWAIN, WIA	Control type	Touch
Fax		Colour display	✓
Faxing *	Mono faxing	Power	
Fax resolution (black)	200 x 100 DPI	Power consumption (max)	1370 W
Modem speed	33.6 Kbit/s	Power consumption (printing)	500 W
Fax memory	512 pages	Power consumption (standby)	9.4 W
Speed dialling	✓	Power consumption (sleep)	0.9 W
Features		Energy Star Typical Electricity Consumption (TEC)	0.33 kWh/week
Recommended duty cycle	750 - 4000 pages per month	AC input voltage	220 - 240 V
Maximum duty cycle *	80000 pages per month	AC input frequency	50 - 60 Hz
Duplex functions *	Copy, Print, Scan		
Printing colours *	Black		
Page description languages	PCL 5e, PCL 6, PostScript 3, UFR II		
Printer fonts	PCL, PostScript		

Input & output capacity		System requirements	
Total number of input trays *	1	Windows operating systems supported	Windows 10, Windows 11, Windows 8.1
Total input capacity *	250 sheets		Mac OS X 10.11 El Capitan, Mac OS X 10.12 Sierra, Mac OS X 10.13 High Sierra, Mac OS X 10.14 Mojave, Mac OS X 10.15 Catalina, Mac OS X 10.15.3 Catalina, Mac OS X 10.2 Jaguar, Mac OS X 10.3 Panther, Mac OS X 10.4 Tiger, Mac OS X 10.5 Leopard, Mac OS X 10.6 Snow Leopard, Mac OS X 10.7 Lion, Mac OS X 10.8 Mountain Lion, Mac OS X 10.9 Mavericks, Mac OS X 11.0 Big Sur
Total output capacity *	150 sheets	Mac operating systems supported	
Multi-Purpose tray	✓		
Multi-Purpose tray input capacity	100 sheets		
Auto document feeder (ADF)	✓		
Auto document feeder (ADF) input capacity	50 sheets		
Maximum input capacity	900 sheets		
Paper handling			
Maximum ISO A-series paper size *	A4	Linux operating systems supported	✓
Paper tray media types *	Envelopes, Heavy paper, Labels, Plain paper, Postcard, Recycled paper, Thin paper	Server operating systems supported	Windows Server 2008, Windows Server 2008 R2, Windows Server 2012, Windows Server 2012 R2, Windows Server 2016, Windows Server 2019
		Operational conditions	
		Operating relative humidity (H-H)	20 - 80%
		Storage temperature (T-T)	10 - 30 °C
		Weight & dimensions	
		Width	453 mm
		Depth	464 mm
		Height	392 mm
		Weight	17.2 kg



8714574670416

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 10-DEC-2024. Prints or copies of Information are only valid on the printed Publication date