ZYXEL

Zyxel WAX650S 3550 Mbit/s Blanc Connexion Ethernet, supportant l'alimentation via ce port (PoE)

Marque : Zyxel

Code produit: WAX650S-EU0101F

Nom du produit : WAX650S


Zyxel WAX650S. 2,4 GHz, 5 GHz, Maximum data transfer rate: 3550 Mbit/s. Algorithme de sécurité soutenu: SNMP, WEP, WPA-Enterprise, WPA-PSK, WPA2, WPA3. LAN Ethernet : taux de transfert des données: 1000,2500,5000 Mbit/s. Connexion Ethernet, supportant l'alimentation via ce port (PoE). Couleur du produit: Blanc





Features		Design	
2.4 GHz *	✓	Product colour *	White
5 GHz *	1	Antenna	
Maximum data transfer rate *	3550 Mbit/s	Antenna type *	Internal
Maximum data transfer rate (2.4 GHz)	1150 Mbit/s	Antenna gain level (max)	5.8 dBi
Maximum data transfer rate (5 GHz)	2400 Mbit/s	Certificates	
Ethernet LAN data rates	1000,2500,5000 Mbit/s		FCC 15C, FCC 15E, ETSI EN 300
Networking standards	IEEE 802.11a, IEEE 802.11ac, IEEE 802.11ax, IEEE 802.11b, IEEE 802.11g, IEEE 802.11n, IEEE 802.3bt	Certification	328, EN 301 893, LP0002 FCC 15B, EN 301 489-1, EN 301 489-17, EN55022, EN55024, EN61000-3-2/-3, EN60601-1-2, BSMI CNS13438 EN 60950-1, IEC 60950-1, BSMI CNS14336-1
MIMO type	Multi User MIMO		00950-1, BSMI CN514550-1
Wi-Fi Multimedia (WMM)/(WME)	 ✓ 	Weight & dimensions	
Fast roaming	1	Width	230 mm 235 mm
VLAN support	1	Depth Height	235 mm 53.5 mm
Wireless isolation	1	Weight	1.16 kg
Band steering	1	Packaging data	- 5
Transmitting power	26 dBmW	Package width	282 mm
Receiver sensitivity	-105 dBm	Package depth	266 mm
Security		Package height	79 mm
Security algorithms *	SNMP, WEP, WPA-Enterprise, WPA-	Package weight	1.49 kg
	PSK, WPA2, WPA3	Packaging content	
MAC address filtering	✓	Quantity per pack	1 pc(s)
Auto Wireless Distribution System (WDS)	 Image: A start of the start of	Mounting kit	√
Management features		Operational conditions	
Web-based management	1	Operating relative humidity (H-H)	10 - 95%

Management features		Operational conditions
Firmware upgradeable	1	Operating temperature (T-T) 0 - 50 °C
Ports & interfaces		Storage temperature (T-T) -30 - 70 °C Storage relative humidity (H-H) 10 - 90%
Ethernet LAN (RJ-45) ports * DC-in jack	2	Logistics data
Power		Harmonized System (HS) code 85176990
Power over Ethernet (PoE) *	1	
AC input voltage	12 V	



4718937609178

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.