

CyberPower OLS3000EA-DE alimentation d'énergie non interrompible Double-conversion (en ligne) 3 kVA 2700 W 7 sortie(s) CA

Marque : CyberPower

Code produit: OLS3000EA-DE

Nom du produit : OLS3000EA-DE

CyberPower OLS3000EA-DE. Topologie UPS: Double-conversion (en ligne), Puissance de sortie, capacité (VA): 3 kVA, Puissance de sortie: 2700 W. Types de sortie AC: Coupleur C13, Nombre de prises en sortie: 7 sortie(s) CA. Technologie batterie: Sealed Lead Acid (VRLA), Temps de secours type au chargement complet: 4,2 min, Temps de secours type à demi de charge: 13,1 min. Élément de format: Tower, Couleur du produit: Noir, Matériau du boîtier/corps: Métal. Certification: RoHS, CE



Features		Battery	
UPS topology *	Double-conversion (Online)	Typical backup time at half load	13.1 min
Output power capacity *	3 kVA	Battery recharge time	4 h
Output power *	2700 W	Charging current	1.5 A
Waveform *	Pure sine	Design	
Input operation voltage (min) *	190 V	Form factor *	Tower
Input operation voltage (max) *	230 V	Housing material	Metal
Input frequency *	50/60 Hz	Cable length	1.5 m
Output operation voltage (min)	208 V	Built-in fan	✓
Output operation voltage (max)	240 V	Product colour *	Black
Output frequency	50/60 Hz	Display type	LCD
Maximum current	13.04 A	LED indicators	Fault, Operation, Power, Status
Surge energy rating	370 J	Operational conditions	
Response time	0 ms	Operating temperature (T-T)	0 - 40 °C
Efficiency (ECO mode)	95%	Storage temperature (T-T)	-20 - 50 °C
Power factor	0.9	Operating relative humidity (H-H)	20 - 90%
Input power factor	0.98	Storage relative humidity (H-H)	10 - 90%
Crest factor	3:1	Operating altitude	0 - 1500 m
Output voltage Total Harmonic Distortion (THD)	5%	Non-operating altitude	0 - 1500 m
EMI/RFI noise filtering	✓	Certificates	
Surge protection	✓	Certification	RoHS, CE
Power protection features	Overload	Packaging content	
Audible alarm(s)	✓	Cables included	Power load cable, USB cable
Audible alarm modes	Battery replacement, Fault, Low battery alarm, Overload alarm	Weight & dimensions	
Ports & interfaces		Width	196 mm
AC outlet types	C13 coupler	Depth	416 mm
AC outlets quantity	7 AC outlet(s)	Height	337 mm

Ports & interfaces		Weight & dimensions	
USB port	✓	Weight	21.3 kg
Battery		Packaging data	
Battery technology	Sealed Lead Acid (VRLA)	Package width	295 mm
Number of batteries supported	3	Package depth	519 mm
Typical backup time at full load	4.2 min	Package height	458 mm
		Package weight	30.4 kg
		Logistics data	
		Harmonized System (HS) code	8504408590
		Country of origin	China



4711027790251



5715063461341

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.