

## CyberPower PR3000ELCDSXL alimentation d'énergie non interruptible Interactivité de ligne 3 kVA 2700 W 9 sortie(s) CA

**Marque :** CyberPower

**Code produit:** PR3000ELCDSXL

**Nom du produit :** PR3000ELCDSXL

CyberPower PR3000ELCDSXL. Topologie UPS: Interactivité de ligne, Puissance de sortie, capacité (VA): 3 kVA, Puissance de sortie: 2700 W. Types de sortie AC: Coupleur C13, Coupleur C19, Prise mâle: Coupleur C20, Nombre de prises en sortie: 9 sortie(s) CA. Technologie batterie: Sealed Lead Acid (VRLA), Temps de secours type au chargement complet: 2 min, Temps de secours type à demi de charge: 7 min. Élément de format: Tower, Couleur du produit: Noir, Longueur de câble: 3,05 m. Compliance certificates: CE, RoHS



Features		Battery	
UPS topology *	Line-Interactive	Number of batteries supported	1
Output power capacity *	3 kVA	Typical backup time at full load	2 min
Output power *	2700 W	Typical backup time at half load	7 min
Waveform *	Pure sine	Battery recharge time	8 h
Input operation voltage (min) *	151 V	Hot-swap battery	✓
Input operation voltage (max) *	301 V	Design	
Input frequency *	50/60 Hz	Form factor *	Tower
Output operation voltage (min)	230 V	Cable length	3.05 m
Output operation voltage (max)	230 V	Product colour *	Black
Output frequency	50/60 Hz	Control type	Buttons
Automatic Voltage Regulation (AVR)	✓	Display type	LCD
Maximum current	16 A	LED indicators	Power
Surge energy rating	405 J	Operational conditions	
Response time	4 ms	Operating temperature (T-T)	0 - 40 °C
Number of input phases	1	Storage temperature (T-T)	-15 - 45 °C
Number of output phases	1	Operating relative humidity (H-H)	0 - 95%
Output power factor	0.9	Storage relative humidity (H-H)	0 - 95%
Power Factor Correction (PFC) type	Active	Operating altitude	0 - 3000 m
Emergency Power Off (EPO)	✓	Non-operating altitude	0 - 15000 m
EMI/RFI noise filtering	✓	Certificates	
Surge protection	✓	Compliance certificates	CE, RoHS
Power protection features	Overload	Packaging content	
Audible alarm(s)	✓	Cables included	Power load cable, Serial, USB cable
Audible alarm modes	Alarm when on battery, Fault, Low battery alarm, Overload alarm	Manual	✓
Ports & interfaces		Sustainability	
AC outlet types	C13 coupler, C19 coupler	Sustainability compliance	✓
Power plug	C20 coupler		

Ports & interfaces		Weight & dimensions	
AC outlets quantity	9 AC outlet(s)	Width	170 mm
USB port	✓	Depth	432 mm
USB 2.0 ports quantity	1	Height	221 mm
USB port type	USB Type-B	Weight	26.8 kg
Serial interface	✓	Packaging data	
Serial interface type	RS-232	Package width	316 mm
Serial ports quantity	1	Package depth	579 mm
RS-232 ports	1	Package height	360 mm
Emergency Power Off (EPO) connector	✓	Package weight	28 kg
Battery		Logistics data	
Battery technology	Sealed Lead Acid (VRLA)	Harmonized System (HS) code	8504408590
		Country of origin	China
		Other features	
		Battery type	RBP0116



4712856276091

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 29-MAR-2025. Prints or copies of Information are only valid on the printed Publication date