
Samsung 46" Video Wall VMB-U 3.5mm BtB

Marque : Samsung Famille de produit: VMB-U Code produit: LH46VMBUBGBXEN

Nom du produit : 46" Video Wall VMB-U 3.5mm BtB








Display		Ports & interfaces	
Display technology * Display diagonal Display resolution HD type Panel type Aspect ratio Pixel pitch * Display brightness * Pixel frequency Contrast ratio (typical) Contrast ratio (dynamic) Response time	LCD 116.8 cm (46") 1920 x 1080 pixels Full HD IPS 16:9 0.53 x 0.53 mm 500 cd/m ² 82 MHz 1200:1 45000:1 0.008 s	USB ports quantity HDCP HDCP version IR input ports quantity Audio input Audio output Power Power consumption (typical) * Energy efficiency scale Energy efficiency class (SDR) Energy consumption (SDR) per 1000	1 2.2 1 4 160 W A to G G 128 kWh
Viewing angle, horizontal Viewing angle, vertical Horizontal scan range Vertical scan range Operating hours (hours/days)	178° 178° 62.7 - 72.3 kHz 57 - 63 Hz 24/7	hours AC input voltage AC input frequency Operational conditions Operating temperature (T-T)	100 - 240 V 50 - 60 Hz
Design		Operating relative humidity (H-H)	10 - 90%
Placement supported * Orientation * Bezel width (side)	Indoor Landscape/Portrait 1.25 mm	Logistics data Harmonized System (HS) code Sustainability	85285210
Bezel width (top) Bezel width (bottom) VESA mounting Panel mounting interface Product colour Panel colour	2.25 mm 2.25 mm	Certification	FCC (USA) Part 15, Subpart B Class ACE (Europe): EN55032: 2012 or 2015 EN55024:2010 or EN 55035:2017VCCI (Japan): VCCI CISPR32:2016 Class BKCC/EK (Korea): Tuner: KN13 / KN20Tunerless: KN22 / KN24BSMI (Taiwan): CNS13438 (ITE EMI) Class A / CNS14336-1 (ITE Safety) / CNS15663 (RoHS)C-Tick (Australia): AS/NZS CISPR32:2015CCC(China): GB/T9254-2008, GB17625.1-2012GOST(Russia/CIS): ROCT CISPR 24-2013/ROCT CISPR 22:2005
Ports & interfaces HDMI ports quantity HDMI version DVI port DisplayPorts quantity	2 2.0 •• 1		
DisplayPort version Ethernet LAN	1.2 ✓	Weight & dimensions	
		Width	1022 mm

orts & interfaces		Weight & dimensions	
Ethernet LAN (RJ-45) ports	1	Depth	69.9 mm
RS-232 input ports	1	Height	577 mm
RS-232 output ports	1	Weight	15.7 kg
RS-232C	✓	Packaging data	
USB port	✓	Package width	1193 mm
		Package depth	257 mm
		Package height	719 mm
		Package weight	22.2 kg



8806094366082

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.