



## CyberPower OL2200ERTXL2U alimentation d'énergie non interruptible Double-conversion (en ligne) 2,2 kVA 2000 W 9 sortie(s) CA

Marque : CyberPower

Code produit: OL2200ERTXL2U

Nom du produit : OL2200ERTXL2U

CyberPower OL2200ERTXL2U. Topologie UPS: Double-conversion (en ligne), Puissance de sortie, capacité (VA): 2,2 kVA, Puissance de sortie: 2000 W. Types de sortie AC: Coupleur C13, Coupleur C19, Prise mâle: Coupleur C20, Nombre de prises en sortie: 9 sortie(s) CA. Technologie batterie: Sealed Lead Acid (VRLA), Tension des piles: 72 V, Temps de secours type au chargement complet: 6,5 min. Élément de format: Rack/Tour, Couleur du produit: Noir, Matériau du boîtier/corps: Métal. Largeur: 433 mm, Profondeur: 600 mm, Hauteur: 88 mm



Features		Battery	
UPS topology *	Double-conversion (Online)	Typical backup time at half load	20 min
Output power capacity *	2.2 kVA	Battery recharge time	5 h
Output power *	2000 W	Charging current	1 A
Waveform *	Pure sine	Hot-swap battery	✓
Input operation voltage (min) *	190 V	Cold start	✓
Input operation voltage (max) *	300 V	Design	
Input frequency *	40/70 Hz	Form factor *	Rackmount/Tower
Output operation voltage (min)	200 V	Housing material	Metal
Output operation voltage (max)	240 V	Rack capacity	2U
Output frequency	50/60 Hz	Cable length	3 m
Maximum current	11 A	Cooling type	Active
Surge energy rating	1335 J	Built-in fan	✓
Response time	0 ms	Product colour *	Black
Heat dissipation	1139 BTU/h	Control type	Buttons
Output power factor	0.9	Display type	LCD
Emergency Power Off (EPO)	✓	LED indicators	✓
Total Harmonic Distortion (THD) (linear load)	3%	Operational conditions	
Total Harmonic Distortion (THD) (non-linear load)	5%	Operating temperature (T-T)	0 - 40 °C
Surge protection	✓	Storage temperature (T-T)	-20 - 45 °C
Surge protection features	Fax, Modem, Network, Telephone	Operating relative humidity (H-H)	0 - 90%
Power protection features	Overload	Storage relative humidity (H-H)	0 - 95%
Country of origin	China	Operating altitude	0 - 3000 m
Ports & interfaces		Non-operating altitude	0 - 15000 m
AC outlet types	C13 coupler, C19 coupler	Technical details	
Power plug	C20 coupler	Sustainability compliance	✓
AC outlets quantity	9 AC outlet(s)	Compliance certificates	CE, RoHS
USB 2.0 ports quantity	1		

Ports & interfaces		Weight & dimensions	
Serial interface	✓	Width	433 mm
Serial interface type	RS-232	Depth	600 mm
Serial ports quantity	1	Height	88 mm
RS-232 ports	1	Weight	31 kg
Ethernet LAN (RJ-45) ports	2	Package width	565 mm
Emergency Power Off (EPO) connector	✓	Package depth	880 mm
Battery		Package height	240 mm
Battery technology	Sealed Lead Acid (VRLA)	Package weight	39.5 kg
Battery voltage	72 V	Packaging data	
Typical backup time at full load	6.5 min	Rack mount kit	✓
		Cables included	Serial, USB cable
		Manual	✓
		Logistics data	
		Harmonized System (HS) code	8504408590
		Other features	
		Battery type	RBP0076



4711027799599

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 16-DEC-2024. Prints or copies of Information are only valid on the printed Publication date