



D-Link DXS-1210-16TC/E commutateur réseau Géré L2 10G Ethernet (100/1000/10000) Gris

Marque : D-Link

Code produit: DXS-1210-16TC/E

Nom du produit : DXS-1210-16TC/E



D-Link DXS-1210-16TC/E. Type de commutateur: Géré, Banc de commutateurs: L2. Type de port Ethernet RJ-45 de commutation de base: 10G Ethernet (100/1000/10000), Quantité de ports Ethernet RJ-45 de commutation de base: 12. Répertoire MAC: 16000 entrées, Capacité de commutation: 320 Gbit/s. Standards réseau: IEEE 802.1D, IEEE 802.1Q, IEEE 802.1s, IEEE 802.1w, IEEE 802.1x, IEEE 802.3ab, IEEE 802.3ad, IEEE.... Power connector: Prise d'entrée AC. Grille de montage

Management features		Data transmission	
Switch type *	Managed	Jumbo frames	16000
Switch layer	L2	Security	
Quality of Service (QoS) support	✓	DHCP features	DHCP client, DHCP server
Web-based management	✓	Access Control List (ACL)	✓
ARP inspection	✓	Access Control List (ACL) rules	256
System event log	✓	IGMP snooping	✓
MIB support	RFC 783, RFC 951, RFC 1157, RFC 1213, RFC 1215, RFC 1350, RFC 1493, RFC 1769, RFC 1542, RFC 1901, RFC 1907, RFC 1908, RFC 2131, RFC 2138, RFC 2139, RFC 2233, RFC-2246, RFC 2475, RFC 2570, RFC 2575, RFC 2598, RFC 2618, RFC 2819, RFC 2865, RFC 3164, RFC 3195, RFC 3411-17	Security algorithms	802.1x RADIUS, SNMP, SSL/TLS
		IP-MAC-Port binding	✓
		Multicast features	
		Multicast support	✓
Ports & interfaces		Protocols	
Basic switching RJ-45 Ethernet ports quantity *	12	Supported network protocols	IPv4, IPv6
Basic switching RJ-45 Ethernet ports type *	10G Ethernet (100/1000/10000)	Design	
Combo SFP ports quantity	2	Rack mounting *	✓
SFP+ module slots quantity	2	Product colour	Grey
Power connector	AC-in jack	LED indicators	✓
Network		Performance	
Networking standards *	IEEE 802.1D, IEEE 802.1Q, IEEE 802.1s, IEEE 802.1w, IEEE 802.1x, IEEE 802.3ab, IEEE 802.3ad, IEEE 802.3ae, IEEE 802.3an, IEEE 802.3az, IEEE 802.3p, IEEE 802.3u, IEEE 802.3z	Power	
	10G support *	Power source *	AC
	Copper ethernet cabling technology	AC input voltage	100 - 240 V
	Cable types supported	AC input frequency	50 - 60 Hz
Port mirroring	✓	Power consumption (max)	90.81 W
Flow control support	✓	Power over Ethernet (PoE)	
Broadcast storm control	✓	Power over Ethernet (PoE) *	✗
Auto MDI/MDI-X	✓	Operational conditions	
Spanning tree protocol	✓	Operating temperature (T-T)	0 - 50 °C
Head-of-line (HOL) blocking	✓	Storage temperature (T-T)	-40 - 70 °C
VLAN support	✓	Operating relative humidity (H-H)	0 - 95%
Virtual LAN features	MAC address-based VLAN, Port-based VLAN, Voice VLAN	Storage relative humidity (H-H)	0 - 95%
Optical fiber		Weight & dimensions	
Fiber ethernet cabling technology	1000BASE-X	Width	440 mm
		Depth	250 mm
		Height	44 mm
		Weight	3.15 kg
		Certificates	
		Certification	CE, FCC, C-Ticket, VCCI, BSMI, CCC

**Data transmission**

Switching capacity *	320 Gbit/s
Forwarding rate	238.08 Mpps
MAC address table *	16000 entries
Store-and-forward	✓
Jumbo frames support	✓



0790069467660



790069467660

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.