

KYOCERA ECOSYS M4132idn Laser A3 1200 x 1200 DPI 32 ppm

Marque : KYOCERA

Famille de produit: ECOSYS

Code produit: 1102P13NL0

Nom du produit : M4132idn

KYOCERA ECOSYS M4132idn. Technologie d'impression: Laser, Impression: Impression mono, Résolution maximale: 1200 x 1200 DPI. Copier: Copie simple, Résolution max. des copies: 600 x 600 DPI. Numérisation: Numérisation couleur, Résolution de numérisation optique: 600 x 600 DPI. Fonctions recto verso: Copie, Télécopie, Impression, Numérisation. Taille de papier de série A ISO maximum: A3. Impression directe. Couleur du produit: Noir, Blanc

Printing		Paper handling	
Duplex printing mode	Auto/Manual	Multi-Purpose Tray media weight	45 - 256 g/m ²
Print technology *	Laser	Auto Document Feeder (ADF) media weight	45 - 160 g/m ²
Printing *	Mono printing	Duplex media weight	60 - 163 g/m ²
Duplex printing *	✓	Media thickness (min)	0.11 mm
Maximum resolution *	1200 x 1200 DPI	Ports & interfaces	
Print speed (black, normal quality, A4/US Letter) *	32 ppm	Standard interfaces	Ethernet, USB 2.0
Print speed (black, normal quality, A3)	17 ppm	Direct printing *	✓
Duplex print speed (black, normal quality, A4/US Letter)	29 ppm	USB port	✓
Warm-up time	20 s	USB 2.0 ports quantity	3
Time to first page (black, normal)	5.2 s	Optional connectivity	Ethernet, Wireless LAN
N-in-1 print function	✓	Network	
Skip blank page function	✓	Wi-Fi *	✗
N-up printing	2, 4	Ethernet LAN *	✓
Barcode printing	✓	Cabling technology	10/100/1000Base-T(X)
Watermark printing	✓	Ethernet LAN data rates	10,100,1000 Mbit/s
Secure printing	✓	Bluetooth	✗
Poster printing function	✓	Near Field Communication (NFC)	✗
Secure PDF printing function	✓	Mobile printing technologies	Apple AirPrint, Google Cloud Print, Kyocera Mobile Print, Mopria Print Service
Copying		Performance	
Duplex copying *	✓	Maximum internal memory	3000 MB
Duplex copying mode	Auto	Internal memory *	1000 MB
Copying *	Mono copying	Compatible memory cards	SD
Maximum copy resolution *	600 x 600 DPI	Built-in processor	✓
Copy speed (black, normal quality, A4)	32 cpm	Processor family	ARM Cortex-A9
Copy speed (black, normal quality, A3)	17 cpm	Processor frequency	1200 MHz
Time to first copy (black, normal)	5.2 s	Processor cores	2
Maximum number of copies	999 copies	Sound pressure level (printing)	50 dB
Copier resize	25 - 400%	Sound pressure level (copying)	50 dB
N-in-1 copy function	✓	Sound power level (standby)	34 dB
N-in-1 copy function (N=)	2, 4	Design	
Copy programming function	✓	Product colour *	Black, White
ID-card copy function	✓	Market positioning *	Business
Scanning		Built-in display *	✓
Duplex scanning *	✓	Display	TFT
Duplex scanning mode	Auto	Display diagonal	17.8 cm (7")
Scanning *	Colour scanning	Touchscreen	✓
Optical scanning resolution *	600 x 600 DPI	Control type	Touch
Maximum scan area	297 x 420 mm	Colour display	✓
Scanner type *	Flatbed & ADF scanner		

Scanning		Power	
Scan technology	CIS/CCD	Power consumption (average operating)	490 W
Scan to	E-mail, FTP, SMB, TWAIN, USB, WIA	Power consumption (PowerSave)	45 W
Scan speed (colour)	50 ppm	Power consumption (printing)	490 W
Scan speed (black)	50 ppm	Power consumption (copying)	490 W
Image formats supported	JPG, MMR, TIF	Power consumption (ready)	70 W
Document formats supported	PDF, XPS	Power consumption (sleep)	0.5 W
Greyscale levels	256	Power consumption (off)	0.1 W
Scan drivers	TWAIN, WIA	Energy Star Typical Electricity Consumption (TEC)	1.39 kWh/week
Fax		AC input voltage	100 - 240 V
Duplex faxing	✓	AC input frequency	50 - 60 Hz
Faxing *	✗	System requirements	
Fax resolution (black)	400 x 400 DPI	Windows operating systems supported	✓
Fax transmission speed	3 sec/page	Mac operating systems supported	Mac OS X 10.10 Yosemite, Mac OS X 10.11 El Capitan, Mac OS X 10.12 Sierra, Mac OS X 10.13 High Sierra, Mac OS X 10.14 Mojave, Mac OS X 10.15 Catalina, Mac OS X 10.5 Leopard, Mac OS X 10.6 Snow Leopard, Mac OS X 10.7 Lion, Mac OS X 10.8 Mountain Lion, Mac OS X 10.9 Mavericks
Modem speed	33.6 Kbit/s		
Fax memory	700 pages		
Fax coding methods	JBIG, MH, MMR, MR	Linux operating systems supported	✓
Features		Operational conditions	
Recommended duty cycle	5000 - 10000 pages per month	Operating relative humidity (H-H)	10 - 80%
Maximum duty cycle *	100000 pages per month	Storage temperature (T-T)	-20 - 40 °C
Duplex functions *	Copy, Fax, Print, Scan	Operating temperature (T-T)	10 - 32.5 °C
Digital sender	✓	Storage relative humidity (H-H)	10 - 90%
Number of print cartridges *	1	Operating altitude	0 - 3500 m
Printing colours *	Black	Non-operating altitude	0.6 - 15000 m
Page description languages	Microsoft XPS, OpenXPS, PCL 5e, PCL 6, PCL XL, PostScript 3	Certificates	
Number of printer fonts	101	Waste Electrical and Electronic Equipment (WEEE) compliance	✓
Optional functions	Fax	Certification	TÜV/GS, CE
Replacement cartridges	TK-6115 (15.000 pagina's)	Sustainability	
Input & output capacity		Sustainability certificates	Blue Angel, EPEAT Silver, ENERGY STAR
Total number of input trays *	1	Weight & dimensions	
Total input capacity *	500 sheets	Width	590 mm
Total output capacity *	300 sheets	Depth	590 mm
Multi-Purpose tray	✓	Height	688 mm
Multi-Purpose tray input capacity	100 sheets	Weight	52 kg
Paper input type	Cassette, Paper tray	Packaging data	
Auto document feeder (ADF)	✓	Package width	760 mm
Auto document feeder (ADF) input capacity	50 sheets	Package depth	760 mm
Maximum number of input trays	3	Package height	911 mm
Maximum input capacity	1600 sheets	Package weight	74 kg
Maximum output capacity	300 sheets	Packaging content	
Paper handling		Cartridge(s) included	✓
Maximum ISO A-series paper size *	A3	Included cartridge capacity (black)	3000 pages
Maximum print size	297 x 432 mm	Imaging unit included	✓
Paper tray media types *	Plain paper	Cables included	AC
Multi-purpose tray media types	Legal, Letter, Plain paper	Drivers included	✓
ISO A-series sizes (A0...A9) *	A3, A4, A5	Power cord included	✓
ISO B-series sizes (B0...B9)	B5	Quick installation guide	✓
Non-ISO print media sizes	Folio, Ledger (media size), Letter	Logistics data	
Custom media width	98 - 297 mm	Harmonized System (HS) code	84433100
Custom media length	148 - 432 mm		
Paper tray media weight	60 - 163 g/m²		

Technical details

Compliance certificates

REACH, RoHS



0632983041499



632983041499

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.