# EIZO ColorEdge CG2700X écran plat de PC 68,6 cm (27") 3840 x 2160 pixels 4K Ultra HD LCD Noir

Marque : EIZO   **Famille de produit:** ColorEdge   **Code produit:** CG2700X

Nom du produit : CG2700X

EIZO ColorEdge CG2700X. Taille de l'écran: 68,6 cm (27"), Résolution de l'écran: 3840 x 2160 pixels, Type HD: 4K Ultra HD, Technologie d'affichage: LCD, Temps de réponse: 13 ms, Ratio de format d'image: 16:9, Angle de vision horizontal: 178°, Angle de vision vertical: 178°. Built-in USB hub, USB hub version: 2.0 / 3.2 Gen 1 (3.1 Gen 1). Montage VESA, Réglage de la hauteur. Couleur du produit: Noir

Display

Display diagonal *	68.6 cm (27")
Display resolution *	3840 x 2160 pixels
HD type *	4K Ultra HD
Native aspect ratio *	16:9
Display technology *	LCD
Panel type *	IPS
Touchscreen *	✘
Display brightness (typical)	500 cd/m²
Response time *	13 ms
Screen shape *	Flat
Contrast ratio (typical) *	1450:1
Maximum refresh rate *	60 Hz
Viewing angle, horizontal	178°
Viewing angle, vertical	178°
Display number of colours *	1.07 billion colours
Pixel pitch	0.155 x 0.155 mm
Pixel density	164 ppi
Horizontal scan range	25 - 137 kHz
Vertical scan range	23 - 61 Hz
Viewable size, horizontal	59.6 cm
Viewable size, vertical	33.5 cm
Display diagonal (metric)	68.4 cm
High Dynamic Range (HDR) supported	✔
High Dynamic Range (HDR) technology	Hybrid Log-Gamma (HLG)
Colour gamut standard	Adobe RGB
sRGB coverage (typical)	100%
Adobe RGB coverage	99%

Ports & interfaces

DisplayPorts quantity	1
Built-in KVM switch	✔
HDCP	✔

Network

Ethernet LAN	✔

Ergonomics

VESA mounting *	✔
Panel mounting interface	100 x 100 mm
Height adjustment *	✔
Adjustable height (max)	15.5 cm
Pivot	✔
Pivot angle	0 - 90°
Swivelling	✔
Swivel angle range	0 - 344°
Tilt adjustment	✔
Tilt angle range	-5 - 35°
On Screen Display (OSD)	✔
On Screen Display (OSD) languages	Simplified Chinese, Traditional Chinese, German, English, Spanish, French, Italian, Japanese, Swedish

Power

Energy efficiency class (SDR) *	G
Energy efficiency class (HDR) *	Not available
Energy consumption (SDR) per 1000 hours *	36 kWh
Power consumption (typical) *	34 W
Power consumption (standby) *	0.5 W

Display

DCI-P3 coverage	98%

Performance

NVIDIA G-SYNC *	✘
AMD FreeSync *	✘
Flicker-free technology	✔

Multimedia

Built-in speaker(s) *	✘
Built-in camera *	✘

Design

Market positioning *	Graphics design
Product colour *	Black
Feet colour	Black

Ports & interfaces

Built-in USB hub *	✔
USB hub version	2.0 / 3.2 Gen 1 (3.1 Gen 1)
USB upstream port type	USB Type-B, USB Type-C
Number of USB Type-B upstream ports quantity	1
Number of USB Type-C upstream ports quantity	1
USB Type-A downstream ports quantity	4
USB Type-C DisplayPort Alternate Mode	✔
USB Power Delivery (USB PD)	✔
USB Power Delivery up to	94 W
HDMI *	✔
HDMI ports quantity	1

Power

Power consumption (max)	225 W
AC input voltage	100 - 240 V
AC input frequency	50 - 60 Hz
Energy efficiency scale	A to G
European Product Registry for Energy Labelling (EPREL) code	1216962

Operational conditions

Operating temperature (T-T)	0 - 35 °C
Operating relative humidity (H-H)	20 - 80%

Weight & dimensions

Width (with stand)	638 mm
Depth (with stand)	245 mm
Height (with stand)	415.9 mm
Weight (with stand)	9.8 kg
Width (without stand)	638 mm
Depth (without stand)	86.2 mm
Height (without stand)	390 mm
Weight (without stand)	6.8 kg

Packaging content

Stand included	✔
Cables included	AC, HDMI, USB Type-A to USB Type-B, USB Type-C
Sun hood included	✔
Quick start guide	✔

Other features

Hardware calibration	✔
Built-in calibration sensor	✔
Certification	CB, CE, UKCA, TUV/GS, cTUVus, FCC-B, CAN ICES-3 (B), TUV/S, PSE, VCCI-B, RCM, EAC, RoHS, WEEE, TUV/Ergonomics

4995047063643