

## NEC MultiSync M861 Écran plat de signalisation numérique 2,18 m (86") LCD 500 cd/m<sup>2</sup> 4K Ultra HD Noir 24/7

Marque : NEC

Famille de produit: MultiSync Code produit: 60005067

Nom du produit : M861

NEC MultiSync M861. Conception du produit: Écran plat de signalisation numérique. Taille de l'écran: 2,18 m (86"), Technologie d'affichage: LCD, Résolution de l'écran: 3840 x 2160 pixels, Luminosité de l'écran: 500 cd/m<sup>2</sup>, Type HD: 4K Ultra HD. horaires de service (heures/jours): 24/7. Couleur du produit: Noir



Display		Design	
Panel type	IPS	Panel mounting interface	600 x 400 mm
LED backlight	✓	Bezel width (bottom)	1.48 cm
LED backlighting type	Direct-LED	Bezel width (side)	1.43 cm
Display diagonal *	2.18 m (86")	Bezel width (top)	1.43 cm
Display technology *	LCD	Performance	
Display resolution *	3840 x 2160 pixels	Purpose *	Universal
Display brightness *	500 cd/m <sup>2</sup>	Operating hours (hours/days)	24/7
HD type *	4K Ultra HD	HDCP	✓
Native aspect ratio	16:9	Power	
Response time	8 ms	Power consumption (typical) *	320 W
Contrast ratio (typical)	8000:1	Energy efficiency class (SDR)	G
Display number of colours	1.073 billion colours	Energy consumption (SDR) per 1000 hours	193 kWh
Display diagonal (metric)	217.4 cm	AC input voltage	100 - 240 V
Horizontal scan range	15 - 135 kHz	AC input frequency	50 - 60 Hz
Vertical scan range	23 - 76 Hz	Weight & dimensions	
Haze rate	28%	Width	1927.6 mm
Ports & interfaces		Depth	83.2 mm
HDMI ports quantity *	3	Height	1099.1 mm
HDMI input ports quantity	2	Weight	47 kg
HDMI output ports quantity	1	Packaging data	
DisplayPorts quantity *	2	Package width	2090 mm
DisplayPorts in	2	Package depth	225 mm
DisplayPorts out	1	Package height	1225 mm
USB port *	✓	Package weight	65.1 kg
USB ports quantity	3	Packaging content	
USB version	2.0	Remote control included	✓
Ethernet LAN *	✓	Batteries included	✓
Ethernet LAN data rates	100 Mbit/s	Cables included	HDMI, Power
Audio		Operational conditions	
Built-in speaker(s) *	✓	Operating temperature (T-T)	0 - 40 °C
Number of built-in speakers	2		
RMS rated power	10 W		

Design		Operational conditions	
Product design *	Digital signage flat panel	Operating relative humidity (H-H)	20 - 80%
Orientation	Horizontal/Vertical	Storage temperature (T-T)	-20 - 60 °C
Product colour *	Black	Storage relative humidity (H-H)	10 - 80%
VESA mounting *	✓		



5028695125247

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 05-APR-2025. Prints or copies of Information are only valid on the printed Publication date