



DELL P5524QT Écran plat interactif 139,7 cm (55") LCD 350 cd/m² 4K Ultra HD Noir Écran tactile



Marque : DELL

Code produit: DELL-P5524QT

Nom du produit : P5524QT

- 54.64" 4K UHD 3840 x 2160, IPS
- 8ms, 16:9, 350cd/m², 1200:1
- USB, HDMI, DisplayPort"
54.64" 4K UHD 3840 x 2160, IPS, 16:9, 350 cd/m² 1.07 Billion, 8 ms, 178°/178°, 1200:1

DELL P5524QT Écran plat interactif 139,7 cm (55") LCD 350 cd/m² 4K Ultra HD Noir Écran tactile:

Rassemblez votre équipe, qu'elle soit dans la même pièce ou à distance, avec ce superbe écran de 55" 4K UHD grand format doté de 20 points tactiles, de la fonction sans interférence de la paume, d'une connectivité USB-C et de deux haut-parleurs de 10 W i
DELL P5524QT. Design Produit: Écran plat interactif. Taille de l'écran: 139,7 cm (55"), Technologie d'affichage: LCD, Résolution de l'écran: 3840 x 2160 pixels, Luminosité de l'écran: 350 cd/m², Type HD: 4K Ultra HD, Écran tactile. Couleur du produit: Noir

Display		Design	
Panel type	IPS	Bezel width (top)	4.47 cm
LED backlight	✓	Anti-glare screen	✓
Display diagonal *	139.7 cm (55")	Performance	
Display technology *	LCD	Purpose *	Corporate
Display resolution *	3840 x 2160 pixels	On Screen Display (OSD)	✓
Display brightness *	350 cd/m ²	Power	
HD type *	4K Ultra HD	Power consumption (typical) *	77.1 W
Touchscreen *	✓	Power consumption (standby) *	0.5 W
Number of simultaneous touchpoints	20	Power consumption (off)	0.3 W
Multi-touch	✓	Power consumption (max)	320 W
Native aspect ratio	16:9	Energy efficiency class (SDR)	F
Contrast ratio (typical)	1300:1	Energy efficiency class (HDR)	Not available
Viewing angle, horizontal	178°	Energy consumption (SDR) per 1000 hours	77 kWh
Viewing angle, vertical	178°	AC input voltage	100 - 240 V
Display number of colours	1.07 billion colours	AC input frequency	50/60 Hz
Pixel pitch	0.315 x 0.315 mm	Heat dissipation	263.08 BTU/h
Display diagonal (metric)	138.787 cm	Energy efficiency scale	A to G
Horizontal scan range	30 - 140 kHz	Computer system	
Vertical scan range	24 - 75 Hz	Windows operating systems supported	Windows 7 Professional, Windows 7 Ultimate, Windows 8, Windows 8.1
Supported graphics resolutions	640 x 480 (VGA), 720 x 400, 800 x 600 (SVGA), 1024 x 768 (XGA), 1152 x 864 (XGA+), 1280 x 1024 (SXGA), 1280 x 800, 1600 x 1200, 1920 x 1080 (HD 1080), 2048 x 1152, 2560 x 1440, 3840 x 2160	Mac operating systems supported	Mac OS X 10.10 Yosemite, Mac OS X 10.11 El Capitan
	480p, 576p, 720p, 1080i, 1080p, 2160p	Linux operating systems supported	✓
Supported video modes	480p, 576p, 720p, 1080i, 1080p, 2160p	Weight & dimensions	
Hardness	3H	Display width	1299 mm
Native refresh rate	60 Hz	Display depth	78.7 mm
RGB colour space	NTSC	Display height	769.8 mm
Colour gamut	72%	Display weight	34.3 kg
Ports & interfaces		Packaging data	
HDMI ports quantity *	3	Package weight	41.9 kg
HDMI version	2.0	Packaging content	
DVI port *	✗	Remote control included	✓
DisplayPorts quantity *	1	Stylus pen	✓
USB port *	✓	Number of stylus pens	2
USB ports quantity	8		

Ports & interfaces		Packaging content	
USB version	2.0/3.2 Gen 1 (3.1 Gen 1)	Cables included	DisplayPort, HDMI, USB, USB Type-C
USB connector type	USB Type-A	Operational conditions	
USB 2.0 Type-B ports quantity	3	Operating temperature (T-T)	0 - 40 °C
USB 3.2 Gen 1 (3.1 Gen 1) Type-A ports quantity	4	Operating relative humidity (H-H)	10 - 80%
USB 3.2 Gen 1 (3.1 Gen 1) Type-C ports quantity	1	Storage temperature (T-T)	-20 - 60 °C
USB Power Delivery (USB PD)	✓	Storage relative humidity (H-H)	5 - 90%
USB Power Delivery up to	90 W	Operating altitude	0 - 5000 m
USB Type-C DisplayPort Alternate Mode	✓	Non-operating altitude	0 - 12192 m
Ethernet LAN *	✓	Features	
Ethernet LAN (RJ-45) ports	1	Heat dissipation (max)	1091.89 BTU/h
Wi-Fi *	✗	Technical details	
Audio (L/R) in	1	Sustainability compliance	✓
RS-232 interface	✓	Sustainability certificates	ENERGY STAR
Audio		Doesn't contain	Arsenic, Mercury, PVC/BFR
Built-in speaker(s) *	✓	Compliance certificates	RoHS
Number of built-in speakers	2	Other features	
RMS rated power	20 W	Quick start guide	✓
Speaker impedance	8 Ω	Cable lock slot	✓
Speaker frequency range	120 - 20000 Hz	LED indicators	✓
Design		On/off switch	✓
Product design *	Interactive flat panel	Viewable size, horizontal	121 cm
Placement supported *	Indoor	Viewable size, vertical	68 cm
Product colour *	Black	Power supply type	Internal
Screen shape	Flat	Cable management	✓
VESA mounting *	✓	Response time	9 s
Panel mounting interface	300 x 400 mm	Plug and Play	✓
Bezel width (bottom)	4.47 cm		
Bezel width (side)	4.47 cm		



5397184821534

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 25-JAN-2025. Prints or copies of Information are only valid on the printed Publication date