



TP-Link RE335 Répéteur réseau 867 Mbit/s Blanc

Marque : TP-Link
Code produit: RE335(DE)
Nom du produit : RE335

TP-Link RE335. Maximum data transfer rate: 867 Mbit/s. Antenna design: Interne. Wi-Fi band: Bi-bande (2,4 GHz / 5 GHz), Top Wi-Fi standard: Wi-Fi 5 (802.11ac), WLAN data transfer rate (max): 867 Mbit/s. Ethernet LAN interface type: Fast Ethernet, LAN Ethernet : taux de transfert des données: 10,100 Mbit/s, Standards réseau: IEEE 802.3, IEEE 802.3u. Technologie de connectivité: Avec fil & sans fil



Transmission des données		Sécurité	
Débit de transfert des données maximum *	867 Mbit/s	Sécurité pair Bouton de commande WPS	✓
Antenne		Caractéristiques	
Conception d'antenne	Interne	Type de produit *	Répéteur réseau
Quantité d'antenne	2	Couleur du produit	Blanc
Caractéristiques Wireless LAN		Voyants	✓
Wifi	✓	Voyant LED d'alimentation	✓
Bande Wi-Fi	Bi-bande (2,4 GHz / 5 GHz)	Bouton de réinitialisation	✓
Norme Wi-Fi	Wi-Fi 5 (802.11ac)	Configuration minimale du système	
Débit de transfert des données WLAN (max)	867 Mbit/s	Systèmes d'exploitation compatibles	Microsoft Windows 98SE, NT, 2000, XP, Vista, Windows 7, 8, 8.1, 10, MAC OS, NetWare, UNIX, Linux Internet Explorer 11, Firefox 12.0, Chrome 20.0, Safari 4.0
Force du signal	30 DBm	Puissance	
Sensibilité du récepteur	5 GHz: 11a 6Mbps: -94dBm, 11a 54Mbps: -77dBm 11ac HT20 MCS0: -94dBm, 11ac HT20 MCS8: -71dBm 11ac HT40 MCS0: -92dBm, 11ac HT40 MCS9: -66dBm 11ac HT80 MCS0: -87dBm, 11ac HT80 MCS9: -62dBm 2.4 GHz: 11g 54Mbps: -78dBm, 11n HT20 MCS7: -76dBm 11n HT40 MCS7: -74dBm	Type de source d'alimentation	Secteur
		Tension d'entrée AC	100 - 240 V
Réseau		Fréquence d'entrée AC	50/60 Hz
Ethernet/LAN	✓	Consommation électrique (typicale)	9,5 W
Type d'interface LAN Ethernet	Fast Ethernet	Consommation (max)	9,5 W
LAN Ethernet : taux de transfert des données	10,100 Mbit/s	Certificat	
Standards réseau	IEEE 802.3, IEEE 802.3u	Certificats de conformité	CE, RoHS
Connectivité		Certification	FCC, RoHS
Technologie de connectivité	Avec fil & sans fil	Poids et dimensions	
		Largeur	69,5 mm
		Profondeur	35 mm
		Hauteur	124,1 mm

Connectivité		Contenu de l'emballage	
Nombre de port ethernet LAN (RJ-45)	1	Guide d'installation rapide	✓
Sécurité		Informations sur l'emballage	
Algorithme de sécurité soutenu	64-bit WEP, 128-bit WEP, WPA-PSK, WPA2-PSK	Type d'emballage	Boîte
		Quantité par paquet	1 pièce(s)



4897098681992

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 20-OCT-2024. Prints or copies of Information are only valid on the printed Publication date