Shuttle Nano PC NA10H PC de dimension 1L Noir 8845HS 3,8 GHz

Marque : Shuttle

Nom du produit : Nano PC NA10H7, AMD Ryzen™ 7-8845HS APU, Radeon 780M , 2xHDMI, 2xUSB 4.0 (DP), 2x2.5Gbit LAN, VESA, 24/7

Code produit: NA10H7

AMD Ryzen™ 7-8845HS APU, Radeon 780M , 2xHDMI, 2xUSB 4.0 (DP), 2x2.5Gbit LAN, VESA, 24/7
Shuttle Nano PC NA10H. Type de châssis: PC de dimension 1L, Type de produit: Mini PC type barebone. Type de BIOS: UEFI AMI. Types de mémoire pris en charge: DDR5-SDRAM, Nombre de logements pour mémoire: 2, Mémoire interne maximale: 64 Go. Types de lecteurs de stockage pris en charge: SSD, D'interface pour unité de stockage: PCI Express. Nombre de port ethernet LAN (RJ-45): 2. Type de refroidissement: Actif. Alimentation d'énergie: 120 W

Processor

Processor manufacturer	AMD
Processor family	AMD Ryzen™ 7
Processor generation	AMD Ryzen 8000 Series
Processor model	8845HS
Processor cores	8
Processor threads	16
Processor boost frequency	5.1 GHz
Processor frequency	3.8 GHz
Built-in processor *	✔
L2 cache	8 MB
L3 cache	16 MB
Thermal Design Power (TDP)	45 W

Memory

Memory slots type *	SO-DIMM
Number of memory slots *	2
Maximum internal memory	64 GB
Supported memory clock speeds	5600 MHz
Supported memory types	DDR5-SDRAM
Memory channels	Dual-channel
Memory voltage	1.1 V
Non-ECC	✔

Storage

Supported storage drive types *	SSD
Storage drive sizes supported *	M.2
SSD form factor	M.2
Storage drive interface	PCI Express
NVMe	✔
Card reader integrated	✔
Compatible memory cards	SD

Graphics

On-board graphics card *	✔
Graphics card family	AMD
On-board graphics card model	AMD Radeon 780M
Number of displays supported	4

Ports & interfaces

Ethernet LAN (RJ-45) ports *	2

Design

Chassis type *	1L sized PC
Product colour *	Black
Cooling type *	Active
LED indicators	Power
Housing material	Plastic
Cable lock slot	✔
Cable lock slot type	Kensington
VESA mounting	✔
Panel mounting interface	75 x 75,100 x 100 mm
Product type *	Mini PC barebone

Performance

BIOS type	UEFI AMI
Trusted Platform Module (TPM)	✔
Trusted Platform Module (TPM) version	2.0
Audio chip	Realtek ALC269

Technical details

Compliance certificates	BSMI, CB, CE, Federal Communications Commission (FCC), RoHS, cTUVus

Logistics data

Harmonized System (HS) code	84714900

Software

Windows operating systems supported	Windows 11 x64
Linux operating systems supported	✔

Sustainability

Sustainability certificates	ENERGY STAR, ErP

Power

Power supply type *	External AC adapter
Power supply	120 W

Audio

Built-in speaker(s) *	✘

Network

Ethernet LAN *	✔
Wi-Fi *	✘
LAN controller	Realtek RTL8125B

Ports & interfaces

USB 2.0 ports quantity *	1
USB 3.2 Gen 2 (3.1 Gen 2) Type-A ports quantity	5
USB4 Gen 2x2 ports quantity	2
HDMI ports quantity *	2
HDMI version	2.0
Combo headphone/mic port	✔

Power

Number of power supply units	1
AC input voltage	100 - 240 V
AC input frequency	50/60 Hz
AC adapter output voltage	19 V
AC adapter output current	6.32 A

Operational conditions

Operating temperature (T-T)	0 - 40 °C
Operating relative humidity (H-H)	10 - 90%

Weight & dimensions

Width	132 mm
Depth	143 mm
Height	55 mm
Weight	800 g
Package weight	1.7 kg

Packaging content

Power cord included	✔
AC adapter included	✔
Quick start guide	✔

0887993007403

887993007403