EZVIZ HB8 Sphérique Caméra de sécurité IP Extérieur 2560 x 1440 pixels Plafond/mur

**Marque :** EZVIZ

Code produit: CS-HB8

Nom du produit : HB8

EZVIZ HB8. Type: Caméra de sécurité IP, Installation prise en charge: Extérieur, Technologie de connectivité: Avec fil &sans fil. Type de montage: Plafond/mur, Couleur du produit: Noir, Blanc, Elément de format: Sphérique. Lens viewing angle, horizontal: 83°, Lens viewing angle, vertical: 44°, Lens viewing angle, diagonal: 100°. Type de capteur: CMOS, Taille du capteur optique: 25,4 / 3 mm (1 / 3"). Focale Fixe: 4 mm

Performance

Type *	IP security camera
Placement supported *	Outdoor
Connectivity technology *	Wired & Wireless
PTZ control	✔
Auto-tracking	✔
Day/night mode	✔
Infrared (IR) cut-off filter	✔
Built-in light	✔
Operating frequency	2400 - 24835 MHz

Design

Form factor *	Spherical
Mounting type *	Ceiling/wall
Product colour *	Black, White
Weatherproof	✔

Camera

Camera pan control	✔
Camera tilt control	✔
Minimum illumination	0 lx
Lens viewing angle, horizontal	83°
Lens viewing angle, vertical	44°
Lens viewing angle, diagonal	100°
Tilt angle range	0 - 65°
Pan range	0 - 340°

Image sensor

Number of sensors	1
Optical sensor size	25.4 / 3 mm (1 / 3")
Progressive scan	✔
Sensor type *	CMOS

Lens system

Maximum aperture number	1.6
Fixed focal length	4 mm

Night vision

Night vision *	✔
Night vision distance	15 m
LED type	IR

Network

Ethernet LAN *	✔
Wi-Fi *	✔
Wi-Fi standards	802.11b, 802.11g, Wi-Fi 4 (802.11n)
Wi-Fi data rate (max)	150 Mbit/s
Bluetooth *	✘
Channel bandwidth	20 MHz

Storage

Built-in HDD *	✘
Flash memory	32000 MB

Security

Password protection	✔
Video motion detection	✔
Security algorithms	64-bit WEP, 128-bit WEP, WPA, WPA-PSK, WPA2, WPA2-PSK
Intelligent Video Surveillance (IVS) system features	Human detection
Motion sensor	✔
Motion sensor technology	Passive infrared (PIR) sensor
Anti-flicker	✔
Heartbeat	✔
Digital watermark	✔

Power

Power source type *	Battery
Power consumption (max)	10 W
DC output voltage	5
DC output current	2 A
Battery capacity	10400 mAh

Operational conditions

Operating temperature (T-T)	-20 - 50 °C
Operating relative humidity (H-H)	0 - 95%

Weight & dimensions

Width	186 mm
Depth	166 mm
Height	116 mm
Weight	803 g

Video

Maximum resolution *	2560 x 1440 pixels
Total megapixels *	4 MP
Video compression formats	H.264, H.265
Supported graphics resolutions	2560 x 1440
Frame rate	15 fps
Noise reduction	✔
Noise reduction technology	3D noise reduction
Bit rate	2 Mbps

Audio

Built-in speaker(s)	✔
Built-in microphone	✔
Audio detection	✔

Packaging data

Package width	216 mm
Package depth	145 mm
Package height	203 mm
Package weight	1.06 kg

Sustainability

Sustainability compliance	✔
Compliance certificates	CE, Federal Communications Commission (FCC), REACH, RoHS, WEEE

Packaging content

Number of cameras *	1
Cables included	USB
Screws included	✔
Drilling template included	✔
Manual	✔

6941545609317