



## TP-Link InSight S285 Dôme Caméra de sécurité IP Extérieur 3840 x 2160 pixels Plafond

Marque : TP-Link

Code produit: INSIGHT S285(4MM)

Nom du produit : InSight S285

TP-Link InSight S285. Type: Caméra de sécurité IP, Installation prise en charge: Extérieur, Technologie de connectivité: Avec fil. Type de montage: Plafond, Couleur du produit: Blanc, Élément de format: Dôme. Lens viewing angle, horizontal: 88°, Lens viewing angle, vertical: 46°, Lens viewing angle, diagonal: 105.4°. Type de capteur: CMOS, Taille du capteur optique: 25,4 / 2,7 mm (1 / 2.7"). Detect distance: 107 m, Observe distance: 44 m, Recognize distance: 21 m



Performance		Audio	
Type *	IP security camera	Audio input channels	1 channels
Placement supported *	Outdoor	Audio output channels	1 channels
Connectivity technology *	Wired	Audio formats supported	G.711 A-law
Maximum operating distance	107 m	Sample rate	8 kHz
Wide Dynamic Range (WDR)	✓	Built-in microphone	✓
Day/night mode	✓	Number of microphones	1
Infrared (IR) cut-off filter	✓	Bit rate range	0 - 64 Kbit/s
Remote viewing	✓	<b>Network</b>	
Dynamic range	120 dB	Ethernet LAN *	✓
<b>Design</b>		Networking standards	IEEE 802.3af, IEEE 802.3at TCP/IP, UDP, ICMP, HTTP, HTTPS, DHCP, DNS, RTSP, NTP, UPnP, UDP, SSL/TLS, FTP/SFTP, RTP, IPv4, IPv6, ARP
Form factor *	Dome	Supported network protocols	
Mounting type *	Ceiling	Wi-Fi *	✗
Product colour *	White	Bluetooth *	✗
Housing material	Metal	Live view	✓
Protection features	Waterproof	<b>Storage</b>	
International Protection (IP) code	IP67	Compatible memory cards	MicroSD (TransFlash)
IK code	IK10	Maximum memory card size	512 GB
Weatherproof	✓	<b>Ports &amp; interfaces</b>	
<b>Camera</b>		Ethernet LAN (RJ-45) ports	1
Minimum illumination	0 lx	DC-in jack	✓
Lens viewing angle, horizontal	88°	<b>Security</b>	
Lens viewing angle, vertical	46°	Built-in siren	✓
Lens viewing angle, diagonal	105.4°	Password protection	✓
Tilt angle range	0 - 75°	Video motion detection	✓
Camera shutter speed	1/3 to 1/10000	IP address filtering	✓
<b>Image sensor</b>		HTTPS encryption	✓
Optical sensor size	25.4 / 2.7 mm (1 / 2.7")		
Progressive scan	✓		
Sensor type *	CMOS		

<b>Lens system</b>		<b>Security</b>	
Detect distance	107 m	Detection distance	107 m
Observe distance	44 m	Alert notification type	Push notification
Recognize distance	21 m		Abnormal sound detection, Crossing line, Human detection, Intrusion, Line crossing detection, Moving object, Region entrance detection, Region exiting detection, Scene change, Vehicle detection
Fixed focus	✓	Intelligent Video Surveillance (IVS) system features	
Maximum aperture number	1.6	Motion sensor	✓
Identify distance	11 m	Mirror	✓
Fixed focal length	4 mm	Human and vehicle targets classification	✓
<b>Night vision</b>		Digest authentication	✓
Night vision *	✓	<b>Management features</b>	
LED type	IR/White	Web-based management	✓
<b>Video</b>		Web browser	✓
Maximum resolution *	3840 x 2160 pixels	Cloud-managed *	✓
Total megapixels *	8 MP	Reset button	✓
Video compression formats	H.264, H.264+, H.265, H.265+ 1280 x 720 (HD 720), 1920 x 1080 (HD 1080), 2048 x 1280, 2304 x 1296, 2560 x 1440, 2688 x 1520, 3840 x 2160	<b>Power</b>	
Supported graphics resolutions		Power source type *	DC, PoE
Video recording	✓	Power consumption (max)	11 W
Image quality adjustment	Brightness, Contrast, Mirror, Saturation, Sharpness	Power consumption (Power over Ethernet (PoE))	12.3 W
Bit rate control	Constant Bit Rate (CBR)/Variable Bit Rate (VBR)	DC output voltage	12
Bit rate	Main Stream: 256 Kbps to 8 Mbps, Sub-Stream: 64 Kbps to 512 Kbps	<b>Operational conditions</b>	
Back Light Compensation (BLC)	✓	Operating temperature (T-T)	-30 - 60 °C
Highlight Compensation (HLC)	✓	Storage temperature (T-T)	-40 - 60 °C
Digital Wide Dynamic Range (DWDR)	✓	Operating relative humidity (H-H)	0 - 95%
<b>Audio</b>		Storage relative humidity (H-H)	0 - 95%
Built-in speaker(s)	✓	<b>Weight &amp; dimensions</b>	
Audio system	2-way	Width	122 mm
		Depth	122 mm
		Height	89 mm
		Weight	620 g
		<b>Packaging content</b>	
		Number of cameras *	1
		Manual	✓

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 02-APR-2025. Prints or copies of Information are only valid on the printed Publication date