PHILIPS

Philips 1000 series 24E2N1100LB/00 écran plat de PC 60,5 cm (23.8") 1920 x 1080 pixels Full HD LCD Noir

Marque : Philips Famille de produit: 1000 Code produit: series 24E2N1100LB/00

Nom du produit : 24E2N1100LB/00

Monitor 24E2N1100LB Moniteur LCD Full HD

Philips 1000 series 24E2N1100LB/00 écran plat de PC 60,5 cm (23.8") 1920 x 1080 pixels Full HD LCD Noir:

Ce moniteur intègre de nombreuses fonctionnalités vous permettant de travailler avec une précision absolue. Avec sa résolution Full HD, une fréquence de rafraîchissement de 100 Hz et un MPRT de 1 ms, ce moniteur offre des images détaillées à la définition exceptionnelle.

Philips 1000 series 24E2N1100LB/00. Taille de l'écran: 60,5 cm (23.8"), Résolution de l'écran: 1920 x 1080 pixels, Type HD: Full HD, Technologie d'affichage: LCD, Temps de réponse: 4 ms, Ratio de format d'image: 16:9, Angle de vision horizontal: 178°, Angle de vision vertical: 178°. Montage VESA. Couleur du produit: Noir





Display		Ergonomics	
Display diagonal *	60.5 cm (23.8")	Cable lock slot type	Kensington
Display resolution *	1920 x 1080 pixels	Height adjustment *	×
HD type *	Full HD	Tilt adjustment	✓
Native aspect ratio *	16:9	Tilt angle range	-5 - 20°
Display technology *	LCD	On Screen Display (OSD)	1
Panel type *	VA		Simplified Chinese, Traditional
LED backlight	✓		Chinese, Czech, German, Dutch,
Backlight type	W-LED	On Screen Display (OSD) languages	English, Spanish, Finnish, French, Greek, Hungarian, Italian, Japanese, Korean, Polish, Portuguese, Russian,
Touchscreen *	×		
Display brightness (typical)	250 cd/m²		Swedish, Turkish, Ukrainian
Response time *	4 ms	Number of OSD languages	21
Response time measurement type	GTG (Gray to Gray)	Plug and Play	✓
Response time (MPRT)	1 ms	LED indicators	Operation, Stand-by
Anti-glare screen	✓	Power	
Screen shape *	Flat	Energy efficiency class (SDR) *	E
Contrast ratio (typical) *	4000:1	Energy efficiency class (HDR) *	Not available
Dynamic contrast ratio marketing name	Mega Infinity DCR	Energy consumption (SDR) per 1000 hours *	
Maximum refresh rate *	100 Hz	Power consumption (typical) *	17.7 W
Viewing angle, horizontal	178°	Power consumption (standby) *	0.5 W
Viewing angle, vertical	178°	Power consumption (off)	0.3 W
Display number of colours *	16.7 million colours	AC input voltage	100 - 240 V
Pixel pitch	0.2745 x 0.2745 mm	AC input frequency	50/60 Hz
Pixel density	92.56 ppi	Power supply type	External
Horizontal scan range	30 - 85 kHz	Energy efficiency scale	A to G
Vertical scan range	48 - 60 Hz	Operational conditions	
Viewable size, horizontal	52.7 cm	Operating temperature (T-T)	0 - 40 °C
Viewable size, vertical	29.6 cm 30 - 115 kHz	Storage temperature (T-T)	-20 - 60 °C
Digital horizontal frequency	20 - 113 KHZ	Storage temperature (1-1)	-20 - 00 C

Display		Operational conditions	
Digital vertical frequency	48 - 100 Hz	Operating relative humidity (H-H)	20 - 80%
Sync-on-green (SOG)	✓	Operating altitude	0 - 3658 m
Display diagonal (metric)	60.5 cm	Non-operating altitude	3658 - 12192 m
DDC/CI	✓	Weight & dimensions	
Haze rate	25%	Width (with stand)	541 mm
Surface hardness	3H	Depth (with stand)	126 mm
Display sRGB	✓	Height (with stand)	378 mm
Performance		Weight (with stand)	2.44 kg
NVIDIA G-SYNC *	×	Width (without stand)	541 mm
AMD FreeSync *	×	Depth (without stand)	34 mm
,	Separate sync, Sync-on-green	Height (without stand) Weight (without stand)	322 mm 2.16 kg
Component video sync	(SOG)	-	2.10 kg
Flicker-free technology	✓	Packaging data	
Low Blue Light technology	✓	Package width	610 mm
Multimedia		Package depth	126 mm
Built-in speaker(s) *	×	Package height Package weight	378 mm 4.63 kg
Built-in camera *	X	5 5	4.03 kg
	^	Packaging content	
Design		Cables included	AC, HDMI
Market positioning *	Home	Sustainability	
Product colour *	Black	Doesn't contain	Mercury
Ports & interfaces		Other features	
Built-in USB hub *	×	Exterior finish type	Textured
VGA (D-Sub) ports quantity	1	Picture enhancement	SmartImage
HDMI *	✓	Recyclable packaging material	100%
HDMI ports quantity	1	Bee later Array de	CB, CE Mark, TUV/ISO9241-307,
HDMI version	1.4	Regulatory Approvals	TUV-BAUART, EAC, EAEU RoHS, UKCA, EMF, FCC, ICES-003
HDCP	•	Adaptive synchronisation	✓
HDCP version	1.4	EasyRead mode	1
Ergonomics		LowBlue mode	·
VESA mounting *	✓	Compliance certificates	RoHS
Panel mounting interface	100 x 100 mm	Mean time between failures (MTBF)	
Cable lock slot *	✓	,	



8721038000351

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.