## D-Link DPE-101GI PoE adapter & injector Gigabit Ethernet

Merk : D-Link

Artikelcode: DPE-101GI


Productnaam : DPE-101GI

D-Link DPE-101GI. Ethernet interface type: Gigabit Ethernet, Ethernet LAN, data-overdrachtsnelheden: 10,100,1000 Mbit/s, Bekabelingstechnologie: 10/100/1000. Kleur van het product: Wit, Maximale afstand: 100 m. Output current: 0,4 A, Vermogensverbruik (max): 19,2 W. Certificering: CE FCC VCCI C-Tick IC. Breedte: 62,2 mm, Diepte: 109,8 mm, Hoogte: 24,5 mm





Network		Weight & dimensions	
Ethernet interface type Ethernet LAN data rates	Gigabit Ethernet 10,100,1000 Mbit/s	Weight	65 g
		Packaging content	
Cabling technology Power over Ethernet (PoE)	10/100/1000	Number of products included	1 pc(s)
	IFEE 802 3 IFEE 802 3ab IFEE	Packaging data	
Networking standards		Package width	153 mm
Features		Package depth	213 mm
Product colour	White	Package height Package weight	68 mm 420 g
Wall mountable	1		420 g
Easy to install	<ul> <li>Image: A start of the start of</li></ul>	Logistics data	
Plug and Play	<ul> <li>Image: A set of the set of the</li></ul>	Shipping (inner) case length Shipping (inner) case width Shipping (inner) case height	32.6 cm 23.3 cm
Maximum operating distance	100 m		36 cm
LED indicators	✓	Shipping (inner) case net weight	4.26 kg
Ports & interfaces		Products per shipping (inner) case	10 pc(s)
Ethernet LAN (RJ-45) ports	2	Pallet gross weight (air)	316.4 kg
DC-in jack	✓	Master (outer) cases per pallet (air)	60 pc(s)
Power		Products per pallet (air) Pallet gross length	600 pc(s) 120 cm
Output current	0.4 A	Pallet gross width	110 cm
Power consumption (max)	19.2 W	Pallet height (air)	194 cm
Certificates		Pallet gross weight (sea)	316.4 kg
Certification	CE FCC VCCI C-Tick IC	Master (outer) cases per pallet (sea)	• • • •
Operational conditions		Products per pallet (sea) Pallet height (sea)	600 pc(s) 194 cm
Operating temperature (T-T)	0 - 50 °C	Shipping (inner) case gross weight	4.94 kg
Operating relative humidity (H-H)	10 - 90%	Harmonized System (HS) code	85044095
Storage temperature (T-T)	-20 - 70 °C		
Storage relative humidity (H-H)	5 - 90%		
Weight & dimensions			
Width	62.2 mm 109.8 mm		
Depth Height	24.5 mm		
licight	2.1.5.1111		





790069341335

0790069341335

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.