



D-Link DGS-1016S netwerk-switch Unmanaged Gigabit Ethernet (10/100/1000) Zwart

Merk : D-Link

Artikelcode: DGS-1016S

Productnaam : 16-Port Gigabit Unmanaged Switch



- 16 Gigabit-poorten
- Slank ontwerp voor plaatsing op een tafel of wandmontage
- Plug & Play voor eenvoudige installatie
- Stille werking door fanless ontwerp

16-Port Gigabit Unmanaged Switch

D-Link DGS-1016S. Switch type: Unmanaged. Type basis-switching RJ-45 Ethernet-poorten: Gigabit Ethernet (10/100/1000), Aantal basis-switching RJ-45 Ethernet-poorten: 16. Full duplex. MAC-adrestabel: 8000 entries, Switchingcapaciteit: 32 Gbit/s. Netwerkstandaard: IEEE 802.1p, IEEE 802.3az, IEEE 802.3x. DC voltage input: 12 V

Beheerfuncties		Design	
Switch type *	Unmanaged	Kleur van het product	Zwart
Quality of Service (QoS)	✓	LED-indicatoren	Activiteit, Link, Stroom, Snelheid
Poorten & interfaces		Veiligheid	LVD
Aantal basis-switching RJ-45 Ethernet-poorten *	16	Prestatie	
Type basis-switching RJ-45 Ethernet-poorten *	Gigabit Ethernet (10/100/1000)	Plug and play	✓
Netwerk		Fanloos	✓
Netwerkstandaard *	IEEE 802.1p, IEEE 802.3az, IEEE 802.3x	Mean time between failures (MTBF)	564658 uur
10G support *	✗	Energie	
Koperen ethernetbekabelingstechnologie	1000BASE-T	DC voltage input	12 V
Full duplex	✓	Stroom	1 A
Half-duplex	✓	Vermogensverbruik (max)	8,89 W
Datastroombeheer	✓	Power over Ethernet (PoE)	
Auto MDI/MDI-X	✓	Power over Ethernet (PoE) *	✗
Auto-negotiation	✓	Eisen aan de omgeving	
Kabellengtedetectie	✓	Temperatuur, in bedrijf	0 - 40 °C
Data-uitwisseling		Temperatuur bij opslag	-40 - 70 °C
Switchingcapaciteit *	32 Gbit/s	Relatieve luchtvochtigheid, in bedrijf	10 - 90 procent
MAC-adrestabel *	8000 entries	Luchtvochtigheid bij opslag	5 - 95 procent
Store-and-forward	✓	Warmtedissipatie	30,32 BTU/h
Aantal wachtrijen	8	Gewicht en omvang	
Jumbo Frames ondersteuning	✓	Breedte	280 mm
Jumbo frames	9216	Diepte	110 mm
Packet forwarding rate (1 Gbps)	1488000 pps	Hoogte	25 mm
Packet forwarding rate (100 Mbps)	148800 pps	Gewicht	770 g
Packet forwarding rate (10 Mbps)	14880 pps	Certificaten	
Packet buffergeheugen	0,512 MB	Certificering	CE, FCC, ICES 003, RCM
		Logistics data	
		Code geharmoniseerd systeem (HS) 85176990	



0790069464256



790069464256

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 26-OCT-2024. Prints or copies of Information are only valid on the printed Publication date