

TP-Link Tapo C325WB Kogel (vorm) IP-beveiligingscamera Binnen & buiten 2688 x 1520 Pixels Muur



Merk : TP-Link

Productfamilie: Tapo

Artikelcode: TAP0 C325WB

Productnaam : Tapo C325WB

TP-Link Tapo C325WB. Soort: IP-beveiligingscamera, Ondersteuning voor plaatsing: Binnen & buiten, Connectiviteitstechnologie: Draadloos. Montagewijze: Muur, Kleur van het product: Wit, Vormfactor: Kogel (vorm). Minimale belichting: 0,0005 Lux, Kijkhoek lens, diagonaal: 127°. Type beeldsensor: CMOS, Omvang optische sensor: 25,4 / 1,79 mm (1 / 1.79"). Maximum resolutie: 2688 x 1520 Pixels, Totaal aantal megapixels: 4 MP, Videocompressieformaten: H.264

Performance		Network	
Type *	IP security camera	Networking standards	IEEE 802.11b, IEEE 802.11g, IEEE 802.11n
Placement supported *	Indoor & outdoor	Supported network protocols	TCP/IP, ICMP, DNS, HTTPS, TCP, UDP
Connectivity technology *	Wireless	Wi-Fi *	✓
Certification	CE, FCC, RoHS, RCM	Wi-Fi standards	802.11b, 802.11g, Wi-Fi 4 (802.11n)
Design		Bluetooth *	✗
Form factor *	Bullet	Storage	
Mounting type *	Wall	Built-in HDD *	✗
Product colour *	White	Card reader integrated	✓
LED indicators	✓	Compatible memory cards	MicroSD (TransFlash)
International Protection (IP) code	IP66	Ports & interfaces	
Camera		Ethernet LAN (RJ-45) ports	1
Minimum illumination	0.0005 lx	DC-in jack	✓
Lens viewing angle, diagonal	127°	Security	
Image sensor		Security algorithms	128-bit AES
Number of sensors	1	Power	
Optical sensor size	25.4 / 1.79 mm (1 / 1.79")	Power source type *	DC
Sensor type *	CMOS	AC input voltage	100 - 240 V
Lens system		AC input frequency	50 - 60 Hz
Number of lenses *	1	DC output voltage	9
Night vision		DC output current	0.6 A
Night vision *	✓	Operational conditions	
Video		Operating temperature (T-T)	-20 - 45 °C
Maximum resolution *	2688 x 1520 pixels	Storage temperature (T-T)	-40 - 60 °C
Total megapixels *	4 MP	Operating relative humidity (H-H)	10 - 90%
Video compression formats	H.264	Storage relative humidity (H-H)	5 - 90%
Supported graphics resolutions	2688 x 1520	Weight & dimensions	
Supported video modes	1512p	Width	148.7 mm
Frame rate	20 fps	Depth	137.9 mm
Network		Height	90.4 mm
Ethernet LAN *	✓	Packaging content	
		Number of cameras *	1



4897098685426



0840030705427



840030705427



4897098685433

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.