



i-tec C31FLAT2PDPRO100W laptop dock & poortreplicator Bedraad USB 3.2 Gen 1 (3.1 Gen 1) Type-C Zilver

Merk : i-tec

Artikelcode: C31FLAT2PDPRO100W

Productnaam : USB-C Metal Ergonomic 3x 4K Display Docking Station with Power Delivery 100 W + i-tec Universal Charger 100 W

USB-C Metal Ergonomic 3x 4K Display Docking Station + Power Delivery 100 W
i-tec C31FLAT2PDPRO100W. Connectiviteitstechnologie: Bedraad, Hostinterface: USB 3.2 Gen 1 (3.1 Gen 1) Type-C, USB Power Delivery up to: 100 W. Ethernet LAN, data-overdrachtsnelheden: 10,100,1000 Mbit/s. Kleur van het product: Zilver, Compatibele geheugenkaarten: MicroSD (TransFlash), SD, Overdrachtssnelheid: 5 Gbit/s. Type stroombron: Sector, AC invoer voltage: 100-240 V, AC invoer frequentie: 50-60 Hz. Andere ondersteunende systemen: Android, ChromeOS



Poorten & interfaces		Energie	
Connectiviteitstechnologie *	Bedraad	Stroom	2.3 A
Hostinterface *	USB 3.2 Gen 1 (3.1 Gen 1) Type-C	Spanning	5/9/12/15/19/20 V
Aantal poorten USB 3.2 Gen 1 (3.1 Gen 1) Type A *	4	Output current	5 A
Aantal poorten USB 3.2 Gen 1 (3.1 Gen 1) Type C	1	Vermogensverbruik (max)	100 W
USB Power Delivery	✓	Compatibele soorten stopcontacten	EU
USB Power Delivery tot max.	100 W	USB kabel lengte	0,6 m
Aantal HDMI-poorten *	1	Software	
Aantal DisplayPorts	2	Ondersteunt Windows	✓
Combo koptelefoon/microfoon port	✓	Ondersteunt Mac-besturingssysteem	✓
Type aansluitplug	3,5 mm	Ondersteunt Linux	✓
Netwerk		Andere ondersteunende systemen	Android, ChromeOS
Ethernet LAN *	✓	Eisen aan de omgeving	
Aantal Ethernet LAN (RJ-45)-poorten	1	Temperatuur, in bedrijf	0 - 40 °C
Ethernet LAN, data-overdrachtsnelheden	10,100,1000 Mbit/s	Relatieve luchtvochtigheid, in bedrijf	10 - 100 procent
Prestatie		Gewicht en omvang	
Geïntegreerde geheugenkaartlezer *	✓	Breedte	270 mm
Compatibele geheugenkaarten	MicroSD (TransFlash), SD	Diepte	85 mm
Overdrachtssnelheid	5 Gbit/s	Hoogte	23 mm
Aantal displays ondersteund	3	Gewicht	268 g
Maximale refresh snelheid	60 Hz	Verpakking	
Kleur van het product *	Zilver	Breedte van de verpakking	316 mm
Materiaal behuizing	Aluminium	Diepte van de doos	130 mm
Energie		Hoogte van de verpakking	30 mm
Type stroombron	Sector	Inhoud van de verpakking	
AC invoer voltage	100-240 V	Inclusief AC-adapter	✓
AC invoer frequentie	50-60 Hz	Gebruikershandleiding	✓
		Maximale notebook-schermgrootte compatibiliteit	38,1 cm (15")



8595611706639

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 27-OCT-2024. Prints or copies of Information are only valid on the printed Publication date