



AOC E3 24E3QAF LED display 60,5 cm (23.8") 1920 x 1080 Pixels Full HD LCD Zwart

Merk : AOC

Productfamilie: E3

Artikelcode: 24E3QAF

Productnaam : 24E3QAF

Screen size (inch) 23.8, Panel resolution 1920x1080, Max Refresh rate 75 Hz, Panel type IPS, HDMI HDMI 1.4 x 1, DisplayPort DisplayPort 1.2 x 1, D-SUB (VGA) 1x, DVI 0x, Sync technology (VRR) Adaptive Sync AOC E3 24E3QAF. Beeldschermdiagonaal: 60,5 cm (23.8"), Resolutie: 1920 x 1080 Pixels, HD type: Full HD, Display technologie: LCD, Responstijd: 4 ms, Oorspronkelijke beeldverhouding: 16:9, Kijkhoek, horizontaal: 178°, Kijkhoek, verticaal: 178°. Ingebouwde luidsprekers. VESA-montage, In hoogte verstelbaar. Kleur van het product: Zwart



Display		Ergonomics	
Display diagonal *	60.5 cm (23.8")	Cable lock slot *	✓
Display resolution *	1920 x 1080 pixels	Cable lock slot type	Kensington
HD type *	Full HD	Height adjustment *	✓
Native aspect ratio *	16:9	Adjustable height (max)	15 cm
Display technology *	LCD	Pivot	✓
Panel type *	IPS	Pivot angle	-90 - 90°
LED backlight	✓	Swivelling	✓
Backlight type	W-LED	Swivel angle range	0 - 180°
Touchscreen *	✗	Tilt adjustment	✓
Response time *	4 ms	Tilt angle range	-5 - 35°
Anti-glare screen	✓	On Screen Display (OSD)	✓
Screen shape *	Flat	On Screen Display (OSD) languages	Simplified Chinese, Traditional Chinese, Czech, German, Dutch, English, Spanish, Finnish, French, Italian, Japanese, Korean, Polish, Portuguese, Russian, Swedish
Contrast ratio (typical) *	1000:1	Number of OSD languages	16
Contrast ratio (dynamic)	20000000:1	Plug and Play	✓
Maximum refresh rate *	75 Hz	LED indicators	✓
Viewing angle, horizontal	178°		
Viewing angle, vertical	178°		
Pixel pitch	0.2745 x 0.2745 mm		
Pixel density	93 ppi		
Horizontal scan range	30 - 85 kHz		
Vertical scan range	48 - 75 Hz		
Viewable size, horizontal	52.7 cm		
Viewable size, vertical	29.6 cm		
Digital horizontal frequency	30 - 85 kHz		
Digital vertical frequency	48 - 75 Hz		
Display diagonal (metric)	60.47 cm		
High Dynamic Range (HDR) supported	✓		
DDC/CI	✓		
		Power	
		Power consumption (typical) *	18 W
		Power consumption (standby) *	0.5 W
		Power consumption (max)	35 W
		Power consumption (off)	0.3 W
		AC input voltage	100 - 240 V
		AC input frequency	50/60 Hz
		Input current	1.5 A
		Power supply type	Internal

Display		Operational conditions	
Surface hardness	3H	Operating temperature (T-T)	0 - 40 °C
Performance		Storage temperature (T-T)	-25 - 55 °C
Fast charging	✗	Operating relative humidity (H-H)	10 - 85%
VESA Adaptive Sync support	✓	Storage relative humidity (H-H)	5 - 93%
Flicker-free technology	✓	Operating altitude	0 - 5000 m
Low Blue Light technology	✓	Non-operating altitude	0 - 12192 m
Game mode	✓	Weight & dimensions	
Multimedia		Width (with stand)	540 mm
Number of speakers	2	Depth (with stand)	200.1 mm
Built-in speaker(s) *	✓	Height (with stand)	503.6 mm
Built-in microphone	✗	Weight (with stand)	4.45 kg
Built-in camera *	✗	Width (without stand)	540 mm
Design		Depth (without stand)	50.7 mm
Market positioning *	Office	Height (without stand)	362.3 mm
Product colour *	Black	Weight (without stand)	2.63 kg
Frameless design	✓	Packaging data	
Front bezel colour	Black	Package width	613 mm
Detachable stand	✓	Package depth	162 mm
Feet colour	Black	Package height	519 mm
Ports & interfaces		Package weight	7.14 kg
Built-in USB hub *	✗	Packaging content	
VGA (D-Sub) ports quantity	1	Stand included	✓
HDMI *	✓	Cables included	AC, DisplayPort, HDMI
HDMI ports quantity	1	Quick start guide	✓
HDMI version	1.4	Sustainability	
DisplayPorts quantity	1	Sustainability compliance	✓
DisplayPort version	1.2	Sustainability certificates	EPEAT Silver, TCO
Audio input	✓	Other features	
Headphone out *	✓	FPS counter	✓
Headphone outputs	1	Dial point	✓
Headphone connectivity	3.5 mm	Shadow control	✓
HDCP	✓	Compatibility	VESA-P2
HDCP version	1.4	Exterior finish type	Textured
AC (power) in	✓	Recyclable packaging material	100%
Mobile High-Definition Link (MHL)	✗	Warranty period	3 year(s)
Ergonomics		Compliance certificates	CB, CE, EAC, Federal Communications Commission (FCC), RoHS, cTUVus, WEEE
VESA mounting *	✓	Light effects	✗
Panel mounting interface	100 x 100 mm	Certification	ISO 9241-307
Cable management	✓	Recycling data	
		Post-consumer recycled plastic	85%



4038986141253

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.