

ViewSonic LED DISPLAY TD2430

Key Features

- SuperClear® technologie
- Frameloos ontwerp
- HDMI, DisplayPort en VGA inputs
- 7H hardheid (scherm)
- Ondersteunt Windows® 7/8/10 en diverse Android en Linux versies



Product Description

Dit scherm kan schuin of plat worden geplaatst voor comfort op maat en biedt maximale touchscreen-veelzijdigheid. De ViewSonic® TD2430 biedt fantastische flexibiliteit voor winkel-, onderwijs- of zakelijke markt en is een 24 inch (23,6 inch zichtbaar) Full HD-scherm met 10-punts multi-touch functionaliteit. De TD2430 biedt instelbare positionering, groothoekweergave en een duurzaam ontwerp en heeft alles om aan uw persoonlijke behoeften te voldoen. Cross-compatibiliteit met een breed scala aan besturingssystemen voegt nog meer gemak toe, waaronder Windows 10 en bepaalde Android- en Linux-versies. * Met een gestroomlijnd edge-to-edge scherm en frameloze rand presteert dit intuïtieve touchscreen net als uw favoriete tablet of smartphone om een zeer nauwkeurige, ultra-responsieve aanraakervaring te bieden, ideaal voor interactiviteit in openbare omgevingen, kiosken, bewegwijzeringstoepassingen, klaslokalen etc... * Ondersteunt Windows 7/8/10, Linux 2.6.38 of hoger en Android 4.0 of hoger.



Visit Us - www.viewsonic.com

DISPLAY

Monitor Size:	24"W (23.6" Viewable) LCD monitor
Panel Technology:	VA TFT LCD
Resolution:	Full HD 1920 x 1080
Display Area:	521.28mm (H) x 293.22mm (V)
Aspect Ratio:	16:9
Brightness:	200 cd/m ² (Typ) (with touch module)
Contrast Ratio:	3000:1 (Typ)
Dynamic Contrast Ratio:	50,000,000:1
Viewing Angles:	178 degrees / 178 degrees (Typ)
Panel Surface:	7H Scratch Resistant Surface Hardness
Pixel Size:	0.2715(H) x 0.2715(V)

INPUT SIGNAL

Frequency:	Analog: Fh = 24 ~ 82KHz ; Fv = 50 ~ 75Hz Digital: Fh = 15 ~ 82KHz ; Fv = 24 ~ 75Hz
Sync:	Analog: Separate Sync / Composite Sync / Sync on Green Digital: TMDS, PCI-E

COMPATIBILITY

PC:	Display: Windows 10 certified Touch Module: Windows 7/8/10 supported, Windows 10 certified
Mac®:	Display: Power Mac tested Touch Module: iOS not support
Others:	Linux: Linux 2.6.38 or later version supported, Ubuntu 14.04.13 tested Android: Android 4.0 or later version supported, Android 4.0, Android 5.0 tested

CONNECTOR

Input:	VGA x 1 HDMI x 1 (v1.4 compatible) DisplayPort x 1 (v1.2 compatible)
Output:	Earphone out x 1 (3.5mm plug)

AUDIO

Speaker:	2.5W x 2
----------	----------

USB

Upstream:	USB3.0 Type B x 1
Downstream:	USB3.0 Type A x 2

POWER

Power:	5.5 x 2.5 x 12 mm DC connector
Voltage:	AC 100-240V (Universal); 50/60Hz
Consumption:	25W
Optimise:	22W
Conserve:	19W

ERGONOMICS

Tilt:	20 ± 2 ~ 53 ± 2, 90 (Flat) degrees
-------	---------------------------------------

WALL MOUNT

VESA®:	100mm x 100mm
--------	---------------

OPERATING CONDITIONS

Temperature (° F / ° C):	32°F to 104°F (0°C to 40°C)
Humidity:	20% to 90% (no condensation)

DIMENSIONS (W X H X D) (MM)

Physical with stand (mm):	573mm (W) x 353mm (H) x 47mm (D) (@0 degree) 573mm (W) x 339mm (H) x 147mm (D) (@20 degrees) 573mm (W) x 218mm (H) x 314mm (D) (@55 degrees)
Physical without stand (mm):	573mm (W) x 353mm (H) x 47mm (D)
Packaging (mm):	643mm (W) x 435mm (H) x 140mm (D)

WEIGHT

Net with stand:	5.51kg
Net without stand:	5.51kg
Gross:	7.08kg

REGULATIONS

cTUVus, FCC-B, ICES003, Energy Star 8.0, CEC, MX-CoC, Mexico Energy, CE, CE EMC, CB, RoHS, ErP, REACH, WEEE, EAC, UkrSEPRO, CCC, China RoHS, China Energy Label, CECP

WARRANTY

*Warranty offered may differ from market to market

PACKAGE CONTENTS

LCD Display
AC/DC Adapter
Power Cable (1.5m)
HDMI Cable (1.5m)
USB3.0 Upstream Cable (1.5m)
Audio Cable (1.5m)
Quick Start Guide