## CyberPower PR1000ELCD UPS Line-interactive 1 kVA 900 W 8 ACuitgang(en)

Merk : CyberPower Artikelcode: PR1000ELCD

Productnaam: PR1000ELCD

CyberPower PR1000ELCD. UPS-topologie: Line-interactive, Output power capacity (VA): 1 kVA, Uitgangsvermogen: 900 W. AC outlet types: C13 stekker, Stekker: C14 stekker, Aantal AC uitgangen: 8 AC-uitgang(en). Energie-opslagtechnologie accu/batterij: Sealed Lead Acid (VRLA), Typische backup tijd op volledige lading: 4 min, Typische backup tijd op halve lading: 16 min. Form factor: Tower, Kleur van het product: Zwart, Materiaal behuizing: Metaal. Breedte: 170 mm, Diepte: 432 mm, Hoogte: 221 mm





Features		Battery	
UPS topology * Line-Interactive Output power capacity * 1 kVA Output power * 900 W Waveform * Pure sine Input operation voltage (min) * 151 V Input operation voltage (max) * 301 V Input frequency * 50/60 Hz Output operation voltage (min) 230 V Output operation voltage (max) 230 V Output frequency 50/60 Hz Automatic Voltage Regulation (AVR) ✓	1 kVA	Typical backup time at half load Battery recharge time Hot-swap battery	16 min 8 h ✔
	151 V 301 V 50/60 Hz 230 V 230 V 50/60 Hz	Pesign  Form factor *  Housing material  Product colour *  Display type  LED indicators  Certification	Tower Metal Black LCD Error, Operation CE, EAC, RCM, RoHS
Surge energy rating Response time Power factor EMI/RFI noise filtering Surge protection Power protection features Country of origin	405 J 4 ms 0.9  V Overload China	Operational conditions Operating temperature (T-T) Storage temperature (T-T) Operating relative humidity (H-H) Storage relative humidity (H-H) Operating altitude Non-operating altitude	0 - 40 °C -15 - 45 °C 0 - 95% 0 - 95% 0 - 3000 m 0 - 15000 m
Ports & interfaces  AC outlet types Power plug  AC outlets quantity  Number of output IEC jumpers  USB 2.0 ports quantity  Serial ports quantity	C13 coupler C14 coupler 8 AC outlet(s) 1 1	Weight & dimensions Width Depth Height Weight Package width Package depth	170 mm 432 mm 221 mm 18.9 kg 316 mm 579 mm
Battery Battery technology Number of batteries supported	Sealed Lead Acid (VRLA)	Package height Package weight	360 mm 21.3 kg

Battery		Packaging data	
Typical backup time at full load	4 min	Cables included	USB cable
		Logistics data	
		Harmonized System (HS) code	8504408590
		Other features	
		Compatible operating systems	Windows 7 / Vista / XP / 2000, Server 2003 / 2008, Linux
		Overload protection	✓









Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.