PHILIPS

Philips 5000 series 34B1U5600CH/00 LED display 86,4 cm (34") 3440 x 1440 Pixels Wide Quad HD LCD Zwart

Merk : Philips   **Productfamilie:** 5000 series   **Artikelcode:** 34B1U5600CH/00

Productnaam :
34B1U5600CH/00

Business Monitor 34B1U5600CH Gebogen UltraWide-scherm met USB-C-dock

Philips 5000 series 34B1U5600CH/00 LED display 86,4 cm (34") 3440 x 1440 Pixels Wide Quad HD LCD Zwart:

Deze USB-C-monitor is bedoeld voor het bekijken van video's, gegevensoverdracht en stroomlevering. De geïntegreerde 5 MP-webcam levert scherpe beelden en met de ruisonderdrukkende microfoon bent u altijd goed te horen. Windows Hello Webcam voor snelle toegang en sterke beveiliging. Philips 5000 series 34B1U5600CH/00. Beeldschermdiagonaal: 86,4 cm (34"), Resolutie: 3440 x 1440 Pixels, HD type: Wide Quad HD, Display technologie: LCD, Responstijd: 4 ms, Oorspronkelijke beeldverhouding: 21:9, Kijkhoek, horizontaal: 178°, Kijkhoek, verticaal: 178°. Ingebouwde luidsprekers. Built-in USB hub, USB hub version: 3.2 Gen 2 (3.1 Gen 2). VESA-montage, In hoogte verstelbaar. Kleur van het product: Zwart

Display

Display diagonal *	86.4 cm (34")
Display resolution *	3440 x 1440 pixels
HD type *	Wide Quad HD
Native aspect ratio *	21:9
Display technology *	LCD
Panel type *	VA
Backlight type	W-LED
Touchscreen *	✘
Display brightness (typical)	350 cd/m²
Response time *	4 ms
Anti-glare screen	✔
Screen shape *	Curved
Screen curvature rating	1500R
Contrast ratio (typical) *	3000:1
Contrast ratio (dynamic)	50000000:1
Dynamic contrast ratio marketing name	SmartContrast
Maximum refresh rate *	100 Hz
Viewing angle, horizontal	178°
Viewing angle, vertical	178°
Display number of colours *	16.7 million colours
Pixel pitch	0.23175 x 0.23175 mm
Pixel density	110 ppi
Horizontal scan range	30 - 160 kHz
Vertical scan range	48 - 100 Hz
Viewable size, horizontal	79.7 cm
Viewable size, vertical	33.4 cm
Display diagonal (metric)	86.36 cm
DDC/CI	✔
Haze rate	25%
Surface hardness	3H
Colour depth	8 bit
Colour gamut standard	sRGB
sRGB coverage (typical)	120%
NTSC coverage (typical)	100%

Ergonomics

VESA mounting *	✔
Panel mounting interface	100 x 100 mm
Cable lock slot *	✔
Cable lock slot type	Kensington
Height adjustment *	✔
Height adjustment	18 cm
Swivelling	✔
Swivel angle range	-180 - 180°
Tilt adjustment	✘
Tilt angle range	-5 - 25°
Picture-in-Picture	✔
On Screen Display (OSD) languages	Simplified Chinese, Traditional Chinese, Czech, German, Dutch, English, Spanish, Finnish, French, Greek, Hungarian, Italian, Japanese, Korean, Polish, Portuguese, Russian, Swedish, Turkish, Ukrainian
Plug and Play	✔
LED indicators	Operation, Stand-by

Power

Energy efficiency class (SDR) *	G
Energy consumption (SDR) per 1000 hours *	40 kWh
Power consumption (typical) *	35 W
Power consumption (standby) *	0.3 W
Power consumption (PowerSave)	31 W
AC input voltage	100 - 240 V
AC input frequency	50 - 60 Hz
Power supply type	Internal
Energy efficiency scale	A to G
European Product Registry for Energy Labelling (EPREL) code	1334754

Operational conditions

Operating temperature (T-T)	0 - 40 °C
Storage temperature (T-T)	-20 - 60 °C

Display

Display sRGB	✔

Performance

NVIDIA G-SYNC *	✘
AMD FreeSync *	✘
Fast charging	✔
Fast charging technology	Power Delivery
VESA Adaptive Sync support	✔
Component video sync	Separate sync
Flicker-free technology	✔
Low Blue Light technology	✔

Multimedia

Number of speakers	2
RMS rated power	5 W
Built-in speaker(s) *	✔
Megapixel (approx.)	5 MP
Built-in microphone	✔
Built-in camera *	✔

Design

Market positioning *	Business
Product colour *	Black
Front bezel colour	Black
Feet colour	Black

Ports & interfaces

Built-in USB hub *	✔
USB hub version	3.2 Gen 2 (3.1 Gen 2)
USB upstream port type	USB Type-C
Number of upstream ports	1
USB Type-A downstream ports quantity	4
USB Type-C downstream ports quantity	1
USB Type-C DisplayPort Alternate Mode	✔
USB Power Delivery (USB PD)	✔
USB Power Delivery up to	100 W
HDMI *	✔
HDMI ports quantity	1
HDMI version	2.0
DisplayPorts quantity	1
DisplayPort version	1.4
Headphone out *	✔
Built-in KVM switch	✔
HDCP	✔
HDCP version	1.4/2.2

Network

Ethernet LAN	✔

Operational conditions

Operating relative humidity (H-H)	20 - 80%
Operating altitude	0 - 3658 m
Non-operating altitude	3658 - 12192 m

Weight & dimensions

Width (with stand)	807 mm
Depth (with stand)	250 mm
Height (with stand)	601 mm
Weight (with stand)	11.7 kg
Width (without stand)	807 mm
Depth (without stand)	110 mm
Height (without stand)	367 mm
Weight (without stand)	8.04 kg

Packaging data

Package width	904 mm
Package depth	282 mm
Package height	525 mm
Package weight	15.4 kg

Packaging content

Stand included	✔
Cables included	HDMI, DisplayPort, USB Type-C, AC
Manual	✔
Bundled software	SmartControl

Sustainability

Sustainability compliance	✔
Sustainability certificates	ENERGY STAR, TCO
Doesn't contain	Mercury, PVC/BFR

Other features

HBR3 support	✔
Compatible operating systems	Mac OS X Windows 11 / 10 / 8.1 / 8 / 7
Picture-by-Picture (PbP)	✔
Exterior finish type	Textured
Picture enhancement	SmartImage
Recyclable packaging material	100%
Regulatory Approvals	CB; CE Mark; FCC Class B; ICES-003; CU-EAC; EAEU RoHS; TUV Ergo; TUV/GS; TUV Eye Comfort certified
Delta E	2
Light sensor	✔
EasyRead mode	✔
LowBlue mode	✔
Philips SmartUniformity	93 - 105%
Compliance certificates	RoHS
Mean time between failures (MTBF)	70000 h
Ethernet LAN data rates	10,100,1000 Mbit/s
Wake-on-LAN	✔

Recycling data

Post-consumer recycled plastic	85%

8712581796525