Viewsonic LS751HD beamer/projector Projector met normale projectieafstand 5000 ANSI lumens 1080p (1920x1080) Wit

Merk : Viewsonic

Productnaam : LS751HD

Artikelcode: LS751HD

Viewsonic LS751HD. Projector helderheid: 5000 ANSI lumens, Projector native resolution: 1080p (1920x1080), Typische contrastverhouding: 3000000:1. Type lichtbron: Laser, Levensduur van de lichtbron: 20000 uur, Levensduur van de lichtbron (besparingsmodus): 30000 uur. Focus: Handmatig, Brandpuntbereik: 20.911 - 32.62 mm, Diafragma (F-F): 2,5 - 3,26. Formaat analoog signaal: NTSC, PAL, SECAM, Ondersteunde video-modi: 480i, 480p, 576i, 576p, 720p, 1080i, 1080p, 2160p. Soort serieële aansluiting: RS-232, HDMI-connector type: Volledige grootte, Type onderhoudspoort: USB Type-A

Projector

Smart projector *	✗
Screen size compatibility *	762 - 7620 mm (30 - 300")
Projection distance	0.93 - 14.88 m
Projector brightness *	5000 ANSI lumens
Projector native resolution *	1080p (1920x1080)
Contrast ratio (typical) *	3000000:1
Native aspect ratio *	16:9
Number of colours	1.07 billion colours
Horizontal scan range	15 - 102 kHz
Vertical scan range	23 - 120 Hz
Keystone correction, horizontal	-30 - 30°
Keystone correction, vertical	-30 - 30°

Light source

Light source type *	Laser
Service life of light source *	20000 h
Service life of light source (economic mode)	30000 h

Lens system

Focus *	Manual
Focal length range	20.911 - 32.62 mm
Aperture range (F-F)	2.5 - 3.26
Zoom capability	✔
Zoom type	Manual
Digital zoom	2x
Optical zoom	1.6x
Throw ratio	1.4 - 2.24
Vertical lens shift range	0 - 18%
Offset	136%

Video

Analog signal format system *	NTSC, PAL, SECAM
Full HD *	✔
3D *	✗
Supported video modes	480i, 480p, 576i, 576p, 720p, 1080i, 1080p, 2160p

Ports & interfaces

HDMI connector type	Full-size
HDMI version	2.0
Service port type	USB Type-A

Network

Ethernet LAN (RJ-45) ports	1
Wi-Fi *	✗

Storage

Card reader integrated *	✗

Features

Interactive *	✗
Noise level (economic mode)	29 dB
HDCP	✔
On Screen Display (OSD)	✔
On Screen Display (OSD) languages	Arabic, Simplified Chinese, Traditional Chinese, Czech, Danish, German, Dutch, English, Spanish, Finnish, French, Greek, Hungarian, Indonesian, Italian, Japanese, Korean, Norwegian, Polish, Portuguese, Romanian, Russian, Slovak, Swedish, Thai, Turkish, Vietnamese
Number of OSD languages	27
HDCP version	1.4/2.2
Noise level *	32 dB

Multimedia

Built-in speaker(s) *	✔
RMS rated power	30 W
Number of built-in speakers	2

Design

Market positioning *	Business
Product type *	Standard throw projector
Product colour *	White
Cable lock slot	✔
Cable lock slot type	Kensington

Display

Built-in display *	✗

Power

Power source *	AC
Power consumption (typical) *	245 W
Power consumption (standby) *	0.5 W
AC input voltage	100 - 240 V

Ports & interfaces

USB 2.0 ports quantity	1
USB 2.0 Type-A ports quantity	1
Serial interface type *	RS-232
PC Audio out	✔
HDMI ports quantity *	2
DVI port *	✘
AC (power) in	✔

Network

Smart TV *	✘
Ethernet LAN *	✔

Power

AC input frequency	50 - 60 Hz

Operational conditions

Operating temperature (T-T)	0 - 40 °C

Weight & dimensions

Width	337 mm
Depth	265 mm
Height	131.5 mm
Weight *	4.5 kg
Package width	496 mm
Package depth	195 mm
Package height	387 mm
Package weight	6.6 kg

Packaging content

Remote control included *	✔
Quick start guide	✔
Warranty card	✔

Technical details

Image lag time	49.9 ms

Logistics data

Quantity per pack	1 pc(s)

0766907019940

766907019940