

TP-Link Omada EAP673 WLAN toegangspunt 5400 Mbit/s Wit Power over Ethernet (PoE)

Merk: TP-Link Productfamilie: Omada Artikelcode: EAP673

Productnaam: EAP673

TP-Link Omada EAP673. 2.4 GHz, 5 GHz, Maximum data transfer rate: 5400 Mbit/s. Ondersteunde beveiligingsalgoritmen: SNMP, SNMPv2, SNMPv3, WPA-Enterprise, WPA-Personal, WPA2-Enterprise, WPA2-Personal, WPA3-Enterprise. Ethernet LAN, data-overdrachtsnelheden: 10,100,1000,2500 Mbit/s. Power over Ethernet (PoE). Kleur van het product: Wit






| Features | | Management features | |
|--------------------------------------|--|------------------------------|------------------------|
| 2.4 GHz * | ✓ | Syslog | 1 |
| 5 GHz * | ✓ | Firmware upgradeable | ✓ |
| 6 GHz * | × | Ports & interfaces | |
| Maximum data transfer rate * | 5400 Mbit/s | Ethernet LAN (RJ-45) ports * | 1 |
| Maximum data transfer rate (2.4 GHz) | 574 Mbit/s | DC-in jack | ✓ |
| Maximum data transfer rate (5 GHz) | 4804 Mbit/s | Power | |
| Ethernet LAN data rates | 10,100,1000,2500 Mbit/s | Power over Ethernet (PoE) * | ✓ |
| Frequency band | 2.4 - 5 GHz | DC voltage range | 12 V |
| Networking standards | IEEE 802.11a, IEEE 802.11ac, IEEE 802.11ax, IEEE 802.11b, IEEE | Design | |
| Number of users | 802.11g, IEEE 802.11n 250 user(s) | Placement * Product colour * | Ceiling, Wall White |
| Automatic channel selection | • | Reset button | ✓ |
| Automatic channel scanning | • | LED indicators | ✓ |
| MIMO | • | Antenna | |
| MIMO type | Multi User MIMO | Antenna type * | Internal |
| VLAN support | , | , · | internal |
| Virtual LAN features | VLAN mapping | Weight & dimensions | |
| Rate limiting | ✓ | Width | 220 mm 220 mm |
| Flow control support | ✓ | Depth | 32.5 mm |
| Band steering | ✓ | Height | 32.5 11111 |
| Airtime Fairness (ATF) | ✓ | Packaging content | |
| Quality of Service (QoS) support | ✓ | Quantity per pack | 1 pc(s) |
| BeamForming | ✓ | Mounting kit | ✓ |
| | | Quick start guide | ✓ |

| Security | | Operational conditions | |
|-----------------------|---|---|--------------------------------------|
| Security algorithms * | SNMP, SNMPv2, SNMPv3, WPA- Enterprise, WPA-Personal, WPA2- Enterprise, WPA2-Personal, WPA3- Enterprise | Operating relative humidity (H-H) Operating temperature (T-T) Storage temperature (T-T) | 10 - 90% 0 - 40 °C -40 - 70 °C |
| Management features | | Storage relative humidity (H-H) | 5 - 90% |
| Web-based management | √ | | |









Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.